

# Computer Programs for Calculating the Isentropic Flow Properties for Mixtures of R-134a and Air

*Raymond G. Kvaternik  
Langley Research Center, Hampton, Virginia*

## The NASA STI Program Office ... in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:


- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.
- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or co-sponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results ... even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to [help@sti.nasa.gov](mailto:help@sti.nasa.gov)
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Phone the NASA STI Help Desk at (301) 621-0390
- Write to:  
NASA STI Help Desk  
NASA Center for AeroSpace Information  
7121 Standard Drive  
Hanover, MD 21076-1320

NASA/TM-2000-210622



# Computer Programs for Calculating the Isentropic Flow Properties for Mixtures of R-134a and Air

*Raymond G. Kvaternik*  
*Langley Research Center, Hampton, Virginia*

National Aeronautics and  
Space Administration

Langley Research Center  
Hampton, Virginia 23681-2199

---

November 2000

## Acknowledgments

The author would like to express his thanks to Mr. Renaldo V. Jenkins for helpful discussions related to modifying his SF<sub>6</sub>/air mixture programs to treat mixtures of R-134a and air.

The use of trademarks or names of manufacturers in this report is for accurate reporting and does not constitute an official endorsement, either expressed or implied, of such products or manufacturers by the National Aeronautics and Space Administration.

---

Available from:

NASA Center for AeroSpace Information (CASI)  
7121 Standard Drive  
Hanover, MD 21076-1320  
(301) 621-0390

National Technical Information Service (NTIS)  
5285 Port Royal Road  
Springfield, VA 22161-2171  
(703) 605-6000

## Table of Contents

Abstract .....	1
Nomenclature .....	1
Introduction .....	5
Pertinent Theoretical Considerations for Real Gas Codes .....	6
Computational Procedures for Real Gas Codes .....	11
Program MACHRK.....	12
Program MIXRK.....	14
Governing Equations for Real Gas Model .....	15
Computer Programs.....	19
Development and Verification Procedures.....	19
Real-Gas Codes .....	19
Perfect-Gas Code.....	21
General Comments relevant to Codes .....	22
Specific Comments relevant to Codes.....	23
Program MACHRK.....	23
Program MIXRK.....	23
Program MACHPG .....	23
Illustrative Calculated Flow Properties .....	24
Concluding Remarks .....	25
Appendix A — Theory and Computational Procedure for Mixtures of Thermally Perfect Gases .....	26
Appendix B — Input Format for Programs MACHRK and MACHPG .....	29
Appendix C — Input Format for Program MIXRK.....	30
Appendix D — Sample Input for Programs MACHRK and MACHPG .....	31
Appendix E — Sample Output from Program MACHRK.....	34
Appendix F — Sample Input for Program MIXRK.....	56
Appendix G — Sample Output from Program MIXRK .....	57
Appendix H — Sample Output from Program MACHPG.....	82
References .....	104
Tables .....	107
Figures .....	108

## Abstract

*Three computer programs for calculating the isentropic flow properties of R-134a/air mixtures which were developed in support of the heavy gas conversion of the Langley Transonic Dynamics Tunnel (TDT) from dichlorodifluoromethane (R-12) to 1,1,1,2 tetrafluoroethane (R-134a) are described. The first program calculates the Mach number and the corresponding flow properties when the total temperature, total pressure, static pressure, and mole fraction of R-134a in the mixture are given. The second program calculates tables of isentropic flow properties for a specified set of free-stream Mach numbers given the total pressure, total temperature, and mole fraction of R-134a. Real-gas effects are accounted for in these programs by treating the gases comprising the mixture as both thermally and calorically imperfect. The third program is a specialized version of the first program in which the gases are thermally perfect. It was written to provide a simpler computational alternative to the first program in those cases where real-gas effects are not important. The theory and computational procedures underlying the programs are summarized, the equations used to compute the flow quantities of interest are given, and sample calculated results that encompass the operating conditions of the TDT are shown.*

## Nomenclature

Calculations are done using the International System of units (SI). However, inputs to and outputs from the programs can be in either SI or U.S. Customary units. For those quantities, the U.S. Customary units are given in parentheses after the SI units. Symbols given in parentheses are the names used in the computer programs.

$A(T,V)$		Helmholtz energy, J/kmol
$A/A^*$	(A/ASTAR)	stream tube area ratio
$a_i$	(Ai)	Redlich-Kwong coefficient for ith species, $\frac{0.42748R^2T_{c,i}^{2.5}}{P_{c,i}}$
$a$	(SofS)	speed of sound, m/sec (ft/sec)
$a_{mix}$	(Amix)	Redlich-Kwong coefficient for the mixture, $\left( \sum_{i=1}^n X_i \sqrt{a_i} \right)^2$
$b_i$	(Bi)	Redlich-Kwong coefficient for ith species, $\frac{0.08664RT_{c,i}}{P_{c,i}}$

$b_{mix}$	(Bmix)	Redlich-Kwong coefficient for the mixture, $\sum_{i=1}^n X_i b_i$
$C_p$	(CP)	molar specific heat capacity at constant pressure, J/kmol-K
$C_p/C_v$	(CPCV)	ratio of constant pressure and constant volume heat capacities
$C_p^o$	(Cpo)	ideal heat capacity at constant pressure, J/kmol-K
$C_v$	(CV)	molar specific heat capacity at constant volume, J/kmol-K
$C_v^o$	(Cvo)	ideal heat capacity at constant volume, $C_p^o - R$
$M$	(M)	Mach number, $u/a$
$H(T,V)$	(H)	enthalpy, J/kmol
$S(T,V)$	(S)	entropy, J/kmol-K
$\rho$	(RHO)	density, kg/m <sup>3</sup> (slug/ft <sup>3</sup> )
$\rho_t$	(RHOT)	total (stagnation) density, kg/m <sup>3</sup> (slug/ft <sup>3</sup> )
$\mu$	(MU)	viscosity, N-sec/m <sup>2</sup> (lb-sec/ft <sup>2</sup> )
$R$	(R)	universal gas constant, 8314.34 J/kmol-K
$Re$	(Re)	Reynolds number per meter (per foot)
$P$		pressure, Pa (psf)
$P_{c,i}$		critical pressure for species $i$ , Pa
$P_1$	(P1)	calculated static pressure, Pa (psf)
$V$		specific molar volume, m <sup>3</sup> /kmol (ft <sup>3</sup> /lbm-mol)
$u$	(u,U1)	flow speed, m/s (ft/sec)
$u/u^*$	(U/USTAR)	flow speed ratio
$u^*$	(USTAR)	flow speed at sonic condition (i.e., $M = 1$ )
$V_1$	(V1)	calculated specific molar volume, m <sup>3</sup> /kmol (ft <sup>3</sup> /lbm-mol)

$T_I$	(T1)	calculated static temperature, K (°F)
$P_t$	(Pt)	given (measured) total pressure, Pa (psf)
$P_s$	(Ps)	given (measured) static pressure, Pa (psf)
$P(T,V)$		pressure as a function of temperature and specific volume
$T_t$	(Tt)	given (measured) total temperature, K (°F)
$V_t$	(Vt)	total specific molar volume, m <sup>3</sup> /kmol
$V_I$	(V1)	static specific molar volume, m <sup>3</sup> /kmol
$W$		molecular weight, kg/kmol
$W_{mix}$	(Wmix)	molecular weight of mixture, kg/kmol
$W_{air}$	(Wair)	molecular weight of air, 28.96 kg/kmol
$W_{134a}$	(W134a)	molecular weight of R-134a, 102.03 kg/kmol
$T$	(T)	temperature, K
$T_c$	(Tc)	critical temperature, K
$P_c$	(Pc)	critical pressure, Pa
$T_{c,i}$		critical temperature for species $i$ , K
$X_i$	(Xi)	mole fraction of species $i$ in mixture
$T_{c134a}$	(Tc134a)	critical temperature of R-134a, 374.23 K
$P_{c134a}$	(Pc134a)	critical pressure of R-134a, 4060300 Pa
$X_{134a}$	(X134a)	mole fraction of R-134a in mixture
$X_{air}$	(Xair)	mole fraction of air in mixture
$Z$	(Z)	compressibility factor, $PV/RT$
$\gamma$	(CPCV)	ratio of specific heats, $C_p/C_v$



$q$	(q)	dynamic pressure, Pa (psf)
$k$	(k)	thermal conductivity, J/m-sec-K (ft-lb/ft-sec-°R)
$Pr$	(Pr)	Prandtl number, $\frac{\mu C_p}{k}$
$F$	(F)	pressure function formed from equation of state, $P - f(T, V)$
$\beta$	(BET)	$= \sqrt{ M^2 - 1 }$

#### Subscripts:

$t$	total condition
$s$	static condition
$l$	calculated local static value
$mix$	mixture
$air$	air
$134a$	R-134a
$( )_T$	temperature held constant during differentiation
$( )_V$	volume held constant during differentiation
$c$	critical condition

#### Superscripts:

$( )^\circ$	ideal state
$^\circ ( )$	degrees
$*$	sonic condition ( $M = 1$ )(local velocity equal to local speed of sound)

## Introduction

The Langley Transonic Dynamics Tunnel (TDT) is a closed-loop, continuous-flow, slot-throat wind tunnel having a test section 16-feet square. The tunnel is capable of operation at stagnation pressures from near vacuum to atmospheric and of Mach numbers from zero up to about 1.2. Either air or a heavy gas can be used as a test medium. The tunnel was originally constructed as a 19-foot diameter subsonic pressure tunnel in 1938 (ref. 1). In the late 1950s, the facility was converted to a transonic dynamics tunnel to fill the need for a wind tunnel dedicated to the testing of aeroelastic models of aerospace flight vehicles through transonic speeds. This new aeroelastic testing capability was made possible by using the high-molecular-weight gas dichlorodifluoromethane (R-12, Freon-12) as the test medium (ref. 2). An aerial view of the wind tunnel is shown in figure 1. Since its inception, the TDT has been a unique national facility for testing aeroelastic models of a variety of aircraft, spacecraft, and launch vehicles (see, for example, refs. 3-4). Environmental concerns raised in the late-1980s regarding the continued use of R-12 (a CFC) led to a decision in 1994 to replace it with the environmentally acceptable refrigerant 1,1,1,2-tetrafluoroethane (R-134a, an HFC). Conversion of the TDT heavy gas test medium from R-12 to R-134a was completed in 1997 and is described in references 5-6. Subsequent wind tunnel characterization and calibration tests were completed in 1998.

The equations used at the TDT for computing the flow properties of Freon-air mixtures are summarized in an internal report (*The Langley Transonic Dynamics Wind Tunnel*, LWP-799, September 1969). Those equations were based on polynomial approximations to the rigorous expressions obtained using the Beattie-Bridgeman equation of state for mixtures and the methods described in reference 7. The simplified expressions were designed to give acceptable engineering accuracy for R-12 volume fractions greater than 80-percent without the need to solve the real-gas equations in each calculation cycle. This expedient was employed so that tunnel flow properties could be calculated on-line in as close to real time as possible using the limited computing resources that were available at that time. Today, the flow properties can be computed on-line in essentially real time using the real-gas equations in each calculation cycle and there is no longer a need to resort to such an approximation. A new, state-of-the-art code for computing the flow properties in the TDT for arbitrary mixtures of R-134a and air was therefore deemed appropriate.

At about this time, there was underway at NASA Langley a research program investigating the potential of the heavy gas sulfur hexafluoride ( $\text{SF}_6$ ) to increase the Reynolds number range for aerodynamic testing in transonic wind tunnels (refs. 8-9). Several computer programs for calculating the isentropic flow properties of  $\text{SF}_6$  and  $\text{SF}_6$ /air mixtures were written in support of those studies (refs. 10-12). Examination of the two  $\text{SF}_6$ /air mixture codes (ref. 12) and the theory and analyses underlying those codes (refs. 10-11) indicated that they could be modified to treat R-134a/air mixtures. Thus, the decision was made to modify and extend those analyses and codes where necessary to make them applicable over the range of operating conditions characteristic of the TDT. The primary purpose of this report is to summarize the theoretical and computational considerations that underlie those computer programs.

Three computer programs for calculating the isentropic flow properties of R-134a/air mixtures are described. The first program (MACHRK) calculates the Mach number and the cor-

responding flow properties when the total temperature, total pressure, static pressure, and mole fraction of R-134a in the mixture are given. The program that has been implemented at the TDT for calculating tunnel flow properties is based on this program. The second program (MIXRK) calculates tables of isentropic flow properties for a specified set of free-stream Mach numbers given the total pressure, total temperature, and mole fraction of R-134a. Real-gas effects are accounted for in these programs by treating the gases comprising the mixture as both thermally and calorically imperfect. The Redlich-Kwong equation of state for mixtures and the constant-pressure ideal heat capacity equation for the mixture are used in the departure function approach of thermodynamics to obtain the expressions needed to compute the flow properties. These two programs are modified versions of the aforementioned SF<sub>6</sub>/air mixture programs. The third program (MACHPG) is a specialized version of the first program in which the gases are assumed thermally perfect. It was written to provide a simpler computational alternative to the first program in those cases where real-gas effects are not important. All three programs are written in FORTRAN 77 with the variables, constants, and functions declared double precision where necessary to ensure the 16 significant decimal digits of precision needed for computations on 32-bit machines. The programs have been compiled, linked, and executed using Lahey Computer Systems' Fortran 90 (LF90) compiler (version 4.5) on a Pentium II-class PC with Windows NT 4.0.

The theory and computational procedures underlying the programs are summarized, the equations used to compute the flow quantities of interest are presented, and the development and verification procedures for the real-gas codes are noted. Illustrative results calculated with the programs for a range of input values that encompass the operating conditions of the TDT are shown.

## **Pertinent Theoretical Considerations for Real Gas Codes**

The theoretical basis of the equations implemented in the two real-gas codes is summarized in this section. It is assumed that the gases comprising the mixture are both thermally and calorically imperfect. Both codes are based on the same theory, but there are some differences in the computational aspects (discussed in the next section). The development in this section is intended to be general and independent of any specific equation of state. However, it is assumed that an equation of state relating pressure to temperature and specific volume ( $P=P(T,V)$ ), and an equation relating the ideal heat capacity at constant pressure to temperature ( $C_p^o = C_p^o(T)$ ), are known for the mixture. Only the principal equations and pertinent considerations are presented here. The reader is referred to references 10-12 for a more extensive development and discussion of the theory underlying the equations that are implemented in the real-gas codes and to references 13-18 for detailed treatment of the relevant thermodynamics and gas dynamics. The comparable theory and computational procedure for mixtures of thermally perfect gases is given in Appendix A.

In developing the compressible flow equations for a real gas, there is a need to determine changes in thermodynamic properties between two states that differ in temperature. This is most easily done by first forming isothermal departure functions to reach the ideal-gas state and then varying the temperature in the ideal state. A departure function (ref. 13) is the difference between a thermodynamic quantity in the real state (as specified by  $T$  and  $V$ ) and in an ideal-gas

state at the same  $T$  and at a volume  $V^o$  which is determined from the real pressure ( $P$ ) and temperature ( $T$ ) by  $V^o = RT/P$ . The advantage of varying temperature in an ideal-gas state is that heat capacity expressions for ideal gases ( $C_p^o(T)$  or  $C_v^o(T)$ ) can then be used, and such expressions are known for many gases.  $C_p^o$  and  $C_v^o$  refer to the ideal-gas state where (in the limit) the pressure is zero and the volume is infinite.

Expressions for the departure function forms of the Helmholtz energy  $A$ , entropy  $S$ , and enthalpy  $H$  are needed. For isothermal processes, these expressions can be written as

$$A(T, V) - A^o(T, V^o) = - \int_{\infty}^V \left[ P(T, V) - \frac{RT}{V} \right] dV + RT \ln \frac{V^o}{V} \quad (1)$$

$$S(T, V) - S^o(T, V^o) = \left( \frac{\partial}{\partial T} \right)_V \int_{\infty}^V \left[ P(T, V) - \frac{RT}{V} \right] dV - R \ln \frac{V^o}{V} \quad (2)$$

and

$$\begin{aligned} H(T, V) - H^o(T, V^o) &= A(T, V) - A^o(T, V^o) + PV - RT \\ &\quad + T [S(T, V) - S^o(T, V^o)] \\ &= - \int_{\infty}^V \left[ P(T, V) - \frac{RT}{V} \right] dV + RT \ln \frac{V^o}{V} + PV - RT \\ &\quad + T \left[ \left( \frac{\partial}{\partial T} \right)_V \int_{\infty}^V \left[ P(T, V) - \frac{RT}{V} \right] dV - R \ln \frac{V^o}{V} \right] \end{aligned} \quad (3)$$

Here,  $V^o$  is the specific volume in an ideal state determined from the real pressure  $P$  and the temperature  $T$  by  $V^o = RT/P$ . The departure function form of the Helmholtz energy, entropy, and enthalpy given in equations 1-3 are valid at any temperature and thus can be used to calculate changes in the values of these quantities between any pair of temperatures. The two temperatures of interest here are  $T_1$  and  $T_t$ , the local (free-stream) static and total temperatures, respectively.

The change in the Helmholtz energy between the two temperatures  $T_1$  and  $T_t$  ( $T_t > T_1$ ) is

$$\begin{aligned}
A(T_t, V_t) - A^O(T_t, V_t^O) - [A(T_1, V_1) - A^O(T_1, V_1^O)] \\
= - \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t + RT_t \ln \frac{V_t^O}{V_t} \\
- \left\{ - \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 + RT_1 \ln \frac{V_1^O}{V_1} \right\}
\end{aligned} \tag{4}$$

The change in entropy is

$$\begin{aligned}
S(T_t, V_t) - S^O(T_t, V_t^O) - [S(T_1, V_1) - S^O(T_1, V_1^O)] \\
= \left( \frac{\partial}{\partial T_t} \right)_{\mathcal{N}_t} \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t - R \ln \frac{V_t^O}{V_t} \\
- \left\{ \left( \frac{\partial}{\partial T_1} \right)_{\mathcal{N}_1} \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 - R \ln \frac{V_1^O}{V_1} \right\}
\end{aligned} \tag{5}$$

The change in enthalpy is

$$\begin{aligned}
H(T_t, V_t) - H^O(T_t, V_t^O) - [H(T_1, V_1) - H^O(T_1, V_1^O)] \\
= A(T_t, V_t) - A^O(T_t, V_t^O) + T_t [S(T_t, V_t) - S^O(T_t, V_t^O)] + P_t V_t - RT_t \\
- \left\{ A(T_1, V_1) - A^O(T_1, V_1^O) + T_1 [S(T_1, V_1) - S^O(T_1, V_1^O)] + P_1 V_1 - RT_1 \right\} \\
= - \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t + \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 \\
+ T_t \left( \frac{\partial}{\partial T_t} \right)_{\mathcal{N}_t} \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t \\
- T_1 \left( \frac{\partial}{\partial T_1} \right)_{\mathcal{N}_1} \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 \\
+ P_t V_t - P_1 V_1 - RT_t + RT_1
\end{aligned} \tag{6}$$

Substituting the entropy and enthalpy changes between temperatures  $T_1$  and  $T_t$  for an ideal gas given by

$$S^O(T_t, V_t^O) - S^O(T_1, V_1^O) = \int_{T_1}^{T_t} \frac{C_p^O}{T} dT - R \ln \frac{P_t}{P_1} \tag{7a}$$

and

$$H^o(T_t, V_t^o) - H^o(T_1, V_1^o) = \int_{T_1}^{T_t} C_p^o dT \quad (7b)$$

into equations 5 and 6 yields the final expressions needed for the entropy and enthalpy changes

$$\begin{aligned} \Delta S &= S(T_t, V_t) - S(T_1, V_1) \\ &= \int_{T_1}^{T_t} \frac{C_p^o}{T} dT + \left( \frac{\partial}{\partial T_t} \right)_{V_t} \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t - R \ln \frac{T_t}{V_t} \\ &\quad - \left\{ \left( \frac{\partial}{\partial T_1} \right)_{V_1} \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 - R \ln \frac{T_1}{V_1} \right\} \end{aligned} \quad (8)$$

$$\begin{aligned} \Delta H &= H(T_t, V_t) - H(T_1, V_1) \\ &= \int_{T_1}^{T_t} C_p^o dT - \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t \\ &\quad + \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 + T_t \left( \frac{\partial}{\partial T_t} \right)_{V_t} \int_{\infty}^{V_t} \left[ P_t(T_t, V_t) - \frac{RT_t}{V_t} \right] dV_t \\ &\quad - T_1 \left( \frac{\partial}{\partial T_1} \right)_{V_1} \int_{\infty}^{V_1} \left[ P_1(T_1, V_1) - \frac{RT_1}{V_1} \right] dV_1 + P_t V_t - P_1 V_1 - RT_t + RT_1 \end{aligned} \quad (9)$$

The heat capacities are related to pressure (equation of state) by (see, for example, refs. 13-14)

$$C_p - C_v = \frac{-T(\partial P / \partial T)_V^2}{(\partial P / \partial V)_T} \quad (10)$$

and

$$C_v = C_v^o + T \int_{\infty}^V \left( \frac{\partial^2 P}{\partial T^2} \right) dV \quad (11)$$

Using the ideal gas relation  $C_v^o = C_p^o - R$  in combination with equations 10 and 11 yields

$$C_v = C_p^o - R + T \int_{\infty}^V \left( \frac{\partial^2 P}{\partial T^2} \right) dV \quad (12)$$

so that

$$\begin{aligned} C_p &= C_v - \frac{T(\partial P / \partial T)_V^2}{(\partial P / \partial V)_T} \\ &= C_p^o - R + T \int_{\infty}^V \left( \frac{\partial^2 P}{\partial T^2} \right) dV - \frac{T(\partial P / \partial T)_V^2}{(\partial P / \partial V)_T} \end{aligned} \quad (13)$$

The ratio of specific heats  $\gamma$  then follows as

$$\gamma = \frac{C_p}{C_v} = 1 - \frac{T \left( \frac{\partial P}{\partial T} \right)_V^2 / \left( \frac{\partial P}{\partial V} \right)_T}{C_p^o - R + T \int_{\infty}^V \left( \frac{\partial^2 P}{\partial T^2} \right) dV} \quad (14)$$

The speed of sound is defined by (ref. 18)

$$a = \sqrt{\left( \frac{C_p}{C_v} \right) \left( \frac{\partial P}{\partial \rho} \right)_T} = \sqrt{\gamma \left( \frac{\partial P}{\partial \rho} \right)_T} \quad (15)$$

where  $(\partial P / \partial \rho)_T$  is calculated using

$$\left( \frac{\partial P}{\partial \rho} \right)_T = - \left( \frac{V^2}{W} \right) \left( \frac{\partial P}{\partial V} \right)_T \quad (16)$$

because the equation of state is assumed to be an explicit function of volume  $V$  rather than density  $\rho$ . The above expressions can be easily evaluated given an equation of state relating pressure to temperature and specific volume, and an equation relating the ideal heat capacity at constant pressure to temperature for the gas mixture of interest.

The flow speed  $u$  is given by (ref. 19)

$$u = \sqrt{\frac{2 [H(T_t, V_t) - H(T_1, V_1)]}{W}} = \sqrt{\frac{2 \Delta H}{W}} \quad (17)$$

The Mach number is then

$$M = \frac{u}{a} \quad (18)$$

The density is

$$\rho = \frac{W}{V} \quad (19)$$

Dynamic pressure is

$$q = \frac{1}{2} \rho u^2 \quad (20)$$

Reynolds number (per unit length) is

$$\text{Re} = \frac{\rho u}{\mu} \quad (21)$$

The Prandtl number is

$$\text{Pr} = \frac{\mu C_p}{kW} \quad (22)$$

The deviation of the behavior of a real gas from that of an ideal gas is indicated by the compressibility factor defined by

$$Z = \frac{PV}{RT} \quad (23)$$

$Z$  is unity for an ideal gas. For real gases,  $Z$  is normally less than one, except at high reduced pressures and temperatures (ref. 20).

## Computational Procedures for Real Gas Codes

The development in this section, as in the previous section, is intended to be general and independent of any specific equation of state. However, as before, it is assumed that an equation



of state relating pressure to temperature and specific volume, and an equation relating the ideal heat capacity at constant pressure to temperature are known for the mixture. Again, only principal equations and pertinent considerations are presented here. The reader is referred to references 10-12 for a more extensive development and discussion of the computational procedures that are implemented in the real-gas codes.

### Program MACHRK

A flow chart indicating the primary computational steps in program MACHRK is shown in figure 2. The purpose of this section is to summarize the equations that have been implemented in the code to carry out those computations. See references 10 and 11 for details.

Program MACHRK calculates Mach number and attendant isentropic flow properties given the total temperature, total pressure, static pressure, and mole fraction of R-134a in the mixture by iterating on static temperature and specific volume to match static pressure. It is assumed that an equation of state relating pressure to temperature and specific volume and an equation relating the ideal heat capacity at constant pressure to temperature are known for the gas mixture. In functional equation form, these relationships can be written as

$$P = f_1(T, V) \quad (24)$$

$$C_p^o = f_2(T) \quad (25)$$

For a real gas,  $f_1(T, V)$  will be a nonlinear function of  $T$  and  $V$ , while  $f_2$  will be a nonlinear function of  $T$ .

The required relationships for the changes in entropy and enthalpy for an expansion between temperatures  $T_t$  and  $T_1$  are found by substituting the expressions

$$P_t = f_1(T_t, V_t) \quad (26)$$

$$P_1 = f_1(T_1, V_1) \quad (27)$$

$$C_p^o = f_2(T) \quad (28)$$

into equations 8 and 9 for  $\Delta S$  and  $\Delta H$  and carrying out the indicated operations. The process is made isentropic by setting the resulting entropy expression to zero. This yields a relationship of the form

$$\Delta S = S(T_t, V_t) - S(T_1, V_1) = g[f_1(T_t, V_t), f_1(T_1, V_1), f_2(T)] = 0 \quad (29)$$

The values of  $P_t, T_t, V_t, P_1, T_1$ , and  $V_1$  are needed to compute the flow properties. Substituting the known values of  $P_t$  and  $T_t$  (either given or measured) into the equation of state  $P_t = f_1(T_t, V_t)$ ,  $V_t$  can be determined from the (nonlinear) function

$$F = P_t - f_1(T_t, V_t) = 0 \quad (30)$$

using Newton iteration. Because the total pressure and total temperature  $P_t$  and  $T_t$  are constant,  $F$  is a function of  $V_t$  only and

$$F' = \left( \frac{\partial}{\partial V_t} \right)_{P_t, T_t} [P_t - f_1(T_t, V_t)] \quad (31)$$

The Newton iteration formula for  $V_t$  is then given by

$$V_{t_{i+1}} = V_{t_i} - \frac{F}{F'} = V_{t_i} - \frac{[P_t - f_1(T_t, V_t)]}{\left( \frac{\partial}{\partial V_t} \right)_{P_t, T_t} [P_t - f_1(T_t, V_t)]} \quad (32)$$

where the first guess for  $V_t$  is the ideal gas value  $V_t^0 = RT_t / P_t$ . The iteration process is continued until  $V_{t_{i+1}} = V_{t_i}$  or the difference is sufficiently small, e.g.,  $|V_{t_{i+1}} - V_{t_i}| < 10^{-10}$ .

The quantities  $P_t, T_t$ , and  $V_t$  [(and  $\rho_t = W / V_t$ )] are now known. Substituting the values of  $T_t$  and  $V_t$  into the entropy relationship

$$g[f_1(T_t, V_t), f_1(T_1, V_1), f_2(T)] = 0 \quad (33)$$

given in equation 29 yields a nonlinear equation in  $T_1$  and  $V_1$  which must be solved for  $T_1$  and  $V_1$ . A nested iteration scheme can be used to find the root  $V_1$  if an expansion temperature  $T_1$  is chosen. An initial estimate of  $T_1$  can be obtained from the (modified) ideal-gas equation

$$T_1 = \alpha T_t \left( \frac{P_s}{P_t} \right)^{(\gamma_t - 1) / \gamma_t} \quad (34)$$

where  $\gamma_t$  is the ratio of heat capacities  $C_p / C_v$  calculated at the total conditions with equation 14 and  $\alpha$  is a constant between 0.9 and 1.0, e.g., .95. The Newton iteration formula for  $V_1$  is

$$V_{1_{i+1}} = V_{1_i} - \frac{g[f_1(T_t, V_t), f_1(T_1, V_1), f_2(T)]}{\left(\frac{\partial}{\partial V_1}\right)_{T_t, V_t, T_1} g[f_1(T_t, V_t), f_1(T_1, V_1), f_2(T)]} \quad (35)$$

where  $V_1^0 = RT_1 / P_s$  is taken as the first guess for  $V_1$ . Iteration continues until  $V_{1_{i+1}} = V_{1_i}$  or  $g$  is sufficiently small (e.g.,  $|g| < 10^{-16}$ ), and  $V_1 > V_t$ .

The quantities  $T_1$  and  $V_1$  are now known and  $P_1$  can be calculated from the equation of state,  $P_1 = f_1(T_1, V_1)$ . The calculated value of  $P_1$  is compared with the value of the given (or measured) static pressure  $P_s$ . If the values do not match to within some tolerance (e.g., 1 Pa), the temperature  $T_1$  is varied and the nested iteration process involving  $T_1$  and  $V_1$  described above is repeated until the pressures do match.

The values of  $P_t, T_t, V_t, T_1, V_1$ , and  $P_1$  resulting from the iterative procedures described above are used to evaluate the quantity  $\Delta H = H(T_t, V_t) - H(T_1, V_1)$  given in equation 9. The flow quantities of interest are then calculated using equations 14-23. This procedure is repeated for each  $T_t, P_t, P_s, X_{134a}$  combination specified (or measured).

### Program MIXRK

A flow chart indicating the primary computational steps in program MIXRK is shown in figure 3. The purpose of this section is to summarize the equations that have been implemented in the code to carry out those computations. See references 10 and 12 for details.

Program MIXRK calculates tables of isentropic flow properties given the total temperature, total pressure, and mole fraction of R-134a in the mixture by iterating on static temperature and specific volume to match a specified set of free-stream Mach numbers. As before, it is assumed that an equation of state relating pressure to temperature and specific volume (eq. 24) and an equation relating the ideal heat capacity at constant pressure to temperature (eq. 25) are known for the gas mixture. The program computes the free-stream properties of the gas mixture for an isentropic expansion from given total (stagnation) conditions  $T_t$  and  $P_t$  to a set of specified Mach numbers. The primary output is a table of flow properties similar in form to the subsonic tables of NACA Report 1135 (ref. 19) in which values for  $P/P_t, \rho/\rho_t, T/T_t, q/P_t, \beta, A/A^*$ , and  $u/u^*$  are tabulated as a function of free-stream Mach number.

The computational procedure in MIXRK is considerably different from that in MACHRK because of the need to find the sonic condition, and the fact that the expansions are from total conditions to conditions that correspond to the set of specified free-stream Mach numbers. However, while the computational procedure is different the primary equations needed to implement the procedure are the same as those used in MACHRK. The total specific volume  $V_t$  is

found using equations 30-32. The sonic condition is determined next using equations 33 and 35 in a nested iteration process involving  $T_1$  and  $V_1$ . Once the sonic condition is found, the flow parameters needed for the remainder of the table are calculated. Reference 10 recommends that the values for  $(T/T_t)^*$  and  $(P/P_t)^*$  be recorded the first time that the sonic condition is found for a new gas and that the program be modified to initiate the sonic convergence procedure at  $T_1 = (T/T_t)^* T_t$ ,  $P_1 = (P/P_t)^* P_t$ , and  $V_1 = RT_1/P_1$ . This has been done in program MIXRK.

## Governing Equations for Real Gas Model

Specification of the explicit equations that describe the real gas model used in this report are made in this section. The Redlich-Kwong equation of state for mixtures and the corresponding mixing rules were obtained from reference 20. The nonlinear equation of state relating pressure, temperature, and specific volume is

$$P = \frac{RT}{V - b_{mix}} - \frac{a_{mix}}{V(V + b_{mix})\sqrt{T}} \quad (36)$$

where the coefficients  $a_{mix}$  and  $b_{mix}$  are obtained from the mixing rules

$$a_{mix} = \left( \sum_{i=1}^n X_i \sqrt{a_i} \right)^2 \quad (37)$$

and

$$b_{mix} = \sum_{i=1}^n X_i b_i \quad (38)$$

The coefficients for the individual species comprising the mixture are calculated from the critical temperature  $T_{c,i}$  and the critical pressure  $P_{c,i}$  for each species by using the equations

$$a_i = \frac{0.42748R^2 T_{c,i}^{2.5}}{P_{c,i}} \quad (39a)$$

and

$$b_i = \frac{0.08664RT_{c,i}}{P_{c,i}} \quad (39b)$$

It should be noted that, once  $a_{mix}$  and  $b_{mix}$  are calculated for the mixture, the computations proceed as though  $a_{mix}$  and  $b_{mix}$  were for a pure (single-component) gas.

The critical temperatures and pressures and the Redlich-Kwong coefficients for the constituent gases used in the present work are summarized in table 1. The critical conditions for R-134a were taken from reference 21; the values for the other gases were obtained from reference 20. It should be noted that, for this investigation, air is assumed to be composed of 79% N<sub>2</sub> and 21% O<sub>2</sub>.

The ideal heat capacity at constant pressure for the mixture is given by

$$\begin{aligned} (C_p^o)_{mix} &= \sum_{i=1}^n X_i (C_p^o)_i = X_{134a} (C_p^o)_{134a} + X_{air} (C_p^o)_{dry\ air + water\ vapor} \\ &= X_{134a} (C_p^o)_{134a} + X_{air} [WP_{ratio} (C_p^o)_{water\ vapor} + AP_{ratio} (C_p^o)_{dry\ air}] \end{aligned} \quad (40)$$

where

$$X_{air} = (1 - X_{134a})$$

$$WP_{ratio} = WP / 760$$

$$AP_{ratio} = 1 - WP_{ratio}$$

and  $WP$  is the pressure (in mm of Hg) of any water vapor which may be present in the air.

Expressions for the viscosity and thermal conductivity (refs. 22-23) of gas mixtures are typically obtained from the corresponding expressions for the viscosity and thermal conductivity of the constituent gases by means of mixing rules. A well-known mixing rule for viscosity that is suitable for the present work is given by Wilke (ref. 24). Wilke's equation for the viscosity of a mixture of two gases having viscosities  $\mu_1$  and  $\mu_2$  and molecular weights  $m_1$  and  $m_2$  can be written as:

$$\mu_{mix} = \frac{\mu_1}{1 + \frac{\frac{X_2}{X_1} \left[ 1 + \sqrt{\frac{\mu_1}{\mu_2} \left( \frac{m_2}{m_1} \right)^{1/4}} \right]^2}{\frac{4}{\sqrt{2}} \left( 1 + \frac{m_1}{m_2} \right)^{1/2}}} + \frac{\mu_2}{1 + \frac{\frac{X_1}{X_2} \left[ 1 + \sqrt{\frac{\mu_2}{\mu_1} \left( \frac{m_1}{m_2} \right)^{1/4}} \right]^2}{\frac{4}{\sqrt{2}} \left( 1 + \frac{m_2}{m_1} \right)^{1/2}}} \quad (41)$$

For pressures that are well below the critical pressures of the component gases, viscosities are essentially independent of pressure (density) and a function of temperature alone. A similar mixing rule was recommended by Wilke for the thermal conductivity of a mixture of gases except that the viscosities  $\mu_i$  are replaced by the conductivities  $k_i$ . Wilke's equation for the thermal conductivity of a mixture of two gases having conductivities  $k_1$  and  $k_2$  and molecular weights  $m_1$  and  $m_2$  is then given by:

$$k_{mix} = \frac{k_1}{1 + \frac{\frac{X_2}{X_1} \left[ 1 + \sqrt{\frac{\mu_1}{\mu_2}} \left( \frac{m_2}{m_1} \right)^{1/4} \right]^2}{\frac{4}{\sqrt{2}} \left( 1 + \frac{m_1}{m_2} \right)^{1/2}}} + \frac{k_2}{1 + \frac{\frac{X_1}{X_2} \left[ 1 + \sqrt{\frac{\mu_2}{\mu_1}} \left( \frac{m_1}{m_2} \right)^{1/4} \right]^2}{\frac{4}{\sqrt{2}} \left( 1 + \frac{m_2}{m_1} \right)^{1/2}}} \quad (42)$$

For low reduced pressures, the thermal conductivity is, like viscosity, essentially independent of pressure (density).

The viscosity of air is computed by Sutherland's formula (ref. 19):

$$\mu_{air} = 1.086881879 \times 10^{-6} \frac{(1.8T)^{3/2}}{1.8T + 198.6} \quad \text{N-sec/m}^2 \quad (43)$$

The thermal conductivity of air is given by (ref. 25):

$$k_{air} = \frac{Ak_{air}\sqrt{T}}{1 + \frac{Bk_{air} \times 10^{-5}}{T} - \frac{Ck_{air}}{T}} \quad \text{J/m-sec-K} \quad (44)$$

where

$$Ak_{air} = .00264638$$

$$Bk_{air} = 245.4$$

$$Ck_{air} = 12.$$

Constant-pressure ideal heat capacity equation for R-134a (ref. 21):

$$C_p^o = A_{cp} + B_{cp}T + C_{cp}T^2 + D_{cp}T^3 + E_{cp}/T^2 \quad (45)$$

where

$$A_{cp} = 19400.6$$

$$B_{cp} = 258.531$$

$$C_{cp} = -0.129665$$

$$D_{cp} = 0.0$$

$$E_{cp} = 0.0$$

Constant-pressure ideal heat capacity equation for water vapor (ref. 20):

$$C_p^o = A_{cph2o} + B_{cph2o}T + C_{cph2o}T^2 + D_{cph2o}T^3 \quad (46)$$

where

$$A_{cph2o} = 3.224 \times 10^5$$

$$B_{cph2o} = 1.924$$

$$C_{cph2o} = 1.055 \times 10^{-2}$$

$$D_{cph2o} = -3.596 \times 10^{-6}$$

Constant-pressure ideal heat capacity equation for dry air (ref. 15):

$$C_p^o = A_{cpair} + B_{cpair}T + C_{cpair}T^2 + D_{cpair}T^3 \quad (47)$$

where

$$A_{cpair} = 28110.$$

$$B_{cpair} = -11.091$$

$$C_{cpair} = .004802$$

$$D_{cpair} = -1.966 \times 10^{-6}$$

Viscosity equation for R-134a (ref. 26):

$$\mu_{134a} = A\mu_{134a} + B\mu_{134a}T \quad (48)$$

where

$$A_{mu134a} = 4.8347 \times 10^{-7}$$

$$B_{mu134a} = 3.8599 \times 10^{-8}$$

Thermal conductivity equation for R-134a (ref. 26):

$$k_{134a} = Ak_{134a} + Bk_{134a} T \quad (49)$$

where

$$Ak_{134a} = -.01410$$

$$Bk_{134a} = .000096$$

Vapor pressure equation for R-134a (ref. 21):

$$\log(P_{vp}) = A_{vp} + B_{vp}/T + C_{vp} \log(T) + D_{vp}T + E_{vp}[(F_{vp} - T)/T] \log(F_{vp} - T) \quad (50)$$

where

$$A_{vp} = 4.069889 \times 10^1$$

$$B_{vp} = -2.362540 \times 10^3$$

$$C_{vp} = -1.306883 \times 10^1$$

$$D_{vp} = 7.616005 \times 10^{-3}$$

$$E_{vp} = 2.342564 \times 10^{-1}$$

$$F_{vp} = 3.761111 \times 10^2$$

## Computer Programs

### Development and Verification Procedures

#### *Real-Gas Codes*

The procedures employed for modifying the SF<sub>6</sub>/air mixture codes of reference 12 to treat mixtures of R-134a and air and verifying the operation of the modified codes are described in this section.

The SF<sub>6</sub>/air programs that were modified are called machRK and mixRK in reference 12. These names are retained in the present work except that they are written as MACHRK and



MIXRK, respectively. It should be pointed out that the SF<sub>6</sub>/air programs were tested and verified extensively by their author over a range of operating conditions well beyond (but including) that experienced in the TDT. Thus, the technical integrity of the original programs is well established and they provided a sound starting point for the subject modifications. However, to ensure proper insertion of new code for R-134a into the existing codes, the theoretical, analytical and computational bases of the codes (refs. 10-11) were first thoroughly reviewed. The codes (ref. 12) were then studied to identify the manner in which the relevant analytical and computational operations were encoded. Once this level of understanding of the programs was established, the algebraic manipulations that are implied by equations 8 to 35 were carried out to ensure the ability to reproduce the pertinent SF<sub>6</sub>/air expressions in the codes. These preparatory actions were deemed a necessary first step before proceeding with any serious modifications to the programs. Programs MACHRK and MIXRK were then obtained from their author and executed using the input data sets of reference 12 to demonstrate the ability to replicate the results in reference 12. At this point, modification of the programs could begin with confidence. The modification and verification procedures employed were incremental in that only a few modifications were made at any one time before program execution and replication of previously computed results were demonstrated. During this process, comparisons were also made to known results in the literature when appropriate to verify computed results. Modifications made to the programs are summarized first. This is followed by a summary of the comparisons that were made with results in the literature as part of the program verification process.

A chronological summary of the major modifications made to the original programs follows: All SF<sub>6</sub>-related variable names were changed to reflect R-134a. The option of having input/output quantities in either U.S. Customary units or SI units was introduced. The data and code necessary to treat R-12 were added. This intermediate step was motivated by the recognition that a substantial portion of the new code for R-134a/air mixtures could be validated by comparing with existing results for R-12/air mixtures. Data for R-12 were obtained from references 20, 27-30. After verifying the computed results for both R-12 and R-12/air mixtures, the data and additional code for R-134a were introduced. Data for R-134a were obtained from references 21 and 31. The assumption that air is calorically perfect was relaxed by introducing an expression for  $(C_p^o)_{air}$  which accounts for its variation with temperature (ref. 15). Code for the calculation of thermal conductivity and Prandtl number was added. Where appropriate, names of variables were changed for consistency with added code. Several output quantities were added, deleted, or reformatted. Extraneous code was deleted. Finally, extensive commentary was added throughout the codes.

A number of comparisons were made with numerical results in the literature to verify correct operation of the programs as they were being modified and after modification. These comparisons were made over a range of pressures and temperatures that included the range of values experienced in operations of the TDT. Typically, total pressures ( $P_t$ ) and static pressures ( $P_s$ ) varied from 2200 psf to 50 psf, and stagnation temperatures varied from -20 °F to 140 °F. The comparisons were made for both dynamic (Mach number  $\neq 0$ ) and static (quiescent) conditions. While some of these comparisons exhibited exact agreement, in most cases the agreement was excellent but not exact. However, in the instances in which differences were noted, they could be attributed to the subtle differences among the various gas models.

Substantiation of MACHRK and MIXRK for SF<sub>6</sub>/air computations was demonstrated by reproducing the results shown in reference 12. The results are in exact agreement in this case because the gas models are identical. The programs were then verified for pure air calculations (X134a = 0.0). MACHRK was verified by duplicating the Mach-q curves shown in figure 1c of LWP-799, and by confirming the values of  $\mu$ ,  $k$ ,  $Pr$ , and  $C_p^o$  for air given in tables 2-8, 2-9, 2-10, and 2-11 of reference 25 over the temperature range of interest. The operation of MIXRK was substantiated by introducing temporary code into MIXRK to enforce ideal-gas behavior on air and then reproducing the tabular values in reference 19. Next, the programs were verified for calculations with R-12. MACHRK was verified for pure R-12 computations (X134a = 1.0) by confirming results given for R-12 in references 15 and 29. MIXRK was verified by comparing to results in an unpublished table that was generated during the development of the original R-12/air equations for the TDT. MACHRK was specialized to a 95% R-12/air mixture (X134a = 0.95) and used to duplicate the Mach-q curves shown in figure 1b of LWP-799. Having demonstrated the integrity of the real-gas codes for computations involving either SF<sub>6</sub> or R-12, the final step was to verify the programs for calculations with R-134a. MACHRK was specialized to pure R-134a and used to demonstrate agreement with results given in reference 31. MIXRK was specialized to pure R-134a and its results compared with results obtained from MACHRK at comparable conditions. Because no results for R-134a/air mixtures were found in the literature, no rigorous check of the real-gas codes could be made for such conditions. However, the Mach-q behavior computed for R-134a/air mixtures was always in close agreement with the behavior computed for R-12/air mixtures at comparable conditions. This agreement was expected and was in fact the driving requirement in selecting a replacement heavy gas for R-12. Thus, the computed results were judged correct. Additional credence was given the mixture calculations by comparisons with results obtained from MACHPG, a perfect gas version of MACHRK (see comments in next section).

The real-gas programs contain several places where numerical values are specified either as a threshold (“epsilon”) value used in testing nearness to zero or as part of an expression used to set values for iteration. The values in the original programs were tailored to treat SF<sub>6</sub>/air mixtures over the range of conditions considered in reference 12. However, it was found that the original settings were applicable to R-134a/air mixtures (as well as R-12/air and SF<sub>6</sub>/air) for the range of conditions of interest in the TDT with only a few minor adjustments.

### ***Perfect-Gas Code***

During the course of the many calculations that were made during the verification process for the real-gas codes, it was observed that the compressibility factor  $Z$  tended to be close to unity for many of the conditions analyzed. Because  $Z$  is unity for an ideal gas, this indicated that the behavior of the real gas did not depart markedly from the behavior of an ideal gas at those conditions. This suggested that the “rigor” of a real-gas analysis might not always be required, in which case a perfect-gas code might be sufficient. Program MACHPG was written to serve as a computational alternative to MACHRK in those cases where real-gas effects are not important. It is a new code and was developed in a straightforward manner using well-established equations for dealing with mixtures of perfect gases (see, for example, ref. 14). To allow for variable specific heats, the gases comprising the mixture in MACHPG are assumed calorically imperfect. The theory and computational procedure underlying this code are summarized in Appendix A. Because of the elementary nature of the formulation on which this code is based, the fidelity of

the program can be established on mathematical logic alone. However, for completeness, the program was also verified numerically. Calculated results for pure air and pure R-134a were verified in the same manner as was done for MACHRK, except that the comparisons were made at pressures low enough to ensure essentially ideal-gas behavior. Operation of the program for mixture calculations was verified by comparing the results from MACHPG with comparable low-pressure results from MACHRK.

Because of the lack of definitive data for verifying MACHRK for mixtures of R-134a and air, MACHPG was used to check MACHRK for mixture calculations. This check consisted of comparing results obtained from the two codes over the full range of TDT operating conditions and confirming that the MACHRK results were either the same as or acceptably close to the MACHPG results.

### **General Comments Relevant to Codes**

Programs MACHRK and MIXRK treat mixtures of real gases. MACHPG is a perfect gas version of MACHRK. As mentioned earlier, it was written to provide a simpler computational alternative to MACHRK in those cases where real-gas effects are not important. All three programs are written in FORTRAN 77 with the variables, constants, and functions declared double precision where necessary to ensure the 16 significant decimal digits of precision needed for computations on 32-bit machines. Calculations are done in SI units but input/output quantities can be in either SI or U.S. Customary units. The programs have been compiled, linked, and executed using Lahey Computer Systems' Fortran 90 (LF90) compiler (version 4.5) on a Pentium II-class PC with Windows NT 4.0.

Selection of units (either U.S. Customary or SI) is made in the source code by activating (uncommenting) and deactivating (commenting) the statements `iunits=1` and `iunits=0` as appropriate. Water vapor can be included as part of the air mixture in the real-gas codes by setting the code variable `WP` equal to its vapor pressure expressed in mm of Hg. The  $\text{SF}_6$  and R-12 data that were used in the development and verification of the real-gas codes have been retained in the codes but are deactivated (commented). Retention of the R-12-relevant code in MACHRK provides a backward compatibility with the R-12/air code that was used previously at the TDT.

The names of variables used in the codes are intended to replicate to the extent possible the nomenclature used for the variables in the equations presented in the text. However, because of naming conflicts this has not always been possible. In addition, for convenience, sometimes more than one name is used for the same variable. Although the naming convention is not fully consistent among the three codes, the differences are not extensive and should not cause any confusion.

### **Specific Comments Relevant to Codes**

#### ***Program MACHRK***

Program MACHRK reads total pressure (Pt), static pressure (Ps), total temperature (Tt), and mole fraction of R-134a in the mixture (X134a) from the input file `PsInR-K`. Input can be in either SI or U.S. Customary units. A description of the required input format is given in Ap-

pendix B. The program computes Mach number  $M$ , dynamic pressure  $q$ , velocity  $u$ , static temperature  $T$ , mass density  $\rho$ , ratio of specific heats  $\gamma$ , speed of sound  $a$ , viscosity  $\mu$ , Reynolds number  $Re$ , Prandtl number  $Pr$ , and compressibility factor  $Z$ . Output from the program is written to the file `MOUTR-K`. Because subsequent executions of the program will replace (overwrite) the contents of file `MOUTR-K`, the user must rename the file if the output needs to be saved.

The user has the option of substituting  $SF_6$  or R-12 properties for R-134a. This option is exercised by activating (uncommenting) the appropriate set of statements near the beginning of the code.

The program that has been implemented at the TDT for calculating tunnel flow properties is based on (but not identical to) `MACHRK`. Differences between the two programs are associated primarily with changes that were made to `MACHRK` to have it conform to the open architecture structure of the other tunnel programs at the Langley Research Center.

#### ***Program MIXRK***

Program `MIXRK` reads total pressure ( $P_t$ ), total temperature ( $T_t$ ), and mole fraction of R-134a in the mixture ( $X_{134a}$ ) from the input file `inmix`. Input can be in either SI or U.S. Customary units. The required input format is given in Appendix C. The primary output from the program is a table of isentropic flow properties in the style of the subsonic air table in NACA Report 1135 (ref. 19). This table gives  $P/P_t$ ,  $\rho/\rho_t$ ,  $T/T_t$ ,  $q/P_t$ ,  $\beta$ ,  $A/A^*$ , and  $u/u^*$  as a function of free-stream Mach number. The secondary output includes a number of free-stream or local parameters such as  $T$ ,  $P$ ,  $\gamma$ ,  $a$ ,  $Re$ , and  $Pr$  as a tabular function of the same set of free-stream Mach numbers. The primary output is written to file `outmix6`. The secondary output is written to file `outmix8`. Because subsequent executions of the program will replace (overwrite) the contents of these output files, the user must rename the files if the output needs to be saved.

The user has the option of substituting  $SF_6$  or R-12 properties for R-134a. This option is exercised by activating (uncommenting) the appropriate set of statements near the beginning of the code.

#### ***Program MACHPG***

Program `MACHPG` treats mixtures of R-134a and air only and does not include the option of substituting  $SF_6$  or R-12 properties for R-134a as do the real-gas codes. While the program is based on the assumption of a thermally perfect gas, the gas is assumed calorically imperfect. However, the user has the option to specify that the gases are calorically perfect. This option is selected by activating (uncommenting) the appropriate statements near the beginning of the code. The required input is identical to that of `MACHRK` (see Appendix B). However, for consistency of notation the input file for `MACHPG` is named `PsInPG` rather than `PsInR-K`. Input can be in either SI or U.S. Customary units. `MACHPG` computes the same flow quantities as `MACHRK`, namely: Mach number  $M$ , dynamic pressure  $q$ , velocity  $u$ , static temperature  $T$ , mass density  $\rho$ , specific heat ratio  $\gamma$ , speed of sound  $a$ , viscosity  $\mu$ , Reynolds number  $Re$ , and Prandtl number  $Pr$ . Output from the program is written to the file `MOUTPG`. As for the other codes, because subsequent executions of the program will replace the contents of file `MOUTPG` the user must rename the file if the output needs to be saved.

## Illustrative Calculated Flow Properties

Flow properties calculated using each of the three programs described in this report are presented in this section. Emphasis is on results obtained with the real-gas codes. In each case, the set of values used for the input quantities  $P_t$ ,  $P_s$ ,  $T_t$ , and  $X_{134a}$  includes combinations that encompass values experienced in typical operations of the TDT. It should be emphasized that the results shown are for illustrative purposes only and are not intended to be the definitive curves characterizing the TDT. To be consistent with the units of measurement and display employed at the TDT, the numerical results presented are in U.S. Customary units.

The primary “working curves” used by test engineers at the TDT during an actual test are calculated plots of dynamic pressure versus Mach number (so-called “Mach-q curves”) for various constant total pressures and a fixed value of total temperature. These curves extend to the operating boundaries of the tunnel as defined by either tunnel structural design limits or drive motor power limits. A number of ancillary working curves have also been found useful for estimating other flow properties (see LWP-799). Several of these types of curves are presented here as part of the illustrative results.

Mach-q curves for air computed by program MACHRK assuming pure air ( $X_{134a} = 0.0$ ) and a total temperature of 100 °F are given in figure 4. These curves are equivalent to the air curves shown in LWP-799. For heavy gas testing, a 95-percent R-134a/air mixture ( $X_{134a} = .95$ ) and a total temperature of 100 °F are representative of the average conditions in many tests. Unless noted otherwise, these values were used for calculating the mixture flow properties shown in this report. Mach-q curves for R-134a/air computed by MACHRK are shown in figure 5. The associated input and output data are given in Appendices G and H, respectively. Comparison of these curves with those shown for R-12/air in LWP-799 shows considerable similarity, as was expected since R-134a and R-12 have comparable properties. Program MACHRK was also used to compute the data needed to generate the curves presented in figures 6-12. The variation of density with static pressure for several fixed values of static temperature is given in figure 6. Figure 7 shows the variation of speed of sound with static temperature for three values of static pressure. The variations with static temperature of viscosity and thermal conductivity are shown in figures 8 and 9, respectively. Figure 10 illustrates the variation of Reynolds number with Mach number for several combinations of constant static pressure and total temperature. The variation of static temperature with Mach number for a series of total temperatures ranging from 0 °F to 120 °F is shown in figure 11. A carpet-type plot portraying the variation of the ratio of specific heats with speed of sound for several combinations of static temperature and R-134a volume fraction is given in figure 12.

The variations of  $P/P_t$ ,  $q/P_t$ ,  $T/T_t$ , and  $\rho/\rho_t$  with Mach number were computed by MIXRK using the input data given in Appendix I. The calculated results are presented in Appendix J and the corresponding curves are shown in figure 13.

Results computed with MACHPG using the same input data that were used for MACHRK (Appendix D) are shown in Appendix H. A comparison of the flow parameters calculated using the perfect gas equations (Appendix H) with the values calculated using MACHRK (Appendix E) indicates considerable agreement. This suggests that, depending on the range of

conditions considered, the results obtained using a perfect-gas code can be an acceptable approximation to the results obtained with a real-gas code.

## **Concluding Remarks**

Three computer programs for calculating the isentropic flow properties of R-134a/air mixtures which were developed in support of the heavy gas conversion of the Langley Transonic Dynamics Tunnel (TDT) from dichlorodifluoromethane (R-12) to 1,1,1,2 tetrafluoroethane (R-134a) have been described. The first program (MACHRK) calculates the Mach number and the corresponding flow properties when the total temperature, total pressure, static pressure, and mole fraction of R-134a in the mixture are given. The second program (MIXRK) calculates tables of isentropic flow properties as a function of a specified set of free-stream Mach numbers given the total pressure, total temperature, and mole fraction of R-134a. Real-gas effects are accounted for in these programs by treating the gases comprising the mixture as both thermally and calorically imperfect. The Redlich-Kwong equation of state for mixtures and the constant-pressure ideal heat capacity equation for the mixture are used in combination with the departure function approach of thermodynamics to obtain the expressions needed to compute the flow properties. These two programs are modified versions of programs that were developed earlier at Langley for a different heavy gas as part of another (unrelated) investigation. The third program (MACHPG) is a specialized version of the first program in which the gases are thermally perfect. It was written to provide a simpler computational alternative to the first program in those cases where real-gas effects are not important.

The theory and computational procedures underlying the programs were summarized, the equations used to compute the flow quantities of interest were presented, and the development and verification procedures were noted. Illustrative results calculated with the programs for a range of input values that encompass the operating conditions of the TDT were also shown. These results indicate (confirm) that the primary flow characteristics of the TDT for R-134a/air operations are not much different from those for R-12/air, as was expected. The programs have supported a number of activities associated with the heavy gas conversion of the TDT from R-12 to R-134a. In particular, program MACHRK is the basis of the program that has been implemented at the TDT for calculating tunnel flow properties.

NASA Langley Research Center  
Hampton, VA 23681-2199  
November 1, 2000

## Appendix A

### Theory and Computational Procedure for Mixtures of Thermally Perfect Gases

The assumption of a perfect gas is often a reasonable approximation in aeronautical applications. Indeed, air at standard conditions behaves very much like an ideal gas. The theory and computational procedure for a program in which the gases comprising the mixture are thermally perfect but calorically imperfect are summarized here. This new program (MACHPG) was written to provide a simpler computational alternative to MACHRK in those cases where real-gas effects are not important. A code for computing tables of isentropic flow properties like program MIXRK but for mixtures of thermally perfect gases is described in reference 32.

#### Theory

The equation of state for mixtures of thermally perfect gases can be written as

$$P = \frac{R_{mix}T}{V} \quad (A1)$$

or

$$P = \rho R_{mix}T \quad (A2)$$

where  $P$  is the pressure (Pa),  $R_{mix}$  is the gas constant (J/kg-K),  $V$  is the specific volume ( $\text{m}^3/\text{kg}$ ),  $T$  is the absolute temperature (in degrees K), and  $\rho$  is the mass density ( $\text{kg}/\text{m}^3$ ). The gas constant for the mixture is given by

$$R_{mix} = \frac{R}{W_{mix}} \quad (A3)$$

where the average molecular weight of a two-component (R-134a and air) mixture is given by

$$W_{mix} = \sum_{i=1}^2 X_i W_i \quad (A4)$$

and

$$X_{air} = 1 - X_{134a} \quad (A5)$$

The equations for  $\mu_{air}$ ,  $\mu_{134a}$ ,  $k_{air}$ ,  $k_{134a}$ ,  $C_{p134a}^o$ , and  $C_{p_{air}}^o$  are the same as those used in the real-gas model.

### Computational Procedure

Given  $T_t$ ,  $P_t$ , and  $P_s$ , compute an initial estimate for  $\gamma_{mix}$  by substituting  $\gamma_{air} = 1.4$  and  $\gamma_{134a} = 1.11$  into the relation (ref. 16)

$$\gamma_{mix} = 1 - \frac{(1 - \gamma_{134a})(1 - \gamma_{air})}{X_{134a}(1 - \gamma_{air}) + (1 - X_{134a})(1 - \gamma_{134a})} \quad (A6)$$

Compute an initial estimate of  $T_s$  for the mixture using the ideal-gas relationship

$$T_s = T_t \left( \frac{P_s}{P_t} \right)^{\frac{\gamma_{mix} - 1}{\gamma_{mix}}} \quad (A7)$$

Compute new values of  $\gamma_{134a}$  and  $\gamma_{air}$ . These are obtained by using equations 45 and 47 to first compute  $C_{P_{134a}}^o$  and  $C_{P_{air}}^o$  at the temperature  $T_s$  obtained from equation A7 and then calculating  $\gamma_{air}$  and  $\gamma_{134a}$  using

$$\gamma_{air} = \frac{C_{P_{air}}^o}{C_{v_{air}}^o} = \frac{C_{P_{air}}^o}{C_{P_{air}}^o - R} \quad (A8a)$$

$$\gamma_{134a} = \frac{C_{P_{134a}}^o}{C_{v_{134a}}^o} = \frac{C_{P_{134a}}^o}{C_{P_{134a}}^o - R} \quad (A8b)$$

Compute a new value of  $\gamma_{mix}$  using equation A6. Repeat the procedure until convergence is attained (usually two cycles).

The values for speed of sound, Mach number, velocity, dynamic pressure, and density of the mixture then follow as:

$$a = \sqrt{\gamma_{mix} R_{mix} T_s} \quad (A9)$$



$$M = \sqrt{\frac{2}{\gamma_{mix} - 1} \left( \frac{T_t}{T_s} - 1 \right)} \quad (\text{A10})$$

$$u = M a \quad (\text{A11})$$

$$q = \frac{1}{2} \gamma_{mix} P_s M^2 \quad (\text{A12})$$

$$\rho = \frac{P_s}{R_{mix} T_s} \quad (\text{A13})$$

Compute  $\mu$  and  $k$  for air and R-134a with equations 43, 44, 48, and 49 using the value of  $T_s$  computed above. Then compute  $\mu$  and  $k$  for the mixture using Wilke's formulas as given in equations 41 and 42. The Reynolds number per unit length for the mixture is then

$$\text{Re} = \frac{\rho_{mix} u}{\mu_{mix}} \quad (\text{A14})$$

and the Prandtl number is

$$\text{Pr} = \left( \frac{\mu C_p}{kW} \right)_{mix} \quad (\text{A15})$$

where  $C_p$  for the mixture is obtained from the relation

$$C_{p_{mix}} = \frac{\gamma_{mix} R}{\gamma_{mix} - 1} \quad (\text{A16})$$

## Appendix B

### Input Format for Programs MACHRK and MACHPG

The input can be in either U.S. Customary units or SI units and is entered as follows:

Line	Format	Columns	Given or measured quantity
1	E10.3	1 to 10	Total temperature (Tt), °F or °K
	E10.3	11 to 20	Total pressure (Pt), lb/ft <sup>2</sup> or Pa
	E10.3	21 to 30	Static pressure (Ps), lb/ft <sup>2</sup> or Pa
	E10.3	31 to 40	Mole fraction of R-134a, (0.0 ≤ X134a ≤ 1.0)
2			Multiple cases can be run by furnishing values for Tt, Pt, Ps, and X134a as in line 1 for n cases
.	.	.	.
.	.	.	.
.	.	.	.
.	.	.	.
.	.	.	.
n			Line is for nth case
The read is terminated by an EOF check inside the program			

## Appendix C

### Input Format for Program MIXRK

The input can be in either U.S. Customary units or SI units and is entered as follows:

Line	Format	Columns	Given or measured quantity
1	E10.3	1 to 10	Total temperature (Tt), °F or °K
	E10.3	11 to 20	Total pressure (Pt), lb/ft <sup>2</sup> or Pa
	E10.3	21 to 30	Mole fraction of R-134a, ( $0.0 \leq X_{134a} \leq 1.0$ )
2			Multiple cases can be run by furnishing values for Tt, Pt, and X <sub>134a</sub> as in line 1 for n cases
.	.	.	.
.	.	.	.
.	.	.	.
.	.	.	.
.	.	.	.
n			Line is for nth case
The read is terminated by an EOF check inside the program			

## Appendix D

### Sample Input for Programs MACHRK and MACHPG

(U.S. Customary units)

100.	2200.	2200.	.95
100.	2200.	2198.	.95
100.	2200.	2196.	.95
100.	2200.	2194.	.95
100.	2200.	2192.	.95
100.	2200.	2190.	.95
100.	2220.	2180.	.95
100.	2220.	2160.	.95
100.	2220.	2140.	.95
100.	2220.	2120.	.95
100.	2200.	2100.	.95
100.	2200.	2080.	.95
100.	2200.	2060.	.95
100.	2200.	2040.	.95
100.	2200.	2020.	.95
100.	2200.	2000.	.95
100.	2200.	1980.	.95
100.	2200.	1960.	.95
100.	2200.	1940.	.95
100.	2200.	1920.	.95
100.	2200.	1900.	.95
100.	2200.	1800.	.95
100.	2200.	1700.	.95
100.	2200.	1600.	.95
100.	2200.	1500.	.95
100.	2200.	1400.	.95
100.	2200.	1300.	.95
100.	2200.	1200.	.95
100.	2200.	1150.	.95
100.	2200.	1100.	.95
100.	2200.	1050.	.95
100.	2200.	1000.	.95
100.	2200.	950.	.95
100.	2200.	900.	.95
100.	2200.	850.	.95
100.	2200.	800.	.95
100.	1000.	1000.	.95
100.	1000.	999.5	.95
100.	1000.	999.	.95
100.	1000.	998.5	.95
100.	1000.	998.	.95
100.	1000.	996.	.95
100.	1000.	994.	.95
100.	1000.	992.	.95
100.	1000.	990.	.95
100.	1000.	988.	.95
100.	1000.	986.	.95
100.	1000.	984.	.95
100.	1000.	982.	.95
100.	1000.	980.	.95
100.	1000.	960.	.95
100.	1000.	940.	.95
100.	1000.	920.	.95
100.	1000.	900.	.95
100.	1000.	880.	.95
100.	1000.	860.	.95

100.	1000.	840.	.95
100.	1000.	820.	.95
100.	1000.	800.	.95
100.	1000.	780.	.95
100.	1000.	760.	.95
100.	1000.	740.	.95
100.	1000.	720.	.95
100.	1000.	700.	.95
100.	1000.	680.	.95
100.	1000.	660.	.95
100.	1000.	640.	.95
100.	1000.	620.	.95
100.	1000.	600.	.95
100.	1000.	580.	.95
100.	1000.	560.	.95
100.	1000.	540.	.95
100.	1000.	520.	.95
100.	1000.	500.	.95
100.	1000.	450.	.95
100.	1000.	400.	.95
100.	1000.	350.	.95
100.	1000.	300.	.95
100.	500.	500.	.95
100.	500.	490.	.95
100.	500.	480.	.95
100.	500.	470.	.95
100.	500.	460.	.95
100.	500.	450.	.95
100.	500.	440.	.95
100.	500.	430.	.95
100.	500.	420.	.95
100.	500.	410.	.95
100.	500.	400.	.95
100.	500.	390.	.95
100.	500.	380.	.95
100.	500.	370.	.95
100.	500.	360.	.95
100.	500.	350.	.95
100.	500.	340.	.95
100.	500.	330.	.95
100.	500.	320.	.95
100.	500.	310.	.95
100.	500.	300.	.95
100.	500.	280.	.95
100.	500.	270.	.95
100.	500.	260.	.95
100.	500.	240.	.95
100.	500.	220.	.95
100.	500.	200.	.95
100.	500.	180.	.95
100.	500.	160.	.95
100.	500.	140.	.95
100.	500.	120.	.95
100.	500.	100.	.95
100.	200.	200.	.95
100.	200.	190.	.95
100.	200.	180.	.95
100.	200.	170.	.95
100.	200.	160.	.95
100.	200.	150.	.95
100.	200.	140.	.95
100.	200.	130.	.95
100.	200.	120.	.95
100.	200.	110.	.95

100.	200.	100.	.95
100.	200.	90.	.95
100.	200.	80.	.95
100.	200.	70.	.95
100.	200.	60.	.95
100.	200.	50.	.95
100.	200.	40.	.95
100.	200.	30.	.95
100.	200.	20.	.95
100.	200.	10.	.95
100.	200.	5.	.95
100.	100.	100.	.95
100.	100.	98.	.95
100.	100.	96.	.95
100.	100.	94.	.95
100.	100.	92.	.95
100.	100.	90.	.95
100.	100.	88.	.95
100.	100.	86.	.95
100.	100.	84.	.95
100.	100.	82.	.95
100.	100.	80.	.95
100.	100.	78.	.95
100.	100.	76.	.95
100.	100.	74.	.95
100.	100.	72.	.95
100.	100.	70.	.95
100.	100.	65.	.95
100.	100.	60.	.95
100.	100.	55.	.95
100.	100.	50.	.95
100.	100.	45.	.95
100.	100.	40.	.95
100.	100.	35.	.95
100.	100.	30.	.95
100.	50.	40.	.95
100.	50.	39.	.95
100.	50.	38.	.95
100.	50.	37.	.95
100.	50.	36.	.95
100.	50.	35.	.95
100.	50.	34.	.95
100.	50.	33.	.95
100.	50.	32.	.95
100.	50.	31.	.95
100.	50.	30.	.95
100.	50.	28.	.95
100.	50.	26.	.95
100.	50.	24.	.95
100.	50.	22.	.95
100.	50.	20.	.95

## Appendix E

### Sample Output from Program MACHRK

```

=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2200.0           2200.0           100.0         0.007888              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.0000    0.00           0.01         0.7888E-02           2200.0          100.0

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.69       0.2641E-06          1.115    0.2225E+03        0.681    0.9861
=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2200.0           2198.0           100.0         0.007888              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.0408    2.01           22.57         0.7882E-02           2198.0          99.9

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.67       0.2641E-06          1.115    0.6734E+06        0.681    0.9861
=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2200.0           2196.0           100.0         0.007888              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.0575    3.98           31.81         0.7875E-02           2196.0          99.9

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.65       0.2641E-06          1.115    0.9486E+06        0.681    0.9861
=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2200.0           2194.0           100.0         0.007888              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.0705    6.00           39.05         0.7869E-02           2194.0          99.8

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.63       0.2641E-06          1.115    0.1164E+07        0.681    0.9861
=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2200.0           2192.0           100.0         0.007888              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.0814    7.98           45.07         0.7862E-02           2192.0          99.8

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.61       0.2640E-06          1.115    0.1342E+07        0.681    0.9861
=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2200.0           2190.0           100.0         0.007888              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.0910    9.97           50.39         0.7856E-02           2190.0          99.7

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.60       0.2640E-06          1.115    0.1499E+07        0.681    0.9861
=====
Pt (lb/sq. ft)    Ps (lb/sq. ft)    Tt (deg F)    RHOt (slugs/cu. ft)    X134a    Xair
2220.0           2180.0           100.0         0.007961              0.950    0.050

M    q (lb/sq. ft)    u (ft/sec)    RHO (slugs/cu. ft)    P (lb/sq. ft)    T (deg F)
0.1820    39.69          100.69        0.7831E-02           2180.0          99.0

a (ft/sec)    Mu (lb-sec/sq. ft)    Gamma    Re/ft    Pr    Z
553.25       0.2637E-06          1.115    0.2990E+07        0.681    0.9861
=====

```

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2220.0	2160.0	100.0	0.007961	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2234	59.25	123.54	0.7765E-02	2160.0	98.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.05	0.2634E-06	1.115	0.3641E+07	0.681	0.9862
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2220.0	2140.0	100.0	0.007961	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2585	78.65	142.94	0.7700E-02	2140.0	97.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.85	0.2632E-06	1.115	0.4181E+07	0.681	0.9863
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2220.0	2120.0	100.0	0.007961	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2898	97.93	160.18	0.7634E-02	2120.0	97.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.65	0.2630E-06	1.115	0.4650E+07	0.682	0.9864
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	2100.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2912	97.90	160.92	0.7562E-02	2100.0	97.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.70	0.2630E-06	1.115	0.4627E+07	0.682	0.9866
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	2080.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3197	116.95	176.66	0.7496E-02	2080.0	96.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.50	0.2627E-06	1.115	0.5040E+07	0.682	0.9866
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	2060.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3463	135.86	191.24	0.7431E-02	2060.0	96.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.29	0.2625E-06	1.115	0.5413E+07	0.682	0.9867
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	2040.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3711	154.55	204.88	0.7365E-02	2040.0	95.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.08	0.2622E-06	1.115	0.5754E+07	0.682	0.9868
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	2020.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3946	173.09	217.79	0.7299E-02	2020.0	95.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.87	0.2620E-06	1.115	0.6068E+07	0.682	0.9869



Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	2000.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4171	191.45	230.09	0.7234E-02	2000.0	94.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.66	0.2617E-06	1.115	0.6359E+07	0.682	0.9870
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1980.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4386	209.62	241.86	0.7168E-02	1980.0	94.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.44	0.2615E-06	1.115	0.6630E+07	0.683	0.9871
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1960.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4593	227.59	253.17	0.7102E-02	1960.0	93.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.22	0.2612E-06	1.115	0.6883E+07	0.683	0.9872
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1940.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4794	245.40	264.12	0.7036E-02	1940.0	93.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.00	0.2609E-06	1.115	0.7121E+07	0.683	0.9873
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1920.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4988	263.01	274.73	0.6970E-02	1920.0	92.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.78	0.2607E-06	1.115	0.7345E+07	0.683	0.9874
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1900.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5177	280.43	285.03	0.6904E-02	1900.0	91.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.55	0.2604E-06	1.115	0.7556E+07	0.683	0.9875
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1800.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6063	364.56	333.06	0.6574E-02	1800.0	88.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
549.37	0.2591E-06	1.116	0.8450E+07	0.684	0.9880
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1700.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6878	443.55	377.02	0.6242E-02	1700.0	85.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
548.12	0.2576E-06	1.116	0.9133E+07	0.685	0.9885

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1600.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7653	517.13	418.43	0.5908E-02	1600.0	82.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
546.77	0.2561E-06	1.116	0.9651E+07	0.687	0.9890
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1500.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8402	584.88	458.20	0.5572E-02	1500.0	78.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
545.33	0.2545E-06	1.117	0.1003E+08	0.688	0.9895
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1400.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9139	646.38	496.96	0.5235E-02	1400.0	74.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
543.77	0.2528E-06	1.117	0.1029E+08	0.690	0.9900
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1300.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9873	701.18	535.23	0.4896E-02	1300.0	70.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
542.09	0.2509E-06	1.117	0.1044E+08	0.691	0.9905
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1200.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0614	748.69	573.42	0.4555E-02	1200.0	66.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
540.25	0.2490E-06	1.118	0.1049E+08	0.693	0.9910
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1150.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0989	769.53	592.62	0.4383E-02	1150.0	64.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
539.27	0.2479E-06	1.118	0.1048E+08	0.695	0.9913
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1100.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1370	788.28	611.95	0.4210E-02	1100.0	61.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
538.23	0.2468E-06	1.118	0.1044E+08	0.696	0.9916
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1050.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1756	804.86	631.46	0.4038E-02	1050.0	59.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
537.15	0.2457E-06	1.119	0.1038E+08	0.697	0.9918

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	1000.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2149	819.14	651.20	0.3864E-02	1000.0	56.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
536.00	0.2445E-06	1.119	0.1029E+08	0.698	0.9921

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	950.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2551	831.01	671.22	0.3689E-02	950.0	53.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
534.80	0.2432E-06	1.119	0.1018E+08	0.700	0.9924

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	900.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2963	840.33	691.60	0.3514E-02	900.0	50.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
533.52	0.2419E-06	1.120	0.1004E+08	0.702	0.9927

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	850.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3387	846.94	712.39	0.3338E-02	850.0	47.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
532.16	0.2405E-06	1.120	0.9885E+07	0.703	0.9930

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
2200.0	800.0	100.0	0.007888	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3825	850.66	733.68	0.3161E-02	800.0	44.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
530.71	0.2391E-06	1.120	0.9700E+07	0.706	0.9933

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	1000.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0000	0.00	0.01	0.3558E-02	1000.0	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.25	0.2641E-06	1.112	0.1013E+03	0.679	0.9937

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	999.5	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0298	0.49	16.62	0.3557E-02	999.5	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.23	0.2641E-06	1.112	0.2238E+06	0.679	0.9937

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	999.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0422	0.98	23.52	0.3555E-02	999.0	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.22	0.2641E-06	1.112	0.3166E+06	0.679	0.9937

---

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	998.5	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0523	1.51	29.12	0.3553E-02	998.5	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.21	0.2641E-06	1.112	0.3917E+06	0.679	0.9937
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	998.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0602	2.00	33.55	0.3552E-02	998.0	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.20	0.2641E-06	1.112	0.4512E+06	0.679	0.9937
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	996.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0853	4.01	47.54	0.3545E-02	996.0	99.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.15	0.2640E-06	1.112	0.6383E+06	0.679	0.9937
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	994.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1044	5.99	58.19	0.3539E-02	994.0	99.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.10	0.2640E-06	1.112	0.7799E+06	0.679	0.9937
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	992.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1207	7.98	67.23	0.3532E-02	992.0	99.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.06	0.2639E-06	1.112	0.8996E+06	0.679	0.9938
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	990.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1349	9.95	75.13	0.3526E-02	990.0	99.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.01	0.2639E-06	1.112	0.1004E+07	0.679	0.9938
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	988.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1478	11.92	82.32	0.3520E-02	988.0	99.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.96	0.2638E-06	1.112	0.1098E+07	0.679	0.9938
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	986.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1598	13.91	88.99	0.3513E-02	986.0	99.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.91	0.2638E-06	1.112	0.1185E+07	0.679	0.9938

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	984.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1710	15.90	95.23	0.3507E-02	984.0	99.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.86	0.2637E-06	1.112	0.1266E+07	0.679	0.9938
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	982.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1815	17.86	101.04	0.3500E-02	982.0	99.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.82	0.2637E-06	1.112	0.1341E+07	0.679	0.9938
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	980.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1914	19.84	106.57	0.3494E-02	980.0	98.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.77	0.2636E-06	1.112	0.1412E+07	0.679	0.9938
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	960.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2721	39.27	151.36	0.3429E-02	960.0	97.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.28	0.2631E-06	1.112	0.1972E+07	0.679	0.9939
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	940.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3351	58.34	186.24	0.3364E-02	940.0	96.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
555.78	0.2626E-06	1.112	0.2386E+07	0.680	0.9940
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	920.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3891	77.01	216.07	0.3300E-02	920.0	95.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
555.27	0.2620E-06	1.112	0.2720E+07	0.680	0.9941
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	900.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4376	95.30	242.75	0.3235E-02	900.0	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.74	0.2615E-06	1.112	0.3003E+07	0.680	0.9942
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	880.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4822	113.19	267.26	0.3170E-02	880.0	92.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.21	0.2609E-06	1.113	0.3246E+07	0.681	0.9943

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	860.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5240	130.64	290.13	0.3104E-02	860.0	91.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.66	0.2604E-06	1.113	0.3459E+07	0.681	0.9944
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	840.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5637	147.69	311.78	0.3039E-02	840.0	90.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.09	0.2598E-06	1.113	0.3647E+07	0.682	0.9945
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	820.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6017	164.28	332.42	0.2974E-02	820.0	89.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.51	0.2592E-06	1.113	0.3814E+07	0.682	0.9946
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	800.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6383	180.45	352.30	0.2908E-02	800.0	87.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.92	0.2585E-06	1.113	0.3962E+07	0.683	0.9947
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	780.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6739	196.13	371.52	0.2842E-02	780.0	86.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.31	0.2579E-06	1.113	0.4094E+07	0.683	0.9947
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	760.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7086	211.36	390.22	0.2776E-02	760.0	84.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.68	0.2573E-06	1.113	0.4211E+07	0.684	0.9948
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	740.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7426	226.08	408.46	0.2710E-02	740.0	83.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.04	0.2566E-06	1.114	0.4314E+07	0.684	0.9949
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
1000.0	720.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7761	240.32	426.38	0.2644E-02	720.0	81.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
549.38	0.2559E-06	1.114	0.4405E+07	0.685	0.9950

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	700.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8092	254.04	443.98	0.2578E-02	700.0	80.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
548.69	0.2552E-06	1.114	0.4484E+07	0.686	0.9951
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	680.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8419	267.21	461.33	0.2511E-02	680.0	78.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
547.99	0.2545E-06	1.114	0.4551E+07	0.686	0.9952
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	660.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8744	279.85	478.52	0.2445E-02	660.0	77.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
547.26	0.2538E-06	1.114	0.4609E+07	0.687	0.9953
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	640.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9068	291.92	495.55	0.2378E-02	640.0	75.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
546.51	0.2530E-06	1.115	0.4656E+07	0.688	0.9954
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	620.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9391	303.41	512.50	0.2311E-02	620.0	73.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
545.74	0.2522E-06	1.115	0.4694E+07	0.688	0.9956
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	600.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9714	314.28	529.36	0.2243E-02	600.0	71.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
544.93	0.2514E-06	1.115	0.4723E+07	0.689	0.9957
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	580.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0038	324.53	546.20	0.2176E-02	580.0	70.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
544.10	0.2506E-06	1.115	0.4742E+07	0.690	0.9958
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	560.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0364	334.11	563.02	0.2108E-02	560.0	68.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
543.24	0.2497E-06	1.116	0.4752E+07	0.691	0.9959

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	540.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0692	343.03	579.90	0.2040E-02	540.0	66.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
542.35	0.2488E-06	1.116	0.4754E+07	0.692	0.9960
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	520.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1024	351.24	596.84	0.1972E-02	520.0	64.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
541.42	0.2479E-06	1.116	0.4747E+07	0.693	0.9961
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	500.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1359	358.72	613.90	0.1904E-02	500.0	62.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
540.45	0.2470E-06	1.116	0.4732E+07	0.694	0.9962
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	450.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2220	373.98	657.22	0.1732E-02	450.0	56.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
537.84	0.2444E-06	1.117	0.4657E+07	0.697	0.9965
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	400.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3123	383.84	701.96	0.1558E-02	400.0	50.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
534.90	0.2415E-06	1.118	0.4528E+07	0.701	0.9968
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	350.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.4089	387.58	748.90	0.1382E-02	350.0	42.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
531.56	0.2383E-06	1.119	0.4343E+07	0.705	0.9970
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
1000.0	300.0	100.0	0.003558	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.5141	384.22	798.94	0.1204E-02	300.0	34.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
527.67	0.2346E-06	1.120	0.4099E+07	0.711	0.9974
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
500.0	500.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0000	0.00	0.01	0.1773E-02	500.0	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
558.71	0.2641E-06	1.111	0.5067E+02	0.678	0.9969



Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	490.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1913	9.92	106.77	0.1741E-02	490.0	98.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
558.21	0.2636E-06	1.111	0.7052E+06	0.678	0.9969
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	480.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2717	19.63	151.55	0.1709E-02	480.0	97.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.70	0.2631E-06	1.111	0.9844E+06	0.678	0.9970
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	470.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3348	29.18	186.56	0.1677E-02	470.0	96.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.18	0.2626E-06	1.111	0.1191E+07	0.679	0.9970
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	460.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3888	38.52	216.42	0.1645E-02	460.0	95.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.65	0.2620E-06	1.111	0.1358E+07	0.679	0.9970
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	450.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4372	47.65	243.13	0.1613E-02	450.0	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.10	0.2615E-06	1.111	0.1499E+07	0.680	0.9971
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	440.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4819	56.62	267.71	0.1580E-02	440.0	92.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
555.54	0.2609E-06	1.111	0.1621E+07	0.680	0.9971
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	430.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5236	65.34	290.61	0.1548E-02	430.0	91.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.97	0.2604E-06	1.112	0.1727E+07	0.680	0.9972
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	420.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5633	73.87	312.27	0.1515E-02	420.0	90.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.39	0.2598E-06	1.112	0.1821E+07	0.681	0.9972

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	410.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6012	82.15	332.92	0.1483E-02	410.0	89.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.79	0.2592E-06	1.112	0.1904E+07	0.681	0.9973
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	400.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6378	90.24	352.83	0.1450E-02	400.0	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.17	0.2586E-06	1.112	0.1978E+07	0.682	0.9973
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	390.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6733	98.07	372.04	0.1417E-02	390.0	86.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.54	0.2579E-06	1.112	0.2044E+07	0.682	0.9974
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	380.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7081	105.72	390.82	0.1384E-02	380.0	84.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.89	0.2573E-06	1.112	0.2103E+07	0.683	0.9974
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	370.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7422	113.09	409.11	0.1352E-02	370.0	83.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.23	0.2566E-06	1.113	0.2154E+07	0.684	0.9975
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	360.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7756	120.20	427.00	0.1319E-02	360.0	81.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.54	0.2560E-06	1.113	0.2199E+07	0.684	0.9975
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	350.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8086	127.05	444.61	0.1286E-02	350.0	80.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
549.84	0.2553E-06	1.113	0.2239E+07	0.685	0.9976
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	340.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8414	133.66	462.02	0.1252E-02	340.0	78.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
549.11	0.2546E-06	1.113	0.2273E+07	0.685	0.9976

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	330.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8739	139.97	479.20	0.1219E-02	330.0	77.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
548.36	0.2538E-06	1.113	0.2302E+07	0.686	0.9977
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	320.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9062	146.00	496.23	0.1186E-02	320.0	75.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
547.59	0.2531E-06	1.114	0.2325E+07	0.687	0.9977
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	310.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9386	151.76	513.20	0.1153E-02	310.0	73.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
546.79	0.2523E-06	1.114	0.2344E+07	0.688	0.9978
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	300.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9708	157.19	530.05	0.1119E-02	300.0	72.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
545.97	0.2515E-06	1.114	0.2359E+07	0.689	0.9978
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	280.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0360	167.13	563.80	0.1052E-02	280.0	68.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
544.23	0.2498E-06	1.115	0.2374E+07	0.690	0.9979
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	270.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0688	171.59	580.67	0.1018E-02	270.0	66.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
543.31	0.2489E-06	1.115	0.2374E+07	0.691	0.9980
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	260.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1019	175.70	597.62	0.9840E-03	260.0	64.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
542.36	0.2480E-06	1.115	0.2371E+07	0.692	0.9980
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	240.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1694	182.80	631.89	0.9158E-03	240.0	59.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
540.33	0.2460E-06	1.116	0.2352E+07	0.695	0.9982

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	220.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2393	188.30	666.89	0.8469E-03	220.0	55.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
538.12	0.2439E-06	1.117	0.2315E+07	0.697	0.9983
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	200.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3120	192.03	702.83	0.7776E-03	200.0	50.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
535.70	0.2416E-06	1.117	0.2262E+07	0.700	0.9984
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	180.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3887	193.80	740.20	0.7075E-03	180.0	44.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
533.01	0.2391E-06	1.118	0.2190E+07	0.704	0.9985
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	160.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.4706	193.37	779.39	0.6367E-03	160.0	38.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
529.99	0.2362E-06	1.119	0.2100E+07	0.708	0.9986
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	140.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.5592	190.43	821.04	0.5651E-03	140.0	31.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
526.57	0.2331E-06	1.120	0.1990E+07	0.713	0.9987
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	120.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.6571	184.59	865.97	0.4924E-03	120.0	23.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
522.60	0.2294E-06	1.122	0.1858E+07	0.720	0.9989
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
500.0	100.0	100.0	0.001773	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.7676	175.30	915.39	0.4185E-03	100.0	13.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
517.88	0.2251E-06	1.123	0.1701E+07	0.728	0.9990
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	200.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0000	0.00	0.01	0.7080E-03	200.0	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
559.59	0.2641E-06	1.110	0.2027E+02	0.677	0.9987

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	190.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3045	9.77	170.00	0.6760E-03	190.0	97.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
558.29	0.2629E-06	1.110	0.4372E+06	0.678	0.9988
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	180.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4368	19.05	243.27	0.6439E-03	180.0	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.92	0.2615E-06	1.111	0.5989E+06	0.679	0.9988
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	170.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5435	27.86	301.87	0.6115E-03	170.0	91.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
555.46	0.2601E-06	1.111	0.7097E+06	0.680	0.9989
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	160.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6375	36.10	353.11	0.5791E-03	160.0	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.92	0.2586E-06	1.111	0.7906E+06	0.681	0.9989
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	150.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7250	43.79	400.42	0.5463E-03	150.0	84.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.28	0.2570E-06	1.112	0.8511E+06	0.683	0.9990
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	140.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8083	50.83	444.96	0.5135E-03	140.0	80.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.52	0.2553E-06	1.112	0.8949E+06	0.684	0.9990
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	130.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8899	57.23	488.22	0.4803E-03	130.0	76.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
548.63	0.2535E-06	1.113	0.9250E+06	0.686	0.9991
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
200.0	120.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9707	62.90	530.55	0.4470E-03	120.0	72.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
546.58	0.2515E-06	1.114	0.9428E+06	0.688	0.9991

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	110.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0521	67.78	572.72	0.4133E-03	110.0	67.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
544.35	0.2494E-06	1.114	0.9492E+06	0.690	0.9992
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	100.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1351	71.79	615.14	0.3795E-03	100.0	62.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
541.91	0.2471E-06	1.115	0.9448E+06	0.693	0.9992
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	90.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2214	74.86	658.57	0.3452E-03	90.0	56.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
539.20	0.2445E-06	1.116	0.9298E+06	0.696	0.9993
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	80.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3119	76.84	703.39	0.3106E-03	80.0	50.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
536.17	0.2416E-06	1.117	0.9041E+06	0.700	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	70.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.4084	77.59	750.30	0.2757E-03	70.0	43.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
532.73	0.2384E-06	1.118	0.8674E+06	0.704	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	60.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.5140	76.92	800.48	0.2401E-03	60.0	35.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
528.73	0.2348E-06	1.119	0.8187E+06	0.710	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	50.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.6318	74.56	855.05	0.2040E-03	50.0	25.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
523.99	0.2304E-06	1.121	0.7569E+06	0.718	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	40.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.7674	70.16	915.90	0.1673E-03	40.0	13.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
518.20	0.2252E-06	1.123	0.6804E+06	0.728	0.9996

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	30.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.9331	63.07	987.20	0.1295E-03	30.0	-1.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
510.68	0.2185E-06	1.126	0.5849E+06	0.744	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	20.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
2.1521	52.33	1076.14	0.9039E-04	20.0	-21.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
500.04	0.2091E-06	1.130	0.4650E+06	0.771	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	10.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
2.5028	35.59	1205.52	0.4899E-04	10.0	-56.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
481.66	0.1935E-06	1.138	0.3051E+06	0.840	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
200.0	5.0	100.0	0.000708	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
2.8330	23.09	1312.43	0.2681E-04	5.0	-89.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
463.27	0.1786E-06	1.146	0.1970E+06	0.952	0.9999
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	100.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.0000	0.00	0.01	0.3538E-03	100.0	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
559.88	0.2641E-06	1.110	0.1015E+02	0.677	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	98.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.1902	1.97	106.39	0.3475E-03	98.0	98.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
559.37	0.2636E-06	1.110	0.1402E+06	0.677	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	96.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.2715	3.92	151.70	0.3410E-03	96.0	97.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
558.84	0.2631E-06	1.110	0.1966E+06	0.678	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	94.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3346	5.84	186.82	0.3346E-03	94.0	96.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
558.30	0.2626E-06	1.110	0.2380E+06	0.678	0.9994

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	92.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.3884	7.70	216.65	0.3282E-03	92.0	95.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.75	0.2621E-06	1.110	0.2713E+06	0.678	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	90.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4368	9.53	243.40	0.3218E-03	90.0	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
557.19	0.2615E-06	1.110	0.2994E+06	0.679	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	88.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.4814	11.32	267.95	0.3153E-03	88.0	93.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.61	0.2610E-06	1.111	0.3237E+06	0.679	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	86.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5230	13.06	290.79	0.3089E-03	86.0	91.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
556.03	0.2604E-06	1.111	0.3449E+06	0.680	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	84.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.5627	14.77	312.54	0.3024E-03	84.0	90.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
555.42	0.2598E-06	1.111	0.3637E+06	0.680	0.9994
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	82.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6010	16.44	333.41	0.2958E-03	82.0	89.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.80	0.2592E-06	1.111	0.3805E+06	0.681	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	80.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6374	18.05	353.25	0.2894E-03	80.0	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.17	0.2586E-06	1.111	0.3952E+06	0.681	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	78.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6729	19.62	372.45	0.2829E-03	78.0	86.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.53	0.2580E-06	1.111	0.4083E+06	0.682	0.9995



Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	76.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7079	21.15	391.36	0.2763E-03	76.0	84.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.85	0.2573E-06	1.112	0.4201E+06	0.682	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	74.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7416	22.61	409.49	0.2698E-03	74.0	83.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.18	0.2567E-06	1.112	0.4303E+06	0.683	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	72.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7751	24.04	427.43	0.2632E-03	72.0	82.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.47	0.2560E-06	1.112	0.4394E+06	0.684	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	70.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8084	25.42	445.21	0.2566E-03	70.0	80.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.75	0.2553E-06	1.112	0.4474E+06	0.684	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	65.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8897	28.62	488.32	0.2400E-03	65.0	76.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
548.84	0.2535E-06	1.113	0.4624E+06	0.686	0.9995
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	60.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9702	31.44	530.51	0.2235E-03	60.0	72.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
546.80	0.2515E-06	1.113	0.4712E+06	0.688	0.9996
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	55.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0518	33.89	572.78	0.2066E-03	55.0	67.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
544.55	0.2494E-06	1.114	0.4745E+06	0.690	0.9996
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
100.0	50.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1348	35.89	615.17	0.1897E-03	50.0	62.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
542.10	0.2471E-06	1.115	0.4723E+06	0.693	0.9996

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
100.0	45.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2212	37.43	658.70	0.1726E-03	45.0	56.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
539.37	0.2445E-06	1.116	0.4648E+06	0.696	0.9996
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
100.0	40.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3117	38.42	703.49	0.1553E-03	40.0	50.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
536.33	0.2417E-06	1.117	0.4520E+06	0.700	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
100.0	35.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.4084	38.80	750.49	0.1378E-03	35.0	43.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
532.87	0.2385E-06	1.118	0.4336E+06	0.704	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
100.0	30.0	100.0	0.000354	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.5139	38.47	800.64	0.1200E-03	30.0	35.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
528.86	0.2348E-06	1.119	0.4093E+06	0.710	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	40.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6379	9.04	353.59	0.1446E-03	40.0	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
554.29	0.2586E-06	1.111	0.1977E+06	0.681	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	39.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.6728	9.81	372.52	0.1414E-03	39.0	86.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
553.65	0.2580E-06	1.111	0.2041E+06	0.682	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	38.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7078	10.58	391.42	0.1381E-03	38.0	84.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.97	0.2573E-06	1.112	0.2100E+06	0.682	0.9997
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	37.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7411	11.30	409.30	0.1349E-03	37.0	83.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
552.30	0.2567E-06	1.112	0.2151E+06	0.683	0.9997

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	36.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.7745	12.01	427.24	0.1316E-03	36.0	82.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
551.60	0.2560E-06	1.112	0.2196E+06	0.683	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	35.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8083	12.71	445.27	0.1282E-03	35.0	80.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.86	0.2553E-06	1.112	0.2237E+06	0.684	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	34.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8405	13.36	462.40	0.1250E-03	34.0	78.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
550.12	0.2546E-06	1.112	0.2270E+06	0.685	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	33.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.8732	14.00	479.68	0.1217E-03	33.0	77.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
549.35	0.2539E-06	1.113	0.2299E+06	0.686	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	32.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9062	14.61	497.11	0.1183E-03	32.0	75.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
548.54	0.2531E-06	1.113	0.2323E+06	0.686	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	31.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9379	15.18	513.73	0.1150E-03	31.0	73.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
547.74	0.2523E-06	1.113	0.2342E+06	0.687	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	30.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
0.9701	15.72	530.55	0.1117E-03	30.0	72.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
546.90	0.2515E-06	1.113	0.2356E+06	0.688	0.9998
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RH0t (slugs/cu. ft)	X134a	Xair
50.0	28.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.0353	16.72	564.34	0.1050E-03	28.0	68.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
545.12	0.2498E-06	1.114	0.2371E+06	0.690	0.9998

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	26.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1011	17.57	598.13	0.9825E-04	26.0	64.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
543.21	0.2480E-06	1.115	0.2369E+06	0.692	0.9998
=====					
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	24.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.1689	18.29	632.55	0.9142E-04	24.0	60.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
541.13	0.2461E-06	1.115	0.2350E+06	0.694	0.9998
=====					
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	22.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.2382	18.83	667.27	0.8461E-04	22.0	55.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
538.90	0.2440E-06	1.116	0.2314E+06	0.697	0.9998
=====					
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	RHOt (slugs/cu. ft)	X134a	Xair
50.0	20.0	100.0	0.000177	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	P (lb/sq. ft)	T (deg F)
1.3114	19.21	703.48	0.7765E-04	20.0	50.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr	Z
536.42	0.2417E-06	1.117	0.2260E+06	0.700	0.9998
=====					
*** ALL DATA CASES HAVE BEEN READ AND PROCESSED - JOB IS COMPLETED ***					

## Appendix F

### Sample Input for Program MIXRK

(U.S. Customary units)

100.	2200.	.95
100.	1000.	.95
100.	500.	.95
100.	200.	.95
100.	100.	.95
100.	50.	.95

## Appendix G

### Sample Output from Program MIXRK

I S E N T R O P I C E X P A N S I O N									
(Output file outmix6)									
Pt (lb/sq. ft)	Tt (deg F)	Tt (deg R)	RH0t (slugs/cu. ft)	X134a	Xair	Zt			
2200.0	100.0	559.7	0.007888	0.950	0.050	0.9861			
M	USTAR	PSTAR/Pt	TSTAR/Tt	RHOSTAR	RHOSTARxUSTAR				
1.000001E+00	5.417835E+02	5.830985E-01	9.465545E-01	4.837427E-03	2.620838E+00				
M	P/Pt	R/RH0t	T/Tt	BET	q/Pt	A/Astar	U/Ustar	Gamma	Pr
0.00	1.0000	1.0000	1.0000	1.0000	0.0000	0.1410E+03	0.004	1.115	0.68
0.01	0.9999	0.9999	1.0000	0.9999	0.0001	0.6001E+02	0.010	1.115	0.68
0.02	0.9998	0.9998	1.0000	0.9998	0.0002	0.3001E+02	0.020	1.115	0.68
0.03	0.9995	0.9995	1.0000	0.9995	0.0005	0.2001E+02	0.031	1.115	0.68
0.04	0.9991	0.9992	0.9999	0.9992	0.0009	0.1502E+02	0.041	1.115	0.68
0.05	0.9986	0.9988	0.9999	0.9987	0.0014	0.1201E+02	0.051	1.115	0.68
0.06	0.9980	0.9982	0.9998	0.9982	0.0020	0.1002E+02	0.061	1.115	0.68
0.07	0.9973	0.9976	0.9997	0.9975	0.0027	0.8594E+01	0.072	1.115	0.68
0.08	0.9965	0.9968	0.9996	0.9968	0.0035	0.7526E+01	0.082	1.115	0.68
0.09	0.9956	0.9960	0.9996	0.9959	0.0044	0.6695E+01	0.092	1.115	0.68
0.10	0.9945	0.9950	0.9994	0.9950	0.0055	0.6032E+01	0.102	1.115	0.68
0.11	0.9934	0.9940	0.9993	0.9939	0.0066	0.5489E+01	0.112	1.115	0.68
0.12	0.9921	0.9928	0.9992	0.9928	0.0079	0.5038E+01	0.123	1.115	0.68
0.13	0.9908	0.9916	0.9991	0.9915	0.0092	0.4656E+01	0.133	1.115	0.68
0.14	0.9893	0.9903	0.9989	0.9902	0.0107	0.4330E+01	0.143	1.115	0.68
0.15	0.9877	0.9888	0.9988	0.9887	0.0122	0.4048E+01	0.153	1.115	0.68
0.16	0.9860	0.9873	0.9986	0.9871	0.0139	0.3801E+01	0.163	1.115	0.68
0.17	0.9843	0.9857	0.9984	0.9854	0.0156	0.3583E+01	0.174	1.115	0.68
0.18	0.9824	0.9839	0.9982	0.9837	0.0175	0.3390E+01	0.184	1.115	0.68
0.19	0.9804	0.9821	0.9980	0.9818	0.0195	0.3218E+01	0.194	1.115	0.68
0.20	0.9783	0.9802	0.9978	0.9798	0.0215	0.3063E+01	0.204	1.115	0.68
0.21	0.9761	0.9782	0.9976	0.9777	0.0237	0.2924E+01	0.214	1.115	0.68
0.22	0.9738	0.9761	0.9973	0.9755	0.0259	0.2797E+01	0.225	1.115	0.68
0.23	0.9714	0.9739	0.9971	0.9732	0.0283	0.2682E+01	0.235	1.115	0.68
0.24	0.9689	0.9716	0.9968	0.9708	0.0307	0.2576E+01	0.245	1.115	0.68
0.25	0.9663	0.9693	0.9966	0.9682	0.0332	0.2479E+01	0.255	1.115	0.68
0.26	0.9636	0.9668	0.9963	0.9656	0.0358	0.2390E+01	0.265	1.115	0.68
0.27	0.9608	0.9643	0.9960	0.9629	0.0385	0.2308E+01	0.276	1.115	0.68
0.28	0.9579	0.9616	0.9957	0.9600	0.0413	0.2232E+01	0.286	1.115	0.68
0.29	0.9549	0.9589	0.9954	0.9570	0.0442	0.2162E+01	0.296	1.115	0.68
0.30	0.9518	0.9561	0.9950	0.9539	0.0471	0.2096E+01	0.306	1.115	0.68
0.31	0.9486	0.9532	0.9947	0.9507	0.0501	0.2035E+01	0.316	1.115	0.68
0.32	0.9454	0.9502	0.9944	0.9474	0.0532	0.1978E+01	0.326	1.115	0.68
0.33	0.9420	0.9471	0.9940	0.9440	0.0564	0.1924E+01	0.336	1.115	0.68
0.34	0.9386	0.9440	0.9936	0.9404	0.0597	0.1874E+01	0.347	1.115	0.68
0.35	0.9350	0.9407	0.9933	0.9367	0.0630	0.1827E+01	0.357	1.115	0.68
0.36	0.9314	0.9374	0.9929	0.9330	0.0664	0.1783E+01	0.367	1.115	0.68
0.37	0.9277	0.9340	0.9925	0.9290	0.0699	0.1741E+01	0.377	1.115	0.68
0.38	0.9239	0.9305	0.9921	0.9250	0.0734	0.1702E+01	0.387	1.115	0.68
0.39	0.9200	0.9270	0.9916	0.9208	0.0770	0.1665E+01	0.397	1.115	0.68
0.40	0.9161	0.9234	0.9912	0.9165	0.0806	0.1630E+01	0.407	1.115	0.68
0.41	0.9120	0.9197	0.9908	0.9121	0.0844	0.1597E+01	0.418	1.115	0.68
0.42	0.9079	0.9159	0.9903	0.9075	0.0881	0.1566E+01	0.428	1.115	0.68
0.43	0.9037	0.9120	0.9899	0.9028	0.0920	0.1536E+01	0.438	1.115	0.68
0.44	0.8994	0.9081	0.9894	0.8980	0.0958	0.1508E+01	0.448	1.115	0.68
0.45	0.8950	0.9041	0.9889	0.8930	0.0998	0.1481E+01	0.458	1.115	0.68
0.46	0.8906	0.9000	0.9884	0.8879	0.1037	0.1456E+01	0.468	1.115	0.68
0.47	0.8861	0.8959	0.9879	0.8827	0.1077	0.1432E+01	0.478	1.115	0.68
0.48	0.8815	0.8917	0.9874	0.8773	0.1118	0.1409E+01	0.488	1.115	0.68
0.49	0.8769	0.8874	0.9868	0.8717	0.1159	0.1387E+01	0.498	1.115	0.68
0.50	0.8722	0.8831	0.9863	0.8660	0.1201	0.1366E+01	0.508	1.115	0.68
0.51	0.8674	0.8787	0.9858	0.8602	0.1242	0.1346E+01	0.518	1.115	0.68
0.52	0.8625	0.8742	0.9852	0.8542	0.1284	0.1328E+01	0.528	1.115	0.68
0.53	0.8576	0.8697	0.9846	0.8480	0.1327	0.1310E+01	0.538	1.115	0.68
0.54	0.8526	0.8651	0.9841	0.8417	0.1369	0.1292E+01	0.548	1.115	0.68

0.55	0.8476	0.8605	0.9835	0.8352	0.1412	0.1276E+01	0.558	1.115	0.68
0.56	0.8425	0.8558	0.9829	0.8285	0.1455	0.1260E+01	0.569	1.115	0.68
0.57	0.8373	0.8510	0.9822	0.8216	0.1499	0.1246E+01	0.579	1.116	0.68
0.58	0.8321	0.8462	0.9816	0.8146	0.1542	0.1231E+01	0.589	1.116	0.68
0.59	0.8269	0.8413	0.9810	0.8074	0.1586	0.1218E+01	0.599	1.116	0.68
0.60	0.8215	0.8364	0.9804	0.8000	0.1630	0.1205E+01	0.609	1.116	0.68
0.61	0.8162	0.8315	0.9797	0.7924	0.1674	0.1192E+01	0.618	1.116	0.68
0.62	0.8107	0.8265	0.9790	0.7846	0.1717	0.1181E+01	0.628	1.116	0.68
0.63	0.8053	0.8214	0.9784	0.7766	0.1762	0.1169E+01	0.638	1.116	0.68
0.64	0.7997	0.8163	0.9777	0.7684	0.1806	0.1159E+01	0.648	1.116	0.68
0.65	0.7942	0.8111	0.9770	0.7599	0.1850	0.1148E+01	0.658	1.116	0.68
0.66	0.7886	0.8059	0.9763	0.7513	0.1894	0.1139E+01	0.668	1.116	0.69
0.67	0.7829	0.8007	0.9756	0.7424	0.1938	0.1129E+01	0.678	1.116	0.69
0.68	0.7772	0.7954	0.9748	0.7332	0.1982	0.1120E+01	0.688	1.116	0.69
0.69	0.7715	0.7901	0.9741	0.7238	0.2026	0.1112E+01	0.698	1.116	0.69
0.70	0.7657	0.7847	0.9734	0.7141	0.2069	0.1104E+01	0.708	1.116	0.69
0.71	0.7599	0.7793	0.9726	0.7042	0.2113	0.1096E+01	0.718	1.116	0.69
0.72	0.7541	0.7739	0.9719	0.6940	0.2156	0.1089E+01	0.728	1.116	0.69
0.73	0.7482	0.7684	0.9711	0.6834	0.2200	0.1082E+01	0.738	1.116	0.69
0.74	0.7423	0.7630	0.9703	0.6726	0.2243	0.1075E+01	0.747	1.116	0.69
0.75	0.7364	0.7574	0.9695	0.6614	0.2286	0.1069E+01	0.757	1.116	0.69
0.76	0.7304	0.7519	0.9687	0.6499	0.2328	0.1063E+01	0.767	1.116	0.69
0.77	0.7244	0.7463	0.9679	0.6380	0.2371	0.1058E+01	0.777	1.116	0.69
0.78	0.7184	0.7407	0.9671	0.6258	0.2413	0.1052E+01	0.787	1.116	0.69
0.79	0.7124	0.7350	0.9662	0.6131	0.2454	0.1047E+01	0.797	1.116	0.69
0.80	0.7063	0.7294	0.9654	0.6000	0.2496	0.1043E+01	0.806	1.116	0.69
0.81	0.7003	0.7237	0.9645	0.5864	0.2537	0.1038E+01	0.816	1.116	0.69
0.82	0.6942	0.7180	0.9637	0.5724	0.2577	0.1034E+01	0.826	1.116	0.69
0.83	0.6881	0.7123	0.9628	0.5578	0.2618	0.1030E+01	0.836	1.116	0.69
0.84	0.6819	0.7065	0.9619	0.5426	0.2658	0.1027E+01	0.846	1.117	0.69
0.85	0.6758	0.7008	0.9610	0.5268	0.2697	0.1023E+01	0.855	1.117	0.69
0.86	0.6697	0.6950	0.9601	0.5103	0.2736	0.1020E+01	0.865	1.117	0.69
0.87	0.6635	0.6892	0.9592	0.4931	0.2775	0.1017E+01	0.875	1.117	0.69
0.88	0.6573	0.6834	0.9583	0.4750	0.2813	0.1015E+01	0.884	1.117	0.69
0.89	0.6511	0.6776	0.9574	0.4559	0.2850	0.1012E+01	0.894	1.117	0.69
0.90	0.6450	0.6718	0.9564	0.4359	0.2887	0.1010E+01	0.904	1.117	0.69
0.91	0.6388	0.6659	0.9555	0.4146	0.2924	0.1008E+01	0.913	1.117	0.69
0.92	0.6326	0.6601	0.9545	0.3919	0.2960	0.1006E+01	0.923	1.117	0.69
0.93	0.6264	0.6542	0.9536	0.3676	0.2995	0.1005E+01	0.933	1.117	0.69
0.94	0.6202	0.6484	0.9526	0.3412	0.3030	0.1004E+01	0.942	1.117	0.69
0.95	0.6140	0.6425	0.9516	0.3123	0.3065	0.1002E+01	0.952	1.117	0.69
0.96	0.6078	0.6367	0.9506	0.2800	0.3098	0.1002E+01	0.962	1.117	0.69
0.97	0.6016	0.6308	0.9496	0.2431	0.3131	0.1001E+01	0.971	1.117	0.69
0.98	0.5954	0.6249	0.9486	0.1990	0.3164	0.1000E+01	0.981	1.117	0.69
0.99	0.5893	0.6191	0.9476	0.1411	0.3196	0.1000E+01	0.990	1.117	0.69
1.00	0.5831	0.6132	0.9466	0.0011	0.3227	0.1000E+01	1.000	1.117	0.69
1.01	0.5769	0.6074	0.9455	0.1417	0.3257	0.1000E+01	1.010	1.117	0.69
1.02	0.5708	0.6015	0.9445	0.2010	0.3287	0.1000E+01	1.019	1.117	0.69
1.03	0.5646	0.5957	0.9434	0.2468	0.3316	0.1001E+01	1.029	1.118	0.69
1.04	0.5585	0.5898	0.9423	0.2857	0.3345	0.1002E+01	1.038	1.118	0.69
1.05	0.5524	0.5840	0.9413	0.3202	0.3372	0.1002E+01	1.048	1.118	0.69
1.06	0.5463	0.5782	0.9402	0.3516	0.3399	0.1003E+01	1.057	1.118	0.69
1.07	0.5402	0.5724	0.9391	0.3807	0.3426	0.1005E+01	1.067	1.118	0.69
1.08	0.5342	0.5666	0.9380	0.4079	0.3451	0.1006E+01	1.076	1.118	0.69
1.09	0.5281	0.5608	0.9369	0.4337	0.3476	0.1008E+01	1.085	1.118	0.69
1.10	0.5221	0.5550	0.9358	0.4583	0.3500	0.1009E+01	1.095	1.118	0.69
1.11	0.5161	0.5492	0.9347	0.4818	0.3524	0.1011E+01	1.104	1.118	0.69
1.12	0.5101	0.5435	0.9335	0.5044	0.3546	0.1013E+01	1.114	1.118	0.70
1.13	0.5041	0.5377	0.9324	0.5262	0.3568	0.1015E+01	1.123	1.118	0.70
1.14	0.4982	0.5320	0.9312	0.5473	0.3589	0.1018E+01	1.132	1.118	0.70
1.15	0.4923	0.5263	0.9301	0.5679	0.3610	0.1021E+01	1.142	1.118	0.70
1.16	0.4864	0.5206	0.9289	0.5879	0.3629	0.1023E+01	1.151	1.118	0.70
1.17	0.4805	0.5150	0.9277	0.6074	0.3648	0.1026E+01	1.160	1.118	0.70
1.18	0.4747	0.5093	0.9265	0.6264	0.3666	0.1029E+01	1.170	1.119	0.70
1.19	0.4689	0.5037	0.9254	0.6450	0.3684	0.1033E+01	1.179	1.119	0.70
1.20	0.4631	0.4981	0.9241	0.6633	0.3700	0.1036E+01	1.188	1.119	0.70
1.21	0.4573	0.4925	0.9229	0.6813	0.3716	0.1040E+01	1.197	1.119	0.70
1.22	0.4516	0.4870	0.9217	0.6988	0.3731	0.1044E+01	1.207	1.119	0.70
1.23	0.4459	0.4815	0.9205	0.7162	0.3745	0.1048E+01	1.216	1.119	0.70
1.24	0.4403	0.4760	0.9193	0.7332	0.3759	0.1052E+01	1.225	1.119	0.70
1.25	0.4347	0.4705	0.9180	0.7500	0.3771	0.1056E+01	1.234	1.119	0.70
1.26	0.4291	0.4650	0.9168	0.7666	0.3783	0.1061E+01	1.243	1.119	0.70

1.27	0.4235	0.4596	0.9155	0.7829	0.3794	0.1065E+01	1.253	1.119	0.70
1.28	0.4180	0.4542	0.9143	0.7990	0.3804	0.1070E+01	1.262	1.119	0.70
1.29	0.4125	0.4489	0.9130	0.8149	0.3814	0.1075E+01	1.271	1.119	0.70
1.30	0.4071	0.4435	0.9117	0.8307	0.3823	0.1080E+01	1.280	1.120	0.70
1.31	0.4017	0.4382	0.9104	0.8462	0.3831	0.1086E+01	1.289	1.120	0.70
1.32	0.3963	0.4329	0.9091	0.8616	0.3838	0.1091E+01	1.298	1.120	0.70

I S E N T R O P I C E X P A N S I O N  
(Output file outmix6)

Pt(lb/sq.ft)	Tt(deg F)	Tt(deg R)	RH0t(slugs/cu.ft)	X134a	Xair	Zt
1000.0	100.0	559.7	0.003558	0.950	0.050	0.9937

M	USTAR	PSTAR/Pt	TSTAR/Tt	RHOSTAR	RHOSTARxUSTAR
9.999997E-01	5.442037E+02	5.823569E-01	9.468748E-01	2.183912E-03	1.188493E+00

M	P/Pt	R/RH0t	T/Tt	BET	q/Pt	A/Astar	U/Ustar	Gamma	Pr
0.00	1.0000	1.0000	1.0000	1.0000	0.0000	0.1405E+03	0.004	1.112	0.68
0.01	0.9999	0.9999	1.0000	0.9999	0.0001	0.5989E+02	0.010	1.112	0.68
0.02	0.9998	0.9998	1.0000	0.9998	0.0002	0.2997E+02	0.020	1.112	0.68
0.03	0.9995	0.9995	1.0000	0.9995	0.0005	0.1998E+02	0.031	1.112	0.68
0.04	0.9991	0.9992	0.9999	0.9992	0.0009	0.1499E+02	0.041	1.112	0.68
0.05	0.9986	0.9988	0.9999	0.9987	0.0014	0.1200E+02	0.051	1.112	0.68
0.06	0.9980	0.9982	0.9998	0.9982	0.0020	0.1001E+02	0.061	1.112	0.68
0.07	0.9973	0.9976	0.9997	0.9975	0.0027	0.8585E+01	0.072	1.112	0.68
0.08	0.9965	0.9968	0.9996	0.9968	0.0035	0.7517E+01	0.082	1.112	0.68
0.09	0.9955	0.9960	0.9996	0.9959	0.0045	0.6688E+01	0.092	1.112	0.68
0.10	0.9945	0.9950	0.9995	0.9950	0.0055	0.6026E+01	0.102	1.112	0.68
0.11	0.9933	0.9940	0.9993	0.9939	0.0066	0.5484E+01	0.113	1.112	0.68
0.12	0.9921	0.9928	0.9992	0.9928	0.0079	0.5033E+01	0.123	1.112	0.68
0.13	0.9907	0.9916	0.9991	0.9915	0.0092	0.4652E+01	0.133	1.112	0.68
0.14	0.9892	0.9903	0.9989	0.9902	0.0107	0.4326E+01	0.143	1.112	0.68
0.15	0.9877	0.9888	0.9988	0.9887	0.0123	0.4043E+01	0.154	1.112	0.68
0.16	0.9860	0.9873	0.9986	0.9871	0.0139	0.3797E+01	0.164	1.112	0.68
0.17	0.9842	0.9857	0.9984	0.9854	0.0157	0.3580E+01	0.174	1.112	0.68
0.18	0.9823	0.9839	0.9982	0.9837	0.0176	0.3387E+01	0.184	1.112	0.68
0.19	0.9803	0.9821	0.9980	0.9818	0.0196	0.3215E+01	0.194	1.112	0.68
0.20	0.9782	0.9802	0.9978	0.9798	0.0216	0.3060E+01	0.205	1.112	0.68
0.21	0.9760	0.9782	0.9976	0.9777	0.0238	0.2921E+01	0.215	1.112	0.68
0.22	0.9736	0.9761	0.9973	0.9755	0.0260	0.2794E+01	0.225	1.112	0.68
0.23	0.9712	0.9739	0.9971	0.9732	0.0284	0.2679E+01	0.235	1.112	0.68
0.24	0.9687	0.9716	0.9968	0.9708	0.0308	0.2574E+01	0.245	1.112	0.68
0.25	0.9661	0.9693	0.9966	0.9682	0.0334	0.2477E+01	0.256	1.112	0.68
0.26	0.9634	0.9668	0.9963	0.9656	0.0360	0.2388E+01	0.266	1.112	0.68
0.27	0.9606	0.9643	0.9960	0.9629	0.0387	0.2306E+01	0.276	1.112	0.68
0.28	0.9577	0.9616	0.9957	0.9600	0.0415	0.2230E+01	0.286	1.112	0.68
0.29	0.9547	0.9589	0.9954	0.9570	0.0444	0.2160E+01	0.296	1.112	0.68
0.30	0.9516	0.9561	0.9951	0.9539	0.0473	0.2094E+01	0.307	1.112	0.68
0.31	0.9484	0.9532	0.9947	0.9507	0.0504	0.2033E+01	0.317	1.112	0.68
0.32	0.9451	0.9502	0.9944	0.9474	0.0535	0.1976E+01	0.327	1.112	0.68
0.33	0.9417	0.9471	0.9940	0.9440	0.0567	0.1923E+01	0.337	1.112	0.68
0.34	0.9383	0.9440	0.9937	0.9404	0.0600	0.1873E+01	0.347	1.112	0.68
0.35	0.9347	0.9408	0.9933	0.9367	0.0633	0.1826E+01	0.357	1.112	0.68
0.36	0.9311	0.9374	0.9929	0.9329	0.0667	0.1782E+01	0.368	1.112	0.68
0.37	0.9274	0.9340	0.9925	0.9290	0.0702	0.1740E+01	0.378	1.112	0.68
0.38	0.9236	0.9306	0.9921	0.9250	0.0737	0.1701E+01	0.388	1.112	0.68
0.39	0.9197	0.9270	0.9917	0.9208	0.0773	0.1664E+01	0.398	1.112	0.68
0.40	0.9157	0.9234	0.9913	0.9165	0.0810	0.1629E+01	0.408	1.112	0.68
0.41	0.9116	0.9197	0.9908	0.9121	0.0847	0.1596E+01	0.418	1.112	0.68
0.42	0.9075	0.9159	0.9904	0.9075	0.0885	0.1565E+01	0.428	1.112	0.68
0.43	0.9033	0.9121	0.9899	0.9028	0.0924	0.1535E+01	0.438	1.112	0.68
0.44	0.8990	0.9081	0.9894	0.8980	0.0962	0.1507E+01	0.448	1.112	0.68
0.45	0.8946	0.9041	0.9890	0.8930	0.1002	0.1480E+01	0.459	1.112	0.68
0.46	0.8902	0.9001	0.9885	0.8879	0.1042	0.1455E+01	0.469	1.112	0.68
0.47	0.8856	0.8959	0.9880	0.8827	0.1082	0.1431E+01	0.479	1.113	0.68
0.48	0.8810	0.8917	0.9874	0.8773	0.1123	0.1408E+01	0.489	1.113	0.68
0.49	0.8764	0.8875	0.9869	0.8717	0.1164	0.1386E+01	0.499	1.113	0.68
0.50	0.8716	0.8831	0.9864	0.8660	0.1205	0.1365E+01	0.509	1.113	0.68
0.51	0.8668	0.8787	0.9858	0.8602	0.1247	0.1346E+01	0.519	1.113	0.68
0.52	0.8620	0.8743	0.9853	0.8542	0.1289	0.1327E+01	0.529	1.113	0.68
0.53	0.8571	0.8698	0.9847	0.8480	0.1332	0.1309E+01	0.539	1.113	0.68
0.54	0.8521	0.8652	0.9841	0.8417	0.1375	0.1292E+01	0.549	1.113	0.68



0.55	0.8470	0.8606	0.9836	0.8352	0.1418	0.1275E+01	0.559	1.113	0.68
0.56	0.8419	0.8559	0.9830	0.8285	0.1461	0.1260E+01	0.569	1.113	0.68
0.57	0.8367	0.8511	0.9823	0.8217	0.1504	0.1245E+01	0.579	1.113	0.68
0.58	0.8315	0.8463	0.9817	0.8146	0.1548	0.1231E+01	0.589	1.113	0.68
0.59	0.8262	0.8415	0.9811	0.8074	0.1592	0.1217E+01	0.599	1.113	0.68
0.60	0.8209	0.8365	0.9805	0.8000	0.1636	0.1204E+01	0.609	1.113	0.68
0.61	0.8155	0.8316	0.9798	0.7924	0.1680	0.1192E+01	0.619	1.113	0.68
0.62	0.8101	0.8266	0.9792	0.7846	0.1724	0.1180E+01	0.629	1.113	0.68
0.63	0.8046	0.8215	0.9785	0.7766	0.1768	0.1169E+01	0.639	1.113	0.68
0.64	0.7991	0.8164	0.9778	0.7684	0.1812	0.1158E+01	0.649	1.113	0.68
0.65	0.7935	0.8113	0.9771	0.7599	0.1856	0.1148E+01	0.659	1.113	0.68
0.66	0.7879	0.8061	0.9764	0.7513	0.1900	0.1138E+01	0.669	1.113	0.68
0.67	0.7822	0.8009	0.9757	0.7424	0.1944	0.1129E+01	0.679	1.113	0.68
0.68	0.7765	0.7956	0.9750	0.7332	0.1988	0.1120E+01	0.689	1.113	0.68
0.69	0.7708	0.7903	0.9743	0.7238	0.2032	0.1112E+01	0.699	1.113	0.68
0.70	0.7650	0.7849	0.9735	0.7141	0.2076	0.1104E+01	0.709	1.113	0.68
0.71	0.7592	0.7795	0.9728	0.7042	0.2120	0.1096E+01	0.718	1.113	0.68
0.72	0.7533	0.7741	0.9720	0.6940	0.2163	0.1089E+01	0.728	1.114	0.68
0.73	0.7475	0.7687	0.9712	0.6834	0.2206	0.1082E+01	0.738	1.114	0.68
0.74	0.7416	0.7632	0.9705	0.6726	0.2250	0.1075E+01	0.748	1.114	0.68
0.75	0.7356	0.7577	0.9697	0.6614	0.2293	0.1069E+01	0.758	1.114	0.68
0.76	0.7297	0.7521	0.9689	0.6499	0.2335	0.1063E+01	0.768	1.114	0.68
0.77	0.7237	0.7466	0.9681	0.6380	0.2377	0.1057E+01	0.777	1.114	0.68
0.78	0.7177	0.7410	0.9673	0.6258	0.2420	0.1052E+01	0.787	1.114	0.69
0.79	0.7116	0.7353	0.9664	0.6131	0.2461	0.1047E+01	0.797	1.114	0.69
0.80	0.7056	0.7297	0.9656	0.6000	0.2503	0.1042E+01	0.807	1.114	0.69
0.81	0.6995	0.7240	0.9647	0.5864	0.2544	0.1038E+01	0.817	1.114	0.69
0.82	0.6934	0.7183	0.9639	0.5724	0.2585	0.1034E+01	0.826	1.114	0.69
0.83	0.6873	0.7126	0.9630	0.5578	0.2625	0.1030E+01	0.836	1.114	0.69
0.84	0.6812	0.7069	0.9621	0.5426	0.2665	0.1026E+01	0.846	1.114	0.69
0.85	0.6750	0.7011	0.9613	0.5268	0.2704	0.1023E+01	0.856	1.114	0.69
0.86	0.6689	0.6954	0.9604	0.5103	0.2743	0.1020E+01	0.865	1.114	0.69
0.87	0.6627	0.6896	0.9595	0.4931	0.2782	0.1017E+01	0.875	1.114	0.69
0.88	0.6565	0.6838	0.9585	0.4750	0.2820	0.1015E+01	0.885	1.114	0.69
0.89	0.6504	0.6780	0.9576	0.4560	0.2857	0.1012E+01	0.894	1.114	0.69
0.90	0.6442	0.6722	0.9567	0.4359	0.2895	0.1010E+01	0.904	1.115	0.69
0.91	0.6380	0.6664	0.9558	0.4146	0.2931	0.1008E+01	0.914	1.115	0.69
0.92	0.6318	0.6605	0.9548	0.3919	0.2967	0.1006E+01	0.923	1.115	0.69
0.93	0.6256	0.6547	0.9538	0.3675	0.3002	0.1005E+01	0.933	1.115	0.69
0.94	0.6194	0.6489	0.9529	0.3412	0.3037	0.1004E+01	0.943	1.115	0.69
0.95	0.6132	0.6430	0.9519	0.3123	0.3072	0.1002E+01	0.952	1.115	0.69
0.96	0.6070	0.6372	0.9509	0.2800	0.3105	0.1002E+01	0.962	1.115	0.69
0.97	0.6009	0.6313	0.9499	0.2431	0.3138	0.1001E+01	0.971	1.115	0.69
0.98	0.5947	0.6255	0.9489	0.1990	0.3171	0.1000E+01	0.981	1.115	0.69
0.99	0.5885	0.6196	0.9479	0.1410	0.3202	0.1000E+01	0.990	1.115	0.69
1.00	0.5824	0.6138	0.9469	0.0031	0.3234	0.1000E+01	1.000	1.115	0.69
1.01	0.5762	0.6079	0.9458	0.1418	0.3264	0.1000E+01	1.010	1.115	0.69
1.02	0.5701	0.6021	0.9448	0.2010	0.3294	0.1000E+01	1.019	1.115	0.69
1.03	0.5639	0.5963	0.9438	0.2468	0.3323	0.1001E+01	1.029	1.115	0.69
1.04	0.5578	0.5904	0.9427	0.2857	0.3351	0.1002E+01	1.038	1.116	0.69
1.05	0.5517	0.5846	0.9416	0.3201	0.3379	0.1002E+01	1.047	1.116	0.69
1.06	0.5456	0.5788	0.9406	0.3516	0.3406	0.1003E+01	1.057	1.116	0.69
1.07	0.5395	0.5730	0.9395	0.3806	0.3432	0.1005E+01	1.066	1.116	0.69
1.08	0.5335	0.5672	0.9384	0.4079	0.3458	0.1006E+01	1.076	1.116	0.69
1.09	0.5274	0.5614	0.9373	0.4337	0.3483	0.1007E+01	1.085	1.116	0.69
1.10	0.5214	0.5557	0.9362	0.4583	0.3507	0.1009E+01	1.095	1.116	0.69
1.11	0.5154	0.5499	0.9350	0.4818	0.3530	0.1011E+01	1.104	1.116	0.69
1.12	0.5094	0.5442	0.9339	0.5044	0.3553	0.1013E+01	1.113	1.116	0.69
1.13	0.5035	0.5385	0.9328	0.5262	0.3575	0.1015E+01	1.123	1.116	0.69
1.14	0.4976	0.5327	0.9316	0.5474	0.3596	0.1018E+01	1.132	1.116	0.69
1.15	0.4917	0.5271	0.9305	0.5679	0.3616	0.1020E+01	1.141	1.116	0.69
1.16	0.4858	0.5214	0.9293	0.5879	0.3636	0.1023E+01	1.150	1.117	0.69
1.17	0.4799	0.5157	0.9282	0.6074	0.3654	0.1026E+01	1.160	1.117	0.70
1.18	0.4741	0.5101	0.9270	0.6264	0.3672	0.1029E+01	1.169	1.117	0.70
1.19	0.4683	0.5045	0.9258	0.6451	0.3690	0.1033E+01	1.178	1.117	0.70
1.20	0.4625	0.4989	0.9246	0.6633	0.3706	0.1036E+01	1.187	1.117	0.70
1.21	0.4568	0.4933	0.9234	0.6813	0.3722	0.1040E+01	1.197	1.117	0.70
1.22	0.4511	0.4878	0.9222	0.6988	0.3737	0.1043E+01	1.206	1.117	0.70
1.23	0.4454	0.4823	0.9210	0.7162	0.3751	0.1047E+01	1.215	1.117	0.70
1.24	0.4398	0.4768	0.9198	0.7332	0.3764	0.1052E+01	1.224	1.117	0.70
1.25	0.4342	0.4713	0.9185	0.7500	0.3777	0.1056E+01	1.233	1.117	0.70
1.26	0.4286	0.4659	0.9173	0.7666	0.3789	0.1060E+01	1.242	1.117	0.70

1.27	0.4231	0.4605	0.9161	0.7829	0.3800	0.1065E+01	1.252	1.118	0.70
1.28	0.4176	0.4551	0.9148	0.7990	0.3810	0.1070E+01	1.261	1.118	0.70
1.29	0.4121	0.4497	0.9135	0.8149	0.3820	0.1075E+01	1.270	1.118	0.70
1.30	0.4067	0.4444	0.9123	0.8307	0.3829	0.1080E+01	1.279	1.118	0.70
1.31	0.4013	0.4391	0.9110	0.8462	0.3837	0.1085E+01	1.288	1.118	0.70
1.32	0.3959	0.4339	0.9097	0.8616	0.3844	0.1091E+01	1.297	1.118	0.70

I S E N T R O P I C E X P A N S I O N  
(Output file outmix6)

Pt(lb/sq.ft)	Tt(deg F)	Tt(deg R)	RH0t(slugs/cu.ft)	X134a	Xair	Zt
500.0	100.0	559.7	0.001773	0.950	0.050	0.9969

M	USTAR	PSTAR/Pt	TSTAR/Tt	RHOSTAR	RHOSTARxUSTAR
9.999998E-01	5.452016E+02	5.820521E-01	9.470064E-01	1.088902E-03	5.936709E-01

M	P/Pt	R/RH0t	T/Tt	BET	q/Pt	A/Astar	U/Ustar	Gamma	Pr
0.00	1.0000	1.0000	1.0000	1.0000	0.0000	0.1403E+03	0.004	1.111	0.68
0.01	0.9999	0.9999	1.0000	0.9999	0.0001	0.5990E+02	0.010	1.111	0.68
0.02	0.9998	0.9998	1.0000	0.9998	0.0002	0.2996E+02	0.020	1.111	0.68
0.03	0.9995	0.9996	1.0000	0.9995	0.0005	0.1998E+02	0.031	1.111	0.68
0.04	0.9991	0.9992	0.9999	0.9992	0.0009	0.1499E+02	0.041	1.111	0.68
0.05	0.9986	0.9988	0.9999	0.9987	0.0014	0.1200E+02	0.051	1.111	0.68
0.06	0.9980	0.9982	0.9998	0.9982	0.0020	0.1001E+02	0.061	1.111	0.68
0.07	0.9973	0.9976	0.9997	0.9975	0.0027	0.8581E+01	0.072	1.111	0.68
0.08	0.9965	0.9968	0.9996	0.9968	0.0035	0.7515E+01	0.082	1.111	0.68
0.09	0.9955	0.9960	0.9996	0.9959	0.0045	0.6685E+01	0.092	1.111	0.68
0.10	0.9945	0.9950	0.9995	0.9950	0.0055	0.6023E+01	0.102	1.111	0.68
0.11	0.9933	0.9940	0.9993	0.9939	0.0067	0.5482E+01	0.113	1.111	0.68
0.12	0.9921	0.9928	0.9992	0.9928	0.0079	0.5031E+01	0.123	1.111	0.68
0.13	0.9907	0.9916	0.9991	0.9915	0.0093	0.4650E+01	0.133	1.111	0.68
0.14	0.9892	0.9903	0.9989	0.9902	0.0107	0.4324E+01	0.143	1.111	0.68
0.15	0.9876	0.9888	0.9988	0.9887	0.0123	0.4042E+01	0.154	1.111	0.68
0.16	0.9859	0.9873	0.9986	0.9871	0.0140	0.3795E+01	0.164	1.111	0.68
0.17	0.9841	0.9857	0.9984	0.9854	0.0157	0.3578E+01	0.174	1.111	0.68
0.18	0.9822	0.9839	0.9982	0.9837	0.0176	0.3386E+01	0.184	1.111	0.68
0.19	0.9802	0.9821	0.9980	0.9818	0.0196	0.3214E+01	0.195	1.111	0.68
0.20	0.9781	0.9802	0.9978	0.9798	0.0217	0.3059E+01	0.205	1.111	0.68
0.21	0.9759	0.9782	0.9976	0.9777	0.0238	0.2920E+01	0.215	1.111	0.68
0.22	0.9736	0.9761	0.9974	0.9755	0.0261	0.2793E+01	0.225	1.111	0.68
0.23	0.9712	0.9739	0.9971	0.9732	0.0284	0.2678E+01	0.235	1.111	0.68
0.24	0.9687	0.9717	0.9968	0.9708	0.0309	0.2573E+01	0.246	1.111	0.68
0.25	0.9660	0.9693	0.9966	0.9682	0.0334	0.2476E+01	0.256	1.111	0.68
0.26	0.9633	0.9668	0.9963	0.9656	0.0361	0.2388E+01	0.266	1.111	0.68
0.27	0.9605	0.9643	0.9960	0.9629	0.0388	0.2305E+01	0.276	1.111	0.68
0.28	0.9576	0.9616	0.9957	0.9600	0.0416	0.2229E+01	0.286	1.111	0.68
0.29	0.9546	0.9589	0.9954	0.9570	0.0445	0.2159E+01	0.297	1.111	0.68
0.30	0.9515	0.9561	0.9951	0.9539	0.0474	0.2094E+01	0.307	1.111	0.68
0.31	0.9483	0.9532	0.9948	0.9507	0.0505	0.2032E+01	0.317	1.111	0.68
0.32	0.9450	0.9502	0.9944	0.9474	0.0536	0.1975E+01	0.327	1.111	0.68
0.33	0.9416	0.9471	0.9941	0.9440	0.0568	0.1922E+01	0.337	1.111	0.68
0.34	0.9382	0.9440	0.9937	0.9404	0.0601	0.1872E+01	0.347	1.111	0.68
0.35	0.9346	0.9408	0.9933	0.9367	0.0634	0.1825E+01	0.358	1.111	0.68
0.36	0.9310	0.9374	0.9929	0.9330	0.0668	0.1781E+01	0.368	1.111	0.68
0.37	0.9272	0.9341	0.9925	0.9290	0.0703	0.1739E+01	0.378	1.111	0.68
0.38	0.9234	0.9306	0.9921	0.9250	0.0739	0.1700E+01	0.388	1.111	0.68
0.39	0.9195	0.9270	0.9917	0.9208	0.0775	0.1663E+01	0.398	1.111	0.68
0.40	0.9155	0.9234	0.9913	0.9165	0.0811	0.1628E+01	0.408	1.111	0.68
0.41	0.9115	0.9197	0.9908	0.9121	0.0849	0.1595E+01	0.418	1.111	0.68
0.42	0.9073	0.9159	0.9904	0.9075	0.0887	0.1564E+01	0.429	1.111	0.68
0.43	0.9031	0.9121	0.9899	0.9028	0.0925	0.1535E+01	0.439	1.111	0.68
0.44	0.8988	0.9082	0.9895	0.8980	0.0964	0.1507E+01	0.449	1.111	0.68
0.45	0.8944	0.9042	0.9890	0.8930	0.1004	0.1480E+01	0.459	1.111	0.68
0.46	0.8900	0.9001	0.9885	0.8879	0.1043	0.1455E+01	0.469	1.111	0.68
0.47	0.8854	0.8960	0.9880	0.8827	0.1084	0.1431E+01	0.479	1.111	0.68
0.48	0.8808	0.8918	0.9875	0.8773	0.1125	0.1408E+01	0.489	1.111	0.68
0.49	0.8762	0.8875	0.9869	0.8717	0.1166	0.1386E+01	0.499	1.111	0.68
0.50	0.8714	0.8832	0.9864	0.8660	0.1207	0.1365E+01	0.509	1.111	0.68
0.51	0.8666	0.8788	0.9859	0.8602	0.1249	0.1345E+01	0.519	1.112	0.68
0.52	0.8618	0.8743	0.9853	0.8542	0.1291	0.1327E+01	0.529	1.112	0.68
0.53	0.8568	0.8698	0.9848	0.8480	0.1334	0.1309E+01	0.539	1.112	0.68
0.54	0.8518	0.8652	0.9842	0.8417	0.1377	0.1292E+01	0.549	1.112	0.68

0.55	0.8468	0.8606	0.9836	0.8352	0.1420	0.1275E+01	0.559	1.112	0.68
0.56	0.8417	0.8559	0.9830	0.8285	0.1463	0.1260E+01	0.569	1.112	0.68
0.57	0.8365	0.8512	0.9824	0.8216	0.1507	0.1245E+01	0.580	1.112	0.68
0.58	0.8313	0.8464	0.9818	0.8146	0.1550	0.1231E+01	0.590	1.112	0.68
0.59	0.8260	0.8415	0.9811	0.8074	0.1594	0.1217E+01	0.599	1.112	0.68
0.60	0.8206	0.8366	0.9805	0.8000	0.1638	0.1204E+01	0.609	1.112	0.68
0.61	0.8152	0.8316	0.9799	0.7924	0.1682	0.1192E+01	0.619	1.112	0.68
0.62	0.8098	0.8266	0.9792	0.7846	0.1726	0.1180E+01	0.629	1.112	0.68
0.63	0.8043	0.8216	0.9785	0.7766	0.1770	0.1169E+01	0.639	1.112	0.68
0.64	0.7988	0.8165	0.9779	0.7684	0.1814	0.1158E+01	0.649	1.112	0.68
0.65	0.7932	0.8113	0.9772	0.7599	0.1859	0.1148E+01	0.659	1.112	0.68
0.66	0.7876	0.8062	0.9765	0.7513	0.1903	0.1138E+01	0.669	1.112	0.68
0.67	0.7819	0.8009	0.9758	0.7424	0.1947	0.1129E+01	0.679	1.112	0.68
0.68	0.7762	0.7957	0.9751	0.7332	0.1991	0.1120E+01	0.689	1.112	0.68
0.69	0.7705	0.7904	0.9743	0.7238	0.2035	0.1112E+01	0.699	1.112	0.68
0.70	0.7647	0.7850	0.9736	0.7141	0.2079	0.1104E+01	0.709	1.112	0.68
0.71	0.7589	0.7796	0.9728	0.7042	0.2122	0.1096E+01	0.719	1.112	0.68
0.72	0.7530	0.7742	0.9721	0.6940	0.2166	0.1089E+01	0.729	1.113	0.68
0.73	0.7472	0.7688	0.9713	0.6835	0.2209	0.1082E+01	0.738	1.113	0.68
0.74	0.7412	0.7633	0.9705	0.6726	0.2252	0.1075E+01	0.748	1.113	0.68
0.75	0.7353	0.7578	0.9698	0.6614	0.2295	0.1069E+01	0.758	1.113	0.68
0.76	0.7293	0.7522	0.9690	0.6499	0.2338	0.1063E+01	0.768	1.113	0.68
0.77	0.7234	0.7467	0.9681	0.6380	0.2380	0.1057E+01	0.778	1.113	0.68
0.78	0.7173	0.7411	0.9673	0.6258	0.2422	0.1052E+01	0.788	1.113	0.68
0.79	0.7113	0.7354	0.9665	0.6131	0.2464	0.1047E+01	0.797	1.113	0.68
0.80	0.7052	0.7298	0.9657	0.6000	0.2506	0.1042E+01	0.807	1.113	0.68
0.81	0.6992	0.7241	0.9648	0.5864	0.2547	0.1038E+01	0.817	1.113	0.68
0.82	0.6931	0.7184	0.9640	0.5724	0.2587	0.1034E+01	0.827	1.113	0.69
0.83	0.6870	0.7127	0.9631	0.5578	0.2628	0.1030E+01	0.836	1.113	0.69
0.84	0.6808	0.7070	0.9622	0.5426	0.2668	0.1026E+01	0.846	1.113	0.69
0.85	0.6747	0.7013	0.9614	0.5268	0.2707	0.1023E+01	0.856	1.113	0.69
0.86	0.6685	0.6955	0.9605	0.5103	0.2746	0.1020E+01	0.866	1.113	0.69
0.87	0.6624	0.6897	0.9596	0.4931	0.2785	0.1017E+01	0.875	1.113	0.69
0.88	0.6562	0.6840	0.9587	0.4750	0.2823	0.1015E+01	0.885	1.114	0.69
0.89	0.6500	0.6782	0.9577	0.4560	0.2860	0.1012E+01	0.895	1.114	0.69
0.90	0.6439	0.6724	0.9568	0.4359	0.2897	0.1010E+01	0.904	1.114	0.69
0.91	0.6377	0.6665	0.9559	0.4146	0.2934	0.1008E+01	0.914	1.114	0.69
0.92	0.6315	0.6607	0.9549	0.3919	0.2970	0.1006E+01	0.923	1.114	0.69
0.93	0.6253	0.6549	0.9540	0.3676	0.3005	0.1005E+01	0.933	1.114	0.69
0.94	0.6191	0.6491	0.9530	0.3412	0.3040	0.1004E+01	0.943	1.114	0.69
0.95	0.6129	0.6432	0.9520	0.3123	0.3074	0.1002E+01	0.952	1.114	0.69
0.96	0.6067	0.6374	0.9510	0.2800	0.3108	0.1002E+01	0.962	1.114	0.69
0.97	0.6006	0.6315	0.9500	0.2431	0.3141	0.1001E+01	0.971	1.114	0.69
0.98	0.5944	0.6257	0.9490	0.1990	0.3173	0.1000E+01	0.981	1.114	0.69
0.99	0.5882	0.6198	0.9480	0.1411	0.3205	0.1000E+01	0.990	1.114	0.69
1.00	0.5821	0.6140	0.9470	0.0008	0.3236	0.1000E+01	1.000	1.114	0.69
1.01	0.5759	0.6082	0.9460	0.1418	0.3267	0.1000E+01	1.010	1.114	0.69
1.02	0.5698	0.6023	0.9449	0.2010	0.3297	0.1000E+01	1.019	1.115	0.69
1.03	0.5636	0.5965	0.9439	0.2468	0.3326	0.1001E+01	1.028	1.115	0.69
1.04	0.5575	0.5907	0.9428	0.2857	0.3354	0.1001E+01	1.038	1.115	0.69
1.05	0.5514	0.5849	0.9418	0.3202	0.3382	0.1002E+01	1.047	1.115	0.69
1.06	0.5453	0.5791	0.9407	0.3516	0.3409	0.1003E+01	1.057	1.115	0.69
1.07	0.5393	0.5733	0.9396	0.3807	0.3435	0.1005E+01	1.066	1.115	0.69
1.08	0.5332	0.5675	0.9385	0.4079	0.3461	0.1006E+01	1.076	1.115	0.69
1.09	0.5272	0.5617	0.9374	0.4337	0.3485	0.1007E+01	1.085	1.115	0.69
1.10	0.5212	0.5559	0.9363	0.4583	0.3509	0.1009E+01	1.094	1.115	0.69
1.11	0.5152	0.5502	0.9352	0.4817	0.3533	0.1011E+01	1.104	1.115	0.69
1.12	0.5092	0.5445	0.9341	0.5044	0.3555	0.1013E+01	1.113	1.115	0.69
1.13	0.5032	0.5387	0.9330	0.5262	0.3577	0.1015E+01	1.122	1.116	0.69
1.14	0.4973	0.5330	0.9318	0.5473	0.3598	0.1018E+01	1.132	1.116	0.69
1.15	0.4914	0.5274	0.9307	0.5679	0.3619	0.1020E+01	1.141	1.116	0.69
1.16	0.4855	0.5217	0.9295	0.5879	0.3638	0.1023E+01	1.150	1.116	0.69
1.17	0.4797	0.5161	0.9283	0.6074	0.3657	0.1026E+01	1.160	1.116	0.69
1.18	0.4739	0.5104	0.9272	0.6264	0.3675	0.1029E+01	1.169	1.116	0.69
1.19	0.4681	0.5048	0.9260	0.6450	0.3692	0.1032E+01	1.178	1.116	0.70
1.20	0.4623	0.4992	0.9248	0.6633	0.3709	0.1036E+01	1.187	1.116	0.70
1.21	0.4566	0.4937	0.9236	0.6812	0.3724	0.1040E+01	1.196	1.116	0.70
1.22	0.4509	0.4881	0.9224	0.6989	0.3739	0.1043E+01	1.206	1.116	0.70
1.23	0.4452	0.4826	0.9212	0.7162	0.3754	0.1047E+01	1.215	1.116	0.70
1.24	0.4396	0.4771	0.9200	0.7332	0.3767	0.1051E+01	1.224	1.117	0.70
1.25	0.4340	0.4717	0.9187	0.7500	0.3780	0.1056E+01	1.233	1.117	0.70
1.26	0.4284	0.4663	0.9175	0.7666	0.3791	0.1060E+01	1.242	1.117	0.70

1.27	0.4229	0.4608	0.9163	0.7829	0.3802	0.1065E+01	1.251	1.117	0.70
1.28	0.4174	0.4555	0.9150	0.7990	0.3813	0.1070E+01	1.260	1.117	0.70
1.29	0.4119	0.4501	0.9138	0.8149	0.3822	0.1075E+01	1.269	1.117	0.70
1.30	0.4065	0.4448	0.9125	0.8307	0.3831	0.1080E+01	1.278	1.117	0.70
1.31	0.4011	0.4395	0.9112	0.8462	0.3839	0.1085E+01	1.287	1.117	0.70
1.32	0.3957	0.4342	0.9099	0.8616	0.3846	0.1091E+01	1.296	1.117	0.70

I S E N T R O P I C E X P A N S I O N  
(Output file outmix6)

Pt(lb/sq.ft)	Tt(deg F)	Tt(deg R)	RH0t(slugs/cu.ft)	X134a	Xair	Zt
200.0	100.0	559.7	0.000708	0.950	0.050	0.9987

M	USTAR	PSTAR/Pt	TSTAR/Tt	RHOSTAR	RHOSTARxUSTAR
9.999993E-01	5.457975E+02	5.818709E-01	9.470849E-01	4.348338E-04	2.373312E-01

M	P/Pt	R/RH0t	T/Tt	BET	q/Pt	A/Astar	U/Ustar	Gamma	Pr
0.00	1.0000	1.0000	1.0000	1.0000	0.0000	0.1401E+03	0.004	1.110	0.68
0.01	0.9999	1.0000	1.0000	1.0000	0.0001	0.5995E+02	0.010	1.110	0.68
0.02	0.9998	0.9998	1.0000	0.9998	0.0002	0.2995E+02	0.021	1.110	0.68
0.03	0.9995	0.9996	1.0000	0.9995	0.0005	0.1998E+02	0.031	1.110	0.68
0.04	0.9991	0.9992	0.9999	0.9992	0.0009	0.1499E+02	0.041	1.110	0.68
0.05	0.9986	0.9988	0.9999	0.9987	0.0014	0.1199E+02	0.051	1.110	0.68
0.06	0.9980	0.9982	0.9998	0.9982	0.0020	0.1000E+02	0.062	1.110	0.68
0.07	0.9973	0.9976	0.9997	0.9975	0.0027	0.8580E+01	0.072	1.110	0.68
0.08	0.9965	0.9968	0.9996	0.9968	0.0035	0.7513E+01	0.082	1.110	0.68
0.09	0.9955	0.9960	0.9996	0.9959	0.0045	0.6684E+01	0.092	1.110	0.68
0.10	0.9945	0.9950	0.9995	0.9950	0.0055	0.6021E+01	0.103	1.110	0.68
0.11	0.9933	0.9940	0.9993	0.9939	0.0067	0.5480E+01	0.113	1.110	0.68
0.12	0.9921	0.9928	0.9992	0.9928	0.0079	0.5030E+01	0.123	1.110	0.68
0.13	0.9907	0.9916	0.9991	0.9915	0.0093	0.4649E+01	0.133	1.110	0.68
0.14	0.9892	0.9903	0.9989	0.9902	0.0107	0.4323E+01	0.143	1.110	0.68
0.15	0.9876	0.9888	0.9988	0.9887	0.0123	0.4041E+01	0.154	1.110	0.68
0.16	0.9859	0.9873	0.9986	0.9871	0.0140	0.3794E+01	0.164	1.110	0.68
0.17	0.9841	0.9857	0.9984	0.9854	0.0158	0.3577E+01	0.174	1.110	0.68
0.18	0.9822	0.9839	0.9982	0.9837	0.0176	0.3385E+01	0.184	1.110	0.68
0.19	0.9802	0.9821	0.9980	0.9818	0.0196	0.3213E+01	0.195	1.110	0.68
0.20	0.9781	0.9802	0.9978	0.9798	0.0217	0.3058E+01	0.205	1.110	0.68
0.21	0.9759	0.9782	0.9976	0.9777	0.0239	0.2919E+01	0.215	1.110	0.68
0.22	0.9736	0.9761	0.9974	0.9755	0.0261	0.2793E+01	0.225	1.110	0.68
0.23	0.9711	0.9739	0.9971	0.9732	0.0285	0.2678E+01	0.235	1.110	0.68
0.24	0.9686	0.9717	0.9969	0.9708	0.0309	0.2572E+01	0.246	1.110	0.68
0.25	0.9660	0.9693	0.9966	0.9682	0.0335	0.2476E+01	0.256	1.110	0.68
0.26	0.9633	0.9668	0.9963	0.9656	0.0361	0.2387E+01	0.266	1.110	0.68
0.27	0.9605	0.9643	0.9960	0.9629	0.0388	0.2305E+01	0.276	1.110	0.68
0.28	0.9576	0.9616	0.9957	0.9600	0.0416	0.2229E+01	0.287	1.110	0.68
0.29	0.9545	0.9589	0.9954	0.9570	0.0445	0.2159E+01	0.297	1.110	0.68
0.30	0.9514	0.9561	0.9951	0.9539	0.0475	0.2093E+01	0.307	1.110	0.68
0.31	0.9482	0.9532	0.9948	0.9507	0.0505	0.2032E+01	0.317	1.110	0.68
0.32	0.9450	0.9502	0.9944	0.9474	0.0536	0.1975E+01	0.327	1.110	0.68
0.33	0.9416	0.9471	0.9941	0.9440	0.0569	0.1922E+01	0.337	1.110	0.68
0.34	0.9381	0.9440	0.9937	0.9404	0.0601	0.1872E+01	0.348	1.110	0.68
0.35	0.9345	0.9408	0.9933	0.9367	0.0635	0.1825E+01	0.358	1.110	0.68
0.36	0.9309	0.9375	0.9929	0.9330	0.0669	0.1781E+01	0.368	1.110	0.68
0.37	0.9272	0.9341	0.9925	0.9290	0.0704	0.1739E+01	0.378	1.110	0.68
0.38	0.9233	0.9306	0.9921	0.9250	0.0739	0.1700E+01	0.388	1.110	0.68
0.39	0.9194	0.9270	0.9917	0.9208	0.0776	0.1663E+01	0.398	1.110	0.68
0.40	0.9154	0.9234	0.9913	0.9165	0.0812	0.1628E+01	0.408	1.110	0.68
0.41	0.9114	0.9197	0.9909	0.9121	0.0850	0.1595E+01	0.419	1.111	0.68
0.42	0.9072	0.9159	0.9904	0.9075	0.0888	0.1564E+01	0.429	1.111	0.68
0.43	0.9030	0.9121	0.9899	0.9028	0.0926	0.1534E+01	0.439	1.111	0.68
0.44	0.8987	0.9082	0.9895	0.8980	0.0965	0.1506E+01	0.449	1.111	0.68
0.45	0.8943	0.9042	0.9890	0.8930	0.1004	0.1480E+01	0.459	1.111	0.68
0.46	0.8898	0.9001	0.9885	0.8879	0.1044	0.1454E+01	0.469	1.111	0.68
0.47	0.8853	0.8960	0.9880	0.8827	0.1085	0.1430E+01	0.479	1.111	0.68
0.48	0.8807	0.8918	0.9875	0.8773	0.1126	0.1407E+01	0.489	1.111	0.68
0.49	0.8760	0.8875	0.9870	0.8717	0.1167	0.1386E+01	0.499	1.111	0.68
0.50	0.8713	0.8832	0.9864	0.8660	0.1208	0.1365E+01	0.509	1.111	0.68
0.51	0.8665	0.8788	0.9859	0.8602	0.1250	0.1345E+01	0.519	1.111	0.68
0.52	0.8616	0.8743	0.9853	0.8542	0.1293	0.1326E+01	0.530	1.111	0.68
0.53	0.8567	0.8698	0.9848	0.8480	0.1335	0.1308E+01	0.540	1.111	0.68
0.54	0.8517	0.8652	0.9842	0.8417	0.1378	0.1291E+01	0.550	1.111	0.68

0.55	0.8466	0.8606	0.9836	0.8352	0.1421	0.1275E+01	0.560	1.111	0.68
0.56	0.8415	0.8559	0.9830	0.8285	0.1464	0.1260E+01	0.570	1.111	0.68
0.57	0.8363	0.8512	0.9824	0.8217	0.1508	0.1245E+01	0.580	1.111	0.68
0.58	0.8311	0.8464	0.9818	0.8146	0.1552	0.1231E+01	0.590	1.111	0.68
0.59	0.8258	0.8415	0.9812	0.8074	0.1595	0.1217E+01	0.600	1.111	0.68
0.60	0.8205	0.8366	0.9805	0.8000	0.1639	0.1204E+01	0.610	1.111	0.68
0.61	0.8151	0.8317	0.9799	0.7924	0.1683	0.1192E+01	0.620	1.111	0.68
0.62	0.8096	0.8267	0.9792	0.7846	0.1728	0.1180E+01	0.630	1.111	0.68
0.63	0.8042	0.8216	0.9786	0.7766	0.1772	0.1169E+01	0.640	1.111	0.68
0.64	0.7986	0.8165	0.9779	0.7684	0.1816	0.1158E+01	0.649	1.111	0.68
0.65	0.7930	0.8114	0.9772	0.7599	0.1860	0.1148E+01	0.659	1.112	0.68
0.66	0.7874	0.8062	0.9765	0.7513	0.1904	0.1138E+01	0.669	1.112	0.68
0.67	0.7817	0.8010	0.9758	0.7424	0.1948	0.1129E+01	0.679	1.112	0.68
0.68	0.7760	0.7957	0.9751	0.7332	0.1993	0.1120E+01	0.689	1.112	0.68
0.69	0.7703	0.7904	0.9744	0.7238	0.2036	0.1111E+01	0.699	1.112	0.68
0.70	0.7645	0.7851	0.9736	0.7141	0.2080	0.1103E+01	0.709	1.112	0.68
0.71	0.7587	0.7797	0.9729	0.7042	0.2124	0.1096E+01	0.719	1.112	0.68
0.72	0.7529	0.7743	0.9721	0.6940	0.2168	0.1089E+01	0.729	1.112	0.68
0.73	0.7470	0.7688	0.9714	0.6834	0.2211	0.1082E+01	0.739	1.112	0.68
0.74	0.7411	0.7633	0.9706	0.6726	0.2254	0.1075E+01	0.748	1.112	0.68
0.75	0.7351	0.7578	0.9698	0.6614	0.2297	0.1069E+01	0.758	1.112	0.68
0.76	0.7292	0.7523	0.9690	0.6499	0.2340	0.1063E+01	0.768	1.112	0.68
0.77	0.7232	0.7467	0.9682	0.6380	0.2382	0.1057E+01	0.778	1.112	0.68
0.78	0.7172	0.7411	0.9674	0.6258	0.2424	0.1052E+01	0.788	1.112	0.68
0.79	0.7111	0.7355	0.9666	0.6131	0.2466	0.1047E+01	0.797	1.112	0.68
0.80	0.7050	0.7299	0.9657	0.6000	0.2507	0.1042E+01	0.807	1.112	0.68
0.81	0.6990	0.7242	0.9649	0.5864	0.2548	0.1038E+01	0.817	1.112	0.68
0.82	0.6929	0.7185	0.9640	0.5724	0.2589	0.1034E+01	0.827	1.113	0.68
0.83	0.6868	0.7128	0.9632	0.5578	0.2629	0.1030E+01	0.836	1.113	0.68
0.84	0.6806	0.7071	0.9623	0.5426	0.2669	0.1026E+01	0.846	1.113	0.69
0.85	0.6745	0.7014	0.9614	0.5268	0.2709	0.1023E+01	0.856	1.113	0.69
0.86	0.6684	0.6956	0.9605	0.5103	0.2748	0.1020E+01	0.866	1.113	0.69
0.87	0.6622	0.6898	0.9596	0.4931	0.2786	0.1017E+01	0.875	1.113	0.69
0.88	0.6560	0.6841	0.9587	0.4750	0.2824	0.1015E+01	0.885	1.113	0.69
0.89	0.6498	0.6783	0.9578	0.4559	0.2862	0.1012E+01	0.895	1.113	0.69
0.90	0.6437	0.6725	0.9569	0.4359	0.2899	0.1010E+01	0.904	1.113	0.69
0.91	0.6375	0.6666	0.9559	0.4146	0.2936	0.1008E+01	0.914	1.113	0.69
0.92	0.6313	0.6608	0.9550	0.3919	0.2972	0.1006E+01	0.924	1.113	0.69
0.93	0.6251	0.6550	0.9540	0.3675	0.3007	0.1005E+01	0.933	1.113	0.69
0.94	0.6189	0.6492	0.9531	0.3412	0.3042	0.1004E+01	0.943	1.113	0.69
0.95	0.6127	0.6433	0.9521	0.3123	0.3076	0.1002E+01	0.952	1.113	0.69
0.96	0.6066	0.6375	0.9511	0.2800	0.3110	0.1002E+01	0.962	1.114	0.69
0.97	0.6004	0.6317	0.9501	0.2431	0.3143	0.1001E+01	0.971	1.114	0.69
0.98	0.5942	0.6258	0.9491	0.1990	0.3175	0.1000E+01	0.981	1.114	0.69
0.99	0.5880	0.6200	0.9481	0.1410	0.3207	0.1000E+01	0.990	1.114	0.69
1.00	0.5819	0.6141	0.9471	0.0011	0.3238	0.1000E+01	1.000	1.114	0.69
1.01	0.5757	0.6083	0.9461	0.1417	0.3268	0.1000E+01	1.009	1.114	0.69
1.02	0.5696	0.6025	0.9450	0.2010	0.3298	0.1000E+01	1.019	1.114	0.69
1.03	0.5634	0.5966	0.9440	0.2468	0.3327	0.1001E+01	1.028	1.114	0.69
1.04	0.5573	0.5908	0.9429	0.2857	0.3356	0.1001E+01	1.038	1.114	0.69
1.05	0.5512	0.5850	0.9419	0.3202	0.3383	0.1002E+01	1.047	1.114	0.69
1.06	0.5452	0.5792	0.9408	0.3516	0.3410	0.1003E+01	1.057	1.114	0.69
1.07	0.5391	0.5734	0.9397	0.3807	0.3437	0.1005E+01	1.066	1.114	0.69
1.08	0.5330	0.5676	0.9386	0.4079	0.3462	0.1006E+01	1.076	1.115	0.69
1.09	0.5270	0.5619	0.9375	0.4337	0.3487	0.1007E+01	1.085	1.115	0.69
1.10	0.5210	0.5561	0.9364	0.4583	0.3511	0.1009E+01	1.094	1.115	0.69
1.11	0.5150	0.5504	0.9353	0.4818	0.3534	0.1011E+01	1.104	1.115	0.69
1.12	0.5090	0.5446	0.9342	0.5044	0.3557	0.1013E+01	1.113	1.115	0.69
1.13	0.5031	0.5389	0.9331	0.5262	0.3579	0.1015E+01	1.122	1.115	0.69
1.14	0.4972	0.5332	0.9319	0.5474	0.3600	0.1018E+01	1.132	1.115	0.69
1.15	0.4913	0.5275	0.9308	0.5679	0.3620	0.1020E+01	1.141	1.115	0.69
1.16	0.4854	0.5219	0.9296	0.5879	0.3640	0.1023E+01	1.150	1.115	0.69
1.17	0.4795	0.5162	0.9285	0.6074	0.3659	0.1026E+01	1.159	1.115	0.69
1.18	0.4737	0.5106	0.9273	0.6264	0.3677	0.1029E+01	1.169	1.116	0.69
1.19	0.4679	0.5050	0.9261	0.6451	0.3694	0.1032E+01	1.178	1.116	0.69
1.20	0.4622	0.4994	0.9249	0.6633	0.3710	0.1036E+01	1.187	1.116	0.70
1.21	0.4565	0.4939	0.9237	0.6812	0.3726	0.1040E+01	1.196	1.116	0.70
1.22	0.4508	0.4883	0.9225	0.6989	0.3741	0.1043E+01	1.205	1.116	0.70
1.23	0.4451	0.4828	0.9213	0.7162	0.3755	0.1047E+01	1.214	1.116	0.70
1.24	0.4395	0.4774	0.9201	0.7332	0.3768	0.1051E+01	1.224	1.116	0.70
1.25	0.4339	0.4719	0.9189	0.7500	0.3781	0.1056E+01	1.233	1.116	0.70
1.26	0.4283	0.4665	0.9176	0.7666	0.3793	0.1060E+01	1.242	1.116	0.70

1.27	0.4228	0.4611	0.9164	0.7829	0.3804	0.1065E+01	1.251	1.116	0.70
1.28	0.4173	0.4557	0.9151	0.7990	0.3814	0.1070E+01	1.260	1.117	0.70
1.29	0.4118	0.4503	0.9139	0.8149	0.3824	0.1075E+01	1.269	1.117	0.70
1.30	0.4064	0.4450	0.9126	0.8307	0.3832	0.1080E+01	1.278	1.117	0.70
1.31	0.4010	0.4397	0.9113	0.8462	0.3840	0.1085E+01	1.287	1.117	0.70
1.32	0.3956	0.4345	0.9101	0.8616	0.3848	0.1091E+01	1.296	1.117	0.70

I S E N T R O P I C E X P A N S I O N  
(Output file outmix6)

Pt(lb/sq.ft)	Tt(deg F)	Tt(deg R)	RH0t(slugs/cu.ft)	X134a	Xair	Zt
100.0	100.0	559.7	0.000354	0.950	0.050	0.9994

M	USTAR	PSTAR/Pt	TSTAR/Tt	RHOSTAR	RHOSTARxUSTAR
9.999997E-01	5.459956E+02	5.818103E-01	9.471109E-01	2.172961E-04	1.186427E-01

M	P/Pt	R/RH0t	T/Tt	BET	q/Pt	A/Astar	U/Ustar	Gamma	Pr
0.00	1.0000	1.0000	1.0000	1.0000	0.0000	0.1401E+03	0.004	1.110	0.68
0.01	0.9999	1.0000	1.0000	1.0000	0.0001	0.5994E+02	0.010	1.110	0.68
0.02	0.9998	0.9998	1.0000	0.9998	0.0002	0.2996E+02	0.021	1.110	0.68
0.03	0.9995	0.9995	1.0000	0.9995	0.0005	0.1997E+02	0.031	1.110	0.68
0.04	0.9991	0.9992	0.9999	0.9992	0.0009	0.1498E+02	0.041	1.110	0.68
0.05	0.9986	0.9988	0.9999	0.9987	0.0014	0.1199E+02	0.051	1.110	0.68
0.06	0.9980	0.9982	0.9998	0.9982	0.0020	0.1000E+02	0.062	1.110	0.68
0.07	0.9973	0.9976	0.9997	0.9975	0.0027	0.8579E+01	0.072	1.110	0.68
0.08	0.9965	0.9968	0.9996	0.9968	0.0035	0.7512E+01	0.082	1.110	0.68
0.09	0.9955	0.9960	0.9996	0.9959	0.0045	0.6684E+01	0.092	1.110	0.68
0.10	0.9945	0.9950	0.9995	0.9950	0.0055	0.6020E+01	0.103	1.110	0.68
0.11	0.9933	0.9940	0.9993	0.9939	0.0067	0.5480E+01	0.113	1.110	0.68
0.12	0.9921	0.9928	0.9992	0.9928	0.0079	0.5029E+01	0.123	1.110	0.68
0.13	0.9907	0.9916	0.9991	0.9915	0.0093	0.4648E+01	0.133	1.110	0.68
0.14	0.9892	0.9903	0.9989	0.9902	0.0108	0.4322E+01	0.143	1.110	0.68
0.15	0.9876	0.9888	0.9988	0.9887	0.0123	0.4040E+01	0.154	1.110	0.68
0.16	0.9859	0.9873	0.9986	0.9871	0.0140	0.3794E+01	0.164	1.110	0.68
0.17	0.9841	0.9857	0.9984	0.9854	0.0158	0.3577E+01	0.174	1.110	0.68
0.18	0.9822	0.9839	0.9982	0.9837	0.0176	0.3384E+01	0.184	1.110	0.68
0.19	0.9802	0.9821	0.9980	0.9818	0.0196	0.3213E+01	0.195	1.110	0.68
0.20	0.9781	0.9802	0.9978	0.9798	0.0217	0.3058E+01	0.205	1.110	0.68
0.21	0.9759	0.9782	0.9976	0.9777	0.0239	0.2919E+01	0.215	1.110	0.68
0.22	0.9736	0.9761	0.9974	0.9755	0.0261	0.2793E+01	0.225	1.110	0.68
0.23	0.9711	0.9739	0.9971	0.9732	0.0285	0.2677E+01	0.236	1.110	0.68
0.24	0.9686	0.9717	0.9969	0.9708	0.0309	0.2572E+01	0.246	1.110	0.68
0.25	0.9660	0.9693	0.9966	0.9682	0.0335	0.2476E+01	0.256	1.110	0.68
0.26	0.9633	0.9668	0.9963	0.9656	0.0361	0.2387E+01	0.266	1.110	0.68
0.27	0.9605	0.9643	0.9960	0.9629	0.0388	0.2305E+01	0.276	1.110	0.68
0.28	0.9575	0.9616	0.9957	0.9600	0.0416	0.2229E+01	0.287	1.110	0.68
0.29	0.9545	0.9589	0.9954	0.9570	0.0445	0.2158E+01	0.297	1.110	0.68
0.30	0.9514	0.9561	0.9951	0.9539	0.0475	0.2093E+01	0.307	1.110	0.68
0.31	0.9482	0.9532	0.9948	0.9507	0.0505	0.2032E+01	0.317	1.110	0.68
0.32	0.9449	0.9502	0.9944	0.9474	0.0537	0.1975E+01	0.327	1.110	0.68
0.33	0.9416	0.9471	0.9941	0.9440	0.0569	0.1922E+01	0.337	1.110	0.68
0.34	0.9381	0.9440	0.9937	0.9404	0.0602	0.1872E+01	0.348	1.110	0.68
0.35	0.9345	0.9408	0.9933	0.9367	0.0635	0.1825E+01	0.358	1.110	0.68
0.36	0.9309	0.9375	0.9929	0.9330	0.0669	0.1781E+01	0.368	1.110	0.68
0.37	0.9271	0.9341	0.9925	0.9290	0.0704	0.1739E+01	0.378	1.110	0.68
0.38	0.9233	0.9306	0.9921	0.9250	0.0740	0.1700E+01	0.388	1.110	0.68
0.39	0.9194	0.9270	0.9917	0.9208	0.0776	0.1663E+01	0.398	1.110	0.68
0.40	0.9154	0.9234	0.9913	0.9165	0.0813	0.1628E+01	0.409	1.110	0.68
0.41	0.9113	0.9197	0.9909	0.9121	0.0850	0.1595E+01	0.419	1.110	0.68
0.42	0.9072	0.9159	0.9904	0.9075	0.0888	0.1564E+01	0.429	1.110	0.68
0.43	0.9030	0.9121	0.9899	0.9028	0.0926	0.1534E+01	0.439	1.110	0.68
0.44	0.8987	0.9082	0.9895	0.8980	0.0965	0.1506E+01	0.449	1.110	0.68
0.45	0.8943	0.9042	0.9890	0.8930	0.1005	0.1480E+01	0.459	1.110	0.68
0.46	0.8898	0.9001	0.9885	0.8879	0.1045	0.1454E+01	0.469	1.110	0.68
0.47	0.8853	0.8960	0.9880	0.8827	0.1085	0.1430E+01	0.479	1.110	0.68
0.48	0.8807	0.8918	0.9875	0.8773	0.1126	0.1407E+01	0.489	1.111	0.68
0.49	0.8760	0.8875	0.9870	0.8717	0.1167	0.1386E+01	0.499	1.111	0.68
0.50	0.8713	0.8832	0.9864	0.8660	0.1209	0.1365E+01	0.509	1.111	0.68
0.51	0.8665	0.8788	0.9859	0.8602	0.1251	0.1345E+01	0.520	1.111	0.68
0.52	0.8616	0.8743	0.9853	0.8542	0.1293	0.1326E+01	0.530	1.111	0.68
0.53	0.8566	0.8698	0.9848	0.8480	0.1336	0.1308E+01	0.540	1.111	0.68
0.54	0.8517	0.8653	0.9842	0.8417	0.1378	0.1291E+01	0.550	1.111	0.68

0.55	0.8466	0.8606	0.9836	0.8352	0.1422	0.1275E+01	0.560	1.111	0.68
0.56	0.8415	0.8559	0.9830	0.8285	0.1465	0.1259E+01	0.570	1.111	0.68
0.57	0.8363	0.8512	0.9824	0.8216	0.1508	0.1245E+01	0.580	1.111	0.68
0.58	0.8311	0.8464	0.9818	0.8146	0.1552	0.1230E+01	0.590	1.111	0.68
0.59	0.8258	0.8415	0.9812	0.8074	0.1596	0.1217E+01	0.600	1.111	0.68
0.60	0.8204	0.8366	0.9805	0.8000	0.1640	0.1204E+01	0.610	1.111	0.68
0.61	0.8150	0.8317	0.9799	0.7924	0.1684	0.1192E+01	0.620	1.111	0.68
0.62	0.8096	0.8267	0.9792	0.7846	0.1728	0.1180E+01	0.630	1.111	0.68
0.63	0.8041	0.8216	0.9786	0.7766	0.1772	0.1169E+01	0.640	1.111	0.68
0.64	0.7986	0.8165	0.9779	0.7684	0.1816	0.1158E+01	0.650	1.111	0.68
0.65	0.7930	0.8114	0.9772	0.7599	0.1861	0.1148E+01	0.659	1.111	0.68
0.66	0.7874	0.8062	0.9765	0.7513	0.1905	0.1138E+01	0.669	1.111	0.68
0.67	0.7817	0.8010	0.9758	0.7424	0.1949	0.1129E+01	0.679	1.111	0.68
0.68	0.7760	0.7957	0.9751	0.7332	0.1993	0.1120E+01	0.689	1.111	0.68
0.69	0.7702	0.7904	0.9744	0.7238	0.2037	0.1111E+01	0.699	1.112	0.68
0.70	0.7645	0.7851	0.9736	0.7142	0.2081	0.1103E+01	0.709	1.112	0.68
0.71	0.7586	0.7797	0.9729	0.7042	0.2125	0.1096E+01	0.719	1.112	0.68
0.72	0.7528	0.7743	0.9721	0.6940	0.2168	0.1089E+01	0.729	1.112	0.68
0.73	0.7469	0.7688	0.9714	0.6835	0.2211	0.1082E+01	0.739	1.112	0.68
0.74	0.7410	0.7634	0.9706	0.6726	0.2255	0.1075E+01	0.748	1.112	0.68
0.75	0.7351	0.7579	0.9698	0.6614	0.2298	0.1069E+01	0.758	1.112	0.68
0.76	0.7291	0.7523	0.9690	0.6499	0.2340	0.1063E+01	0.768	1.112	0.68
0.77	0.7231	0.7467	0.9682	0.6380	0.2383	0.1057E+01	0.778	1.112	0.68
0.78	0.7171	0.7412	0.9674	0.6258	0.2425	0.1052E+01	0.788	1.112	0.68
0.79	0.7110	0.7355	0.9666	0.6131	0.2466	0.1047E+01	0.797	1.112	0.68
0.80	0.7050	0.7299	0.9657	0.6000	0.2508	0.1042E+01	0.807	1.112	0.68
0.81	0.6989	0.7242	0.9649	0.5864	0.2549	0.1038E+01	0.817	1.112	0.68
0.82	0.6928	0.7186	0.9640	0.5724	0.2590	0.1034E+01	0.827	1.112	0.68
0.83	0.6867	0.7129	0.9632	0.5578	0.2630	0.1030E+01	0.836	1.112	0.68
0.84	0.6806	0.7071	0.9623	0.5426	0.2670	0.1026E+01	0.846	1.112	0.68
0.85	0.6744	0.7014	0.9614	0.5268	0.2709	0.1023E+01	0.856	1.113	0.69
0.86	0.6683	0.6956	0.9605	0.5103	0.2748	0.1020E+01	0.866	1.113	0.69
0.87	0.6621	0.6899	0.9596	0.4931	0.2787	0.1017E+01	0.875	1.113	0.69
0.88	0.6560	0.6841	0.9587	0.4750	0.2825	0.1015E+01	0.885	1.113	0.69
0.89	0.6498	0.6783	0.9578	0.4560	0.2863	0.1012E+01	0.895	1.113	0.69
0.90	0.6436	0.6725	0.9569	0.4359	0.2900	0.1010E+01	0.904	1.113	0.69
0.91	0.6374	0.6667	0.9559	0.4146	0.2936	0.1008E+01	0.914	1.113	0.69
0.92	0.6312	0.6609	0.9550	0.3919	0.2972	0.1006E+01	0.924	1.113	0.69
0.93	0.6250	0.6550	0.9540	0.3676	0.3008	0.1005E+01	0.933	1.113	0.69
0.94	0.6189	0.6492	0.9531	0.3412	0.3042	0.1004E+01	0.943	1.113	0.69
0.95	0.6127	0.6434	0.9521	0.3123	0.3077	0.1002E+01	0.952	1.113	0.69
0.96	0.6065	0.6375	0.9511	0.2800	0.3110	0.1002E+01	0.962	1.113	0.69
0.97	0.6003	0.6317	0.9501	0.2431	0.3143	0.1001E+01	0.971	1.113	0.69
0.98	0.5941	0.6259	0.9491	0.1990	0.3176	0.1000E+01	0.981	1.114	0.69
0.99	0.5880	0.6200	0.9481	0.1411	0.3207	0.1000E+01	0.990	1.114	0.69
1.00	0.5818	0.6142	0.9471	0.0013	0.3239	0.1000E+01	1.000	1.114	0.69
1.01	0.5757	0.6083	0.9461	0.1418	0.3269	0.1000E+01	1.009	1.114	0.69
1.02	0.5695	0.6025	0.9450	0.2010	0.3299	0.1000E+01	1.019	1.114	0.69
1.03	0.5634	0.5967	0.9440	0.2468	0.3328	0.1001E+01	1.028	1.114	0.69
1.04	0.5573	0.5909	0.9430	0.2857	0.3356	0.1001E+01	1.038	1.114	0.69
1.05	0.5512	0.5851	0.9419	0.3202	0.3384	0.1002E+01	1.047	1.114	0.69
1.06	0.5451	0.5793	0.9408	0.3516	0.3411	0.1003E+01	1.057	1.114	0.69
1.07	0.5390	0.5735	0.9397	0.3807	0.3437	0.1005E+01	1.066	1.114	0.69
1.08	0.5330	0.5677	0.9387	0.4079	0.3463	0.1006E+01	1.076	1.114	0.69
1.09	0.5270	0.5619	0.9376	0.4337	0.3487	0.1007E+01	1.085	1.115	0.69
1.10	0.5209	0.5562	0.9365	0.4582	0.3512	0.1009E+01	1.094	1.115	0.69
1.11	0.5150	0.5504	0.9353	0.4818	0.3535	0.1011E+01	1.104	1.115	0.69
1.12	0.5090	0.5447	0.9342	0.5044	0.3557	0.1013E+01	1.113	1.115	0.69
1.13	0.5030	0.5390	0.9331	0.5262	0.3579	0.1015E+01	1.122	1.115	0.69
1.14	0.4971	0.5333	0.9320	0.5474	0.3600	0.1018E+01	1.132	1.115	0.69
1.15	0.4912	0.5276	0.9308	0.5679	0.3621	0.1020E+01	1.141	1.115	0.69
1.16	0.4853	0.5219	0.9297	0.5879	0.3640	0.1023E+01	1.150	1.115	0.69
1.17	0.4795	0.5163	0.9285	0.6074	0.3659	0.1026E+01	1.159	1.115	0.69
1.18	0.4737	0.5107	0.9273	0.6264	0.3677	0.1029E+01	1.169	1.115	0.69
1.19	0.4679	0.5051	0.9261	0.6451	0.3694	0.1032E+01	1.178	1.115	0.69
1.20	0.4621	0.4995	0.9250	0.6633	0.3711	0.1036E+01	1.187	1.116	0.70
1.21	0.4564	0.4940	0.9238	0.6812	0.3726	0.1040E+01	1.196	1.116	0.70
1.22	0.4507	0.4884	0.9226	0.6989	0.3741	0.1043E+01	1.205	1.116	0.70
1.23	0.4450	0.4829	0.9213	0.7162	0.3756	0.1047E+01	1.214	1.116	0.70
1.24	0.4394	0.4774	0.9201	0.7332	0.3769	0.1051E+01	1.224	1.116	0.70
1.25	0.4338	0.4720	0.9189	0.7500	0.3781	0.1056E+01	1.233	1.116	0.70
1.26	0.4282	0.4665	0.9177	0.7666	0.3793	0.1060E+01	1.242	1.116	0.70

1.27	0.4227	0.4611	0.9164	0.7829	0.3804	0.1065E+01	1.251	1.116	0.70
1.28	0.4172	0.4558	0.9152	0.7990	0.3815	0.1070E+01	1.260	1.116	0.70
1.29	0.4118	0.4504	0.9139	0.8149	0.3824	0.1075E+01	1.269	1.117	0.70
1.30	0.4063	0.4451	0.9127	0.8307	0.3833	0.1080E+01	1.278	1.117	0.70
1.31	0.4010	0.4398	0.9114	0.8462	0.3841	0.1085E+01	1.287	1.117	0.70
1.32	0.3956	0.4345	0.9101	0.8616	0.3848	0.1091E+01	1.296	1.117	0.70

I S E N T R O P I C E X P A N S I O N  
(Output file outmix6)

Pt(lb/sq.ft)	Tt(deg F)	Tt(deg R)	RH0t(slugs/cu.ft)	X134a	Xair	Zt
50.0	100.0	559.7	0.000177	0.950	0.050	0.9997

M	USTAR	PSTAR/Pt	TSTAR/Tt	RHOSTAR	RHOSTARxUSTAR
9.999998E-01	5.460946E+02	5.817802E-01	9.471240E-01	1.086179E-04	5.931567E-02

M	P/Pt	R/RH0t	T/Tt	BET	q/Pt	A/Astar	U/Ustar	Gamma	Pr
0.00	1.0000	1.0000	1.0000	1.0000	0.0000	0.1401E+03	0.004	1.109	0.68
0.01	0.9999	1.0000	1.0000	1.0000	0.0001	0.5993E+02	0.010	1.109	0.68
0.02	0.9998	0.9998	1.0000	0.9998	0.0002	0.2996E+02	0.021	1.109	0.68
0.03	0.9995	0.9996	1.0000	0.9995	0.0005	0.1997E+02	0.031	1.109	0.68
0.04	0.9991	0.9992	0.9999	0.9992	0.0009	0.1498E+02	0.041	1.109	0.68
0.05	0.9986	0.9988	0.9999	0.9987	0.0014	0.1199E+02	0.051	1.109	0.68
0.06	0.9980	0.9982	0.9998	0.9982	0.0020	0.1000E+02	0.062	1.109	0.68
0.07	0.9973	0.9976	0.9997	0.9975	0.0027	0.8578E+01	0.072	1.109	0.68
0.08	0.9965	0.9968	0.9997	0.9968	0.0035	0.7511E+01	0.082	1.110	0.68
0.09	0.9955	0.9960	0.9996	0.9959	0.0045	0.6683E+01	0.092	1.110	0.68
0.10	0.9945	0.9950	0.9995	0.9950	0.0055	0.6021E+01	0.103	1.110	0.68
0.11	0.9933	0.9940	0.9993	0.9939	0.0067	0.5480E+01	0.113	1.110	0.68
0.12	0.9920	0.9928	0.9992	0.9928	0.0079	0.5029E+01	0.123	1.110	0.68
0.13	0.9907	0.9916	0.9991	0.9915	0.0093	0.4648E+01	0.133	1.110	0.68
0.14	0.9892	0.9903	0.9989	0.9902	0.0108	0.4322E+01	0.144	1.110	0.68
0.15	0.9876	0.9888	0.9988	0.9887	0.0123	0.4040E+01	0.154	1.110	0.68
0.16	0.9859	0.9873	0.9986	0.9871	0.0140	0.3794E+01	0.164	1.110	0.68
0.17	0.9841	0.9857	0.9984	0.9854	0.0158	0.3577E+01	0.174	1.110	0.68
0.18	0.9822	0.9839	0.9982	0.9837	0.0177	0.3384E+01	0.184	1.110	0.68
0.19	0.9802	0.9821	0.9980	0.9818	0.0196	0.3213E+01	0.195	1.110	0.68
0.20	0.9781	0.9802	0.9978	0.9798	0.0217	0.3058E+01	0.205	1.110	0.68
0.21	0.9759	0.9782	0.9976	0.9777	0.0239	0.2919E+01	0.215	1.110	0.68
0.22	0.9735	0.9761	0.9974	0.9755	0.0261	0.2792E+01	0.225	1.110	0.68
0.23	0.9711	0.9739	0.9971	0.9732	0.0285	0.2677E+01	0.236	1.110	0.68
0.24	0.9686	0.9717	0.9969	0.9708	0.0309	0.2572E+01	0.246	1.110	0.68
0.25	0.9660	0.9693	0.9966	0.9682	0.0335	0.2476E+01	0.256	1.110	0.68
0.26	0.9633	0.9668	0.9963	0.9656	0.0361	0.2387E+01	0.266	1.110	0.68
0.27	0.9604	0.9643	0.9960	0.9629	0.0388	0.2305E+01	0.276	1.110	0.68
0.28	0.9575	0.9616	0.9957	0.9600	0.0416	0.2229E+01	0.287	1.110	0.68
0.29	0.9545	0.9589	0.9954	0.9570	0.0445	0.2158E+01	0.297	1.110	0.68
0.30	0.9514	0.9561	0.9951	0.9539	0.0475	0.2093E+01	0.307	1.110	0.68
0.31	0.9482	0.9532	0.9948	0.9507	0.0506	0.2032E+01	0.317	1.110	0.68
0.32	0.9449	0.9502	0.9944	0.9474	0.0537	0.1975E+01	0.327	1.110	0.68
0.33	0.9415	0.9471	0.9941	0.9440	0.0569	0.1921E+01	0.337	1.110	0.68
0.34	0.9381	0.9440	0.9937	0.9404	0.0602	0.1872E+01	0.348	1.110	0.68
0.35	0.9345	0.9408	0.9933	0.9367	0.0635	0.1825E+01	0.358	1.110	0.68
0.36	0.9309	0.9375	0.9929	0.9330	0.0669	0.1781E+01	0.368	1.110	0.68
0.37	0.9271	0.9341	0.9925	0.9290	0.0704	0.1739E+01	0.378	1.110	0.68
0.38	0.9233	0.9306	0.9921	0.9250	0.0740	0.1700E+01	0.388	1.110	0.68
0.39	0.9194	0.9270	0.9917	0.9208	0.0776	0.1663E+01	0.398	1.110	0.68
0.40	0.9154	0.9234	0.9913	0.9165	0.0813	0.1628E+01	0.409	1.110	0.68
0.41	0.9113	0.9197	0.9909	0.9121	0.0850	0.1595E+01	0.419	1.110	0.68
0.42	0.9072	0.9159	0.9904	0.9075	0.0888	0.1564E+01	0.429	1.110	0.68
0.43	0.9029	0.9121	0.9900	0.9028	0.0927	0.1534E+01	0.439	1.110	0.68
0.44	0.8986	0.9082	0.9895	0.8980	0.0965	0.1506E+01	0.449	1.110	0.68
0.45	0.8943	0.9042	0.9890	0.8930	0.1005	0.1480E+01	0.459	1.110	0.68
0.46	0.8898	0.9001	0.9885	0.8879	0.1045	0.1454E+01	0.469	1.110	0.68
0.47	0.8853	0.8960	0.9880	0.8827	0.1085	0.1430E+01	0.479	1.110	0.68
0.48	0.8807	0.8918	0.9875	0.8773	0.1126	0.1407E+01	0.489	1.110	0.68
0.49	0.8760	0.8875	0.9870	0.8717	0.1167	0.1386E+01	0.499	1.110	0.68
0.50	0.8712	0.8832	0.9864	0.8660	0.1209	0.1365E+01	0.510	1.111	0.68
0.51	0.8664	0.8788	0.9859	0.8602	0.1251	0.1345E+01	0.520	1.111	0.68
0.52	0.8616	0.8744	0.9853	0.8542	0.1293	0.1326E+01	0.530	1.111	0.68
0.53	0.8566	0.8698	0.9848	0.8480	0.1336	0.1308E+01	0.540	1.111	0.68
0.54	0.8516	0.8653	0.9842	0.8417	0.1379	0.1291E+01	0.550	1.111	0.68



0.55	0.8466	0.8606	0.9836	0.8352	0.1422	0.1275E+01	0.560	1.111	0.68
0.56	0.8414	0.8559	0.9830	0.8285	0.1465	0.1259E+01	0.570	1.111	0.68
0.57	0.8363	0.8512	0.9824	0.8216	0.1509	0.1245E+01	0.580	1.111	0.68
0.58	0.8310	0.8464	0.9818	0.8146	0.1552	0.1230E+01	0.590	1.111	0.68
0.59	0.8257	0.8415	0.9812	0.8074	0.1596	0.1217E+01	0.600	1.111	0.68
0.60	0.8204	0.8366	0.9805	0.8000	0.1640	0.1204E+01	0.610	1.111	0.68
0.61	0.8150	0.8317	0.9799	0.7924	0.1684	0.1192E+01	0.620	1.111	0.68
0.62	0.8096	0.8267	0.9792	0.7846	0.1728	0.1180E+01	0.630	1.111	0.68
0.63	0.8041	0.8216	0.9786	0.7766	0.1773	0.1169E+01	0.640	1.111	0.68
0.64	0.7985	0.8165	0.9779	0.7684	0.1817	0.1158E+01	0.650	1.111	0.68
0.65	0.7930	0.8114	0.9772	0.7599	0.1861	0.1148E+01	0.659	1.111	0.68
0.66	0.7873	0.8062	0.9765	0.7513	0.1905	0.1138E+01	0.669	1.111	0.68
0.67	0.7817	0.8010	0.9758	0.7424	0.1949	0.1129E+01	0.679	1.111	0.68
0.68	0.7760	0.7957	0.9751	0.7332	0.1993	0.1120E+01	0.689	1.111	0.68
0.69	0.7702	0.7904	0.9744	0.7238	0.2037	0.1111E+01	0.699	1.111	0.68
0.70	0.7644	0.7851	0.9736	0.7141	0.2081	0.1103E+01	0.709	1.112	0.68
0.71	0.7586	0.7797	0.9729	0.7042	0.2125	0.1096E+01	0.719	1.112	0.68
0.72	0.7528	0.7743	0.9721	0.6940	0.2168	0.1088E+01	0.729	1.112	0.68
0.73	0.7469	0.7688	0.9714	0.6835	0.2212	0.1082E+01	0.739	1.112	0.68
0.74	0.7410	0.7634	0.9706	0.6726	0.2255	0.1075E+01	0.748	1.112	0.68
0.75	0.7350	0.7579	0.9698	0.6614	0.2298	0.1069E+01	0.758	1.112	0.68
0.76	0.7291	0.7523	0.9690	0.6499	0.2341	0.1063E+01	0.768	1.112	0.68
0.77	0.7231	0.7468	0.9682	0.6380	0.2383	0.1057E+01	0.778	1.112	0.68
0.78	0.7171	0.7412	0.9674	0.6258	0.2425	0.1052E+01	0.788	1.112	0.68
0.79	0.7110	0.7355	0.9666	0.6131	0.2467	0.1047E+01	0.797	1.112	0.68
0.80	0.7050	0.7299	0.9657	0.6000	0.2508	0.1042E+01	0.807	1.112	0.68
0.81	0.6989	0.7242	0.9649	0.5864	0.2549	0.1038E+01	0.817	1.112	0.68
0.82	0.6928	0.7186	0.9641	0.5724	0.2590	0.1034E+01	0.827	1.112	0.68
0.83	0.6867	0.7129	0.9632	0.5578	0.2630	0.1030E+01	0.836	1.112	0.68
0.84	0.6806	0.7071	0.9623	0.5426	0.2670	0.1026E+01	0.846	1.112	0.68
0.85	0.6744	0.7014	0.9614	0.5268	0.2710	0.1023E+01	0.856	1.112	0.69
0.86	0.6683	0.6957	0.9605	0.5103	0.2749	0.1020E+01	0.866	1.113	0.69
0.87	0.6621	0.6899	0.9596	0.4930	0.2787	0.1017E+01	0.875	1.113	0.69
0.88	0.6559	0.6841	0.9587	0.4750	0.2825	0.1015E+01	0.885	1.113	0.69
0.89	0.6498	0.6783	0.9578	0.4560	0.2863	0.1012E+01	0.895	1.113	0.69
0.90	0.6436	0.6725	0.9569	0.4359	0.2900	0.1010E+01	0.904	1.113	0.69
0.91	0.6374	0.6667	0.9560	0.4146	0.2936	0.1008E+01	0.914	1.113	0.69
0.92	0.6312	0.6609	0.9550	0.3919	0.2972	0.1006E+01	0.924	1.113	0.69
0.93	0.6250	0.6550	0.9541	0.3675	0.3008	0.1005E+01	0.933	1.113	0.69
0.94	0.6188	0.6492	0.9531	0.3412	0.3043	0.1004E+01	0.943	1.113	0.69
0.95	0.6126	0.6434	0.9521	0.3122	0.3077	0.1002E+01	0.952	1.113	0.69
0.96	0.6065	0.6376	0.9511	0.2800	0.3111	0.1002E+01	0.962	1.113	0.69
0.97	0.6003	0.6317	0.9501	0.2431	0.3144	0.1001E+01	0.971	1.113	0.69
0.98	0.5941	0.6259	0.9492	0.1990	0.3176	0.1000E+01	0.981	1.113	0.69
0.99	0.5879	0.6200	0.9481	0.1411	0.3208	0.1000E+01	0.990	1.114	0.69
1.00	0.5818	0.6142	0.9471	0.0025	0.3239	0.1000E+01	1.000	1.114	0.69
1.01	0.5756	0.6084	0.9461	0.1418	0.3269	0.1000E+01	1.009	1.114	0.69
1.02	0.5695	0.6025	0.9451	0.2010	0.3299	0.1000E+01	1.019	1.114	0.69
1.03	0.5634	0.5967	0.9440	0.2467	0.3328	0.1001E+01	1.028	1.114	0.69
1.04	0.5573	0.5909	0.9430	0.2857	0.3356	0.1001E+01	1.038	1.114	0.69
1.05	0.5512	0.5851	0.9419	0.3202	0.3384	0.1002E+01	1.047	1.114	0.69
1.06	0.5451	0.5793	0.9408	0.3515	0.3411	0.1003E+01	1.057	1.114	0.69
1.07	0.5390	0.5735	0.9398	0.3807	0.3437	0.1005E+01	1.066	1.114	0.69
1.08	0.5329	0.5677	0.9387	0.4079	0.3463	0.1006E+01	1.076	1.114	0.69
1.09	0.5269	0.5619	0.9376	0.4337	0.3488	0.1007E+01	1.085	1.114	0.69
1.10	0.5209	0.5562	0.9365	0.4583	0.3512	0.1009E+01	1.094	1.115	0.69
1.11	0.5149	0.5505	0.9354	0.4817	0.3535	0.1011E+01	1.104	1.115	0.69
1.12	0.5090	0.5447	0.9342	0.5044	0.3558	0.1013E+01	1.113	1.115	0.69
1.13	0.5030	0.5390	0.9331	0.5262	0.3580	0.1015E+01	1.122	1.115	0.69
1.14	0.4971	0.5333	0.9320	0.5473	0.3601	0.1018E+01	1.132	1.115	0.69
1.15	0.4912	0.5276	0.9308	0.5679	0.3621	0.1020E+01	1.141	1.115	0.69
1.16	0.4853	0.5220	0.9297	0.5879	0.3640	0.1023E+01	1.150	1.115	0.69
1.17	0.4795	0.5163	0.9285	0.6074	0.3659	0.1026E+01	1.159	1.115	0.69
1.18	0.4737	0.5107	0.9273	0.6264	0.3677	0.1029E+01	1.169	1.115	0.69
1.19	0.4679	0.5051	0.9262	0.6451	0.3695	0.1032E+01	1.178	1.115	0.69
1.20	0.4621	0.4995	0.9250	0.6633	0.3711	0.1036E+01	1.187	1.116	0.70
1.21	0.4564	0.4940	0.9238	0.6812	0.3727	0.1040E+01	1.196	1.116	0.70
1.22	0.4507	0.4885	0.9226	0.6988	0.3742	0.1043E+01	1.205	1.116	0.70
1.23	0.4450	0.4829	0.9214	0.7162	0.3756	0.1047E+01	1.214	1.116	0.70
1.24	0.4394	0.4775	0.9202	0.7332	0.3769	0.1051E+01	1.224	1.116	0.70
1.25	0.4338	0.4720	0.9189	0.7500	0.3782	0.1056E+01	1.233	1.116	0.70
1.26	0.4282	0.4666	0.9177	0.7666	0.3794	0.1060E+01	1.242	1.116	0.70

1.27	0.4227	0.4612	0.9165	0.7829	0.3805	0.1065E+01	1.251	1.116	0.70
1.28	0.4172	0.4558	0.9152	0.7990	0.3815	0.1070E+01	1.260	1.116	0.70
1.29	0.4117	0.4504	0.9139	0.8149	0.3824	0.1075E+01	1.269	1.116	0.70
1.30	0.4063	0.4451	0.9127	0.8307	0.3833	0.1080E+01	1.278	1.117	0.70
1.31	0.4009	0.4398	0.9114	0.8462	0.3841	0.1085E+01	1.287	1.117	0.70
1.32	0.3956	0.4346	0.9101	0.8616	0.3848	0.1091E+01	1.296	1.117	0.70

=====  
 \*\*\* ALL DATA CASES HAVE BEEN READ AND PROCESSED - JOB IS COMPLETED \*\*\*

I S E N T R O P I C E X P A N S I O N  
(Output file outmix8)

Tt (deg F)	Pt (lb/sq. ft)	Vt (ft <sup>3</sup> /lbm-mol)	Zt	Cpt/Cvt	Prt	X134a	Xair
100.0	2200.0	0.1247E+05	0.9861	1.115	0.681	0.950	0.050
M	T(deg F)	P(psf)	Re/ft	V(ft <sup>3</sup> /lbm-mol)	Z	CP/CV	a(ft/sec)
0.00	100.0	2200.0	0.7037E+05	0.1247E+05	0.9861	1.115	553.69
0.01	100.0	2199.9	0.1653E+06	0.1247E+05	0.9861	1.115	553.69
0.02	100.0	2199.5	0.3306E+06	0.1247E+05	0.9861	1.115	553.69
0.03	100.0	2198.9	0.4959E+06	0.1248E+05	0.9861	1.115	553.68
0.04	100.0	2198.1	0.6608E+06	0.1248E+05	0.9861	1.115	553.67
0.05	99.9	2197.0	0.8259E+06	0.1249E+05	0.9861	1.115	553.66
0.06	99.9	2195.7	0.9905E+06	0.1249E+05	0.9861	1.115	553.65
0.07	99.8	2194.1	0.1155E+07	0.1250E+05	0.9861	1.115	553.63
0.08	99.8	2192.3	0.1319E+07	0.1251E+05	0.9861	1.115	553.62
0.09	99.7	2190.2	0.1483E+07	0.1252E+05	0.9861	1.115	553.60
0.10	99.7	2187.9	0.1646E+07	0.1253E+05	0.9861	1.115	553.58
0.11	99.6	2185.4	0.1809E+07	0.1255E+05	0.9862	1.115	553.55
0.12	99.6	2182.7	0.1971E+07	0.1256E+05	0.9862	1.115	553.52
0.13	99.5	2179.7	0.2133E+07	0.1258E+05	0.9862	1.115	553.49
0.14	99.4	2176.4	0.2294E+07	0.1259E+05	0.9862	1.115	553.46
0.15	99.3	2173.0	0.2454E+07	0.1261E+05	0.9862	1.115	553.43
0.16	99.2	2169.3	0.2614E+07	0.1263E+05	0.9862	1.115	553.39
0.17	99.1	2165.4	0.2773E+07	0.1265E+05	0.9863	1.115	553.36
0.18	99.0	2161.2	0.2931E+07	0.1267E+05	0.9863	1.115	553.31
0.19	98.9	2156.8	0.3089E+07	0.1270E+05	0.9863	1.115	553.27
0.20	98.8	2152.2	0.3246E+07	0.1272E+05	0.9863	1.115	553.23
0.21	98.6	2147.4	0.3401E+07	0.1275E+05	0.9863	1.115	553.18
0.22	98.5	2142.3	0.3556E+07	0.1278E+05	0.9864	1.115	553.13
0.23	98.4	2137.0	0.3710E+07	0.1280E+05	0.9864	1.115	553.08
0.24	98.2	2131.5	0.3863E+07	0.1283E+05	0.9864	1.115	553.02
0.25	98.1	2125.8	0.4015E+07	0.1287E+05	0.9864	1.115	552.96
0.26	97.9	2119.9	0.4165E+07	0.1290E+05	0.9865	1.115	552.90
0.27	97.8	2113.7	0.4315E+07	0.1293E+05	0.9865	1.115	552.84
0.28	97.6	2107.3	0.4463E+07	0.1297E+05	0.9865	1.115	552.78
0.29	97.4	2100.8	0.4610E+07	0.1301E+05	0.9866	1.115	552.71
0.30	97.2	2094.0	0.4756E+07	0.1304E+05	0.9866	1.115	552.64
0.31	97.0	2087.0	0.4900E+07	0.1308E+05	0.9866	1.115	552.57
0.32	96.8	2079.8	0.5044E+07	0.1312E+05	0.9866	1.115	552.50
0.33	96.6	2072.4	0.5186E+07	0.1317E+05	0.9867	1.115	552.42
0.34	96.4	2064.8	0.5326E+07	0.1321E+05	0.9867	1.115	552.34
0.35	96.2	2057.1	0.5465E+07	0.1326E+05	0.9868	1.115	552.26
0.36	96.0	2049.1	0.5603E+07	0.1330E+05	0.9868	1.115	552.18
0.37	95.8	2040.9	0.5739E+07	0.1335E+05	0.9868	1.115	552.09
0.38	95.6	2032.6	0.5874E+07	0.1340E+05	0.9869	1.115	552.01
0.39	95.3	2024.0	0.6007E+07	0.1345E+05	0.9869	1.115	551.92
0.40	95.1	2015.3	0.6138E+07	0.1351E+05	0.9870	1.115	551.82
0.41	94.8	2006.4	0.6268E+07	0.1356E+05	0.9870	1.115	551.73
0.42	94.6	1997.3	0.6396E+07	0.1362E+05	0.9870	1.115	551.63
0.43	94.3	1988.1	0.6522E+07	0.1367E+05	0.9871	1.115	551.53
0.44	94.1	1978.7	0.6647E+07	0.1373E+05	0.9871	1.115	551.43
0.45	93.8	1969.1	0.6770E+07	0.1379E+05	0.9872	1.115	551.32
0.46	93.5	1959.3	0.6891E+07	0.1386E+05	0.9872	1.115	551.22
0.47	93.2	1949.4	0.7011E+07	0.1392E+05	0.9873	1.115	551.11
0.48	92.9	1939.3	0.7129E+07	0.1399E+05	0.9873	1.115	550.99
0.49	92.6	1929.1	0.7244E+07	0.1405E+05	0.9874	1.115	550.88
0.50	92.3	1918.7	0.7358E+07	0.1412E+05	0.9874	1.115	550.76
0.51	92.0	1908.2	0.7470E+07	0.1419E+05	0.9875	1.115	550.64
0.52	91.7	1897.5	0.7581E+07	0.1427E+05	0.9875	1.115	550.52
0.53	91.4	1886.7	0.7689E+07	0.1434E+05	0.9876	1.115	550.40
0.54	91.1	1875.8	0.7795E+07	0.1442E+05	0.9876	1.115	550.27
0.55	90.7	1864.7	0.7900E+07	0.1449E+05	0.9877	1.115	550.14
0.56	90.4	1853.5	0.8002E+07	0.1457E+05	0.9877	1.115	550.01
0.57	90.1	1842.1	0.8103E+07	0.1465E+05	0.9878	1.116	549.88
0.58	89.7	1830.7	0.8201E+07	0.1474E+05	0.9878	1.116	549.74
0.59	89.4	1819.1	0.8298E+07	0.1482E+05	0.9879	1.116	549.60
0.60	89.0	1807.4	0.8392E+07	0.1491E+05	0.9879	1.116	549.46
0.61	88.6	1795.6	0.8485E+07	0.1500E+05	0.9880	1.116	549.32
0.62	88.3	1783.6	0.8575E+07	0.1509E+05	0.9881	1.116	549.17
0.63	87.9	1771.6	0.8663E+07	0.1518E+05	0.9881	1.116	549.02
0.64	87.5	1759.4	0.8750E+07	0.1528E+05	0.9882	1.116	548.87

0.65	87.1	1747.2	0.8834E+07	0.1537E+05	0.9882	1.116	548.72
0.66	86.7	1734.9	0.8916E+07	0.1547E+05	0.9883	1.116	548.56
0.67	86.3	1722.4	0.8996E+07	0.1558E+05	0.9884	1.116	548.41
0.68	85.9	1709.9	0.9074E+07	0.1568E+05	0.9884	1.116	548.24
0.69	85.5	1697.3	0.9149E+07	0.1578E+05	0.9885	1.116	548.08
0.70	85.1	1684.6	0.9223E+07	0.1589E+05	0.9885	1.116	547.92
0.71	84.7	1671.8	0.9294E+07	0.1600E+05	0.9886	1.116	547.75
0.72	84.2	1659.0	0.9364E+07	0.1611E+05	0.9887	1.116	547.58
0.73	83.8	1646.1	0.9431E+07	0.1623E+05	0.9887	1.116	547.40
0.74	83.4	1633.1	0.9496E+07	0.1635E+05	0.9888	1.116	547.23
0.75	82.9	1620.0	0.9559E+07	0.1646E+05	0.9889	1.116	547.05
0.76	82.5	1606.9	0.9620E+07	0.1659E+05	0.9889	1.116	546.87
0.77	82.0	1593.8	0.9679E+07	0.1671E+05	0.9890	1.116	546.69
0.78	81.6	1580.5	0.9735E+07	0.1684E+05	0.9891	1.116	546.50
0.79	81.1	1567.3	0.9790E+07	0.1697E+05	0.9891	1.116	546.31
0.80	80.6	1554.0	0.9842E+07	0.1710E+05	0.9892	1.116	546.12
0.81	80.2	1540.6	0.9892E+07	0.1723E+05	0.9893	1.116	545.93
0.82	79.7	1527.2	0.9940E+07	0.1737E+05	0.9893	1.116	545.73
0.83	79.2	1513.8	0.9986E+07	0.1751E+05	0.9894	1.116	545.54
0.84	78.7	1500.3	0.1003E+08	0.1765E+05	0.9895	1.117	545.33
0.85	78.2	1486.8	0.1007E+08	0.1780E+05	0.9895	1.117	545.13
0.86	77.7	1473.3	0.1011E+08	0.1794E+05	0.9896	1.117	544.93
0.87	77.2	1459.7	0.1015E+08	0.1809E+05	0.9897	1.117	544.72
0.88	76.7	1446.1	0.1019E+08	0.1825E+05	0.9897	1.117	544.51
0.89	76.1	1432.5	0.1022E+08	0.1840E+05	0.9898	1.117	544.29
0.90	75.6	1418.9	0.1025E+08	0.1856E+05	0.9899	1.117	544.08
0.91	75.1	1405.3	0.1028E+08	0.1873E+05	0.9899	1.117	543.86
0.92	74.6	1391.7	0.1031E+08	0.1889E+05	0.9900	1.117	543.64
0.93	74.0	1378.1	0.1033E+08	0.1906E+05	0.9901	1.117	543.42
0.94	73.5	1364.4	0.1036E+08	0.1923E+05	0.9902	1.117	543.19
0.95	72.9	1350.8	0.1038E+08	0.1941E+05	0.9902	1.117	542.96
0.96	72.4	1337.2	0.1040E+08	0.1959E+05	0.9903	1.117	542.73
0.97	71.8	1323.6	0.1041E+08	0.1977E+05	0.9904	1.117	542.50
0.98	71.2	1310.0	0.1043E+08	0.1996E+05	0.9904	1.117	542.26
0.99	70.7	1296.4	0.1044E+08	0.2014E+05	0.9905	1.117	542.02
1.00	70.1	1282.8	0.1046E+08	0.2034E+05	0.9906	1.117	541.78
1.01	69.5	1269.3	0.1047E+08	0.2053E+05	0.9907	1.117	541.54
1.02	68.9	1255.7	0.1047E+08	0.2073E+05	0.9907	1.117	541.29
1.03	68.3	1242.2	0.1048E+08	0.2094E+05	0.9908	1.118	541.05
1.04	67.7	1228.8	0.1049E+08	0.2114E+05	0.9909	1.118	540.80
1.05	67.1	1215.3	0.1049E+08	0.2135E+05	0.9909	1.118	540.54
1.06	66.5	1201.9	0.1049E+08	0.2157E+05	0.9910	1.118	540.29
1.07	65.9	1188.5	0.1049E+08	0.2179E+05	0.9911	1.118	540.03
1.08	65.3	1175.2	0.1048E+08	0.2201E+05	0.9912	1.118	539.77
1.09	64.7	1161.9	0.1048E+08	0.2224E+05	0.9912	1.118	539.50
1.10	64.1	1148.6	0.1047E+08	0.2247E+05	0.9913	1.118	539.24
1.11	63.4	1135.4	0.1047E+08	0.2271E+05	0.9914	1.118	538.97
1.12	62.8	1122.2	0.1046E+08	0.2295E+05	0.9914	1.118	538.70
1.13	62.2	1109.1	0.1045E+08	0.2319E+05	0.9915	1.118	538.43
1.14	61.5	1096.0	0.1043E+08	0.2344E+05	0.9916	1.118	538.15
1.15	60.9	1083.0	0.1042E+08	0.2369E+05	0.9917	1.118	537.87
1.16	60.2	1070.1	0.1040E+08	0.2395E+05	0.9917	1.118	537.59
1.17	59.6	1057.2	0.1039E+08	0.2422E+05	0.9918	1.118	537.31
1.18	58.9	1044.3	0.1037E+08	0.2448E+05	0.9919	1.119	537.02
1.19	58.2	1031.5	0.1035E+08	0.2476E+05	0.9920	1.119	536.73
1.20	57.5	1018.8	0.1033E+08	0.2504E+05	0.9920	1.119	536.44
1.21	56.9	1006.2	0.1030E+08	0.2532E+05	0.9921	1.119	536.15
1.22	56.2	993.6	0.1028E+08	0.2561E+05	0.9922	1.119	535.85
1.23	55.5	981.1	0.1025E+08	0.2590E+05	0.9922	1.119	535.56
1.24	54.8	968.6	0.1022E+08	0.2620E+05	0.9923	1.119	535.26
1.25	54.1	956.3	0.1019E+08	0.2651E+05	0.9924	1.119	534.95
1.26	53.4	944.0	0.1016E+08	0.2682E+05	0.9924	1.119	534.65
1.27	52.7	931.8	0.1013E+08	0.2713E+05	0.9925	1.119	534.34
1.28	52.0	919.6	0.1010E+08	0.2746E+05	0.9926	1.119	534.03
1.29	51.3	907.6	0.1007E+08	0.2778E+05	0.9927	1.119	533.72
1.30	50.6	895.6	0.1003E+08	0.2812E+05	0.9927	1.120	533.40
1.31	49.9	883.7	0.9995E+07	0.2846E+05	0.9928	1.120	533.08
1.32	49.1	871.9	0.9958E+07	0.2881E+05	0.9929	1.120	532.76

I S E N T R O P I C E X P A N S I O N  
(Output file outmix8)

Tt (deg F)	Pt (lb/sq. ft)	Vt (ft^3/lbm-mol)	Zt	Cpt/Cvt	Prt	X134a	Xair
100.0	1000.0	0.2765E+05	0.9937	1.112	0.679	0.950	0.050

M	T (deg F)	P (psf)	Re/ft	V (ft^3/lbm-mol)	Z	CP/CV	a (ft/sec)
0.00	100.0	1000.0	0.3203E+05	0.2765E+05	0.9937	1.112	557.25
0.01	100.0	999.9	0.7512E+05	0.2765E+05	0.9937	1.112	557.24
0.02	100.0	999.8	0.1501E+06	0.2765E+05	0.9937	1.112	557.24
0.03	100.0	999.5	0.2251E+06	0.2766E+05	0.9937	1.112	557.23
0.04	100.0	999.1	0.3001E+06	0.2767E+05	0.9937	1.112	557.23
0.05	99.9	998.6	0.3749E+06	0.2768E+05	0.9937	1.112	557.21
0.06	99.9	998.0	0.4496E+06	0.2770E+05	0.9937	1.112	557.20
0.07	99.8	997.3	0.5242E+06	0.2772E+05	0.9937	1.112	557.18
0.08	99.8	996.5	0.5987E+06	0.2774E+05	0.9937	1.112	557.16
0.09	99.8	995.5	0.6730E+06	0.2776E+05	0.9937	1.112	557.14
0.10	99.7	994.5	0.7471E+06	0.2779E+05	0.9937	1.112	557.12
0.11	99.6	993.3	0.8210E+06	0.2782E+05	0.9937	1.112	557.09
0.12	99.6	992.1	0.8947E+06	0.2785E+05	0.9938	1.112	557.06
0.13	99.5	990.7	0.9680E+06	0.2788E+05	0.9938	1.112	557.03
0.14	99.4	989.2	0.1041E+07	0.2792E+05	0.9938	1.112	556.99
0.15	99.3	987.7	0.1114E+07	0.2796E+05	0.9938	1.112	556.95
0.16	99.2	986.0	0.1187E+07	0.2800E+05	0.9938	1.112	556.91
0.17	99.1	984.2	0.1259E+07	0.2805E+05	0.9938	1.112	556.87
0.18	99.0	982.3	0.1331E+07	0.2810E+05	0.9938	1.112	556.82
0.19	98.9	980.3	0.1402E+07	0.2815E+05	0.9938	1.112	556.77
0.20	98.8	978.2	0.1473E+07	0.2821E+05	0.9938	1.112	556.72
0.21	98.6	976.0	0.1544E+07	0.2826E+05	0.9938	1.112	556.67
0.22	98.5	973.6	0.1614E+07	0.2832E+05	0.9938	1.112	556.61
0.23	98.4	971.2	0.1684E+07	0.2839E+05	0.9938	1.112	556.55
0.24	98.2	968.7	0.1753E+07	0.2845E+05	0.9939	1.112	556.49
0.25	98.1	966.1	0.1822E+07	0.2852E+05	0.9939	1.112	556.43
0.26	97.9	963.4	0.1890E+07	0.2860E+05	0.9939	1.112	556.36
0.27	97.8	960.6	0.1958E+07	0.2867E+05	0.9939	1.112	556.29
0.28	97.6	957.7	0.2026E+07	0.2875E+05	0.9939	1.112	556.22
0.29	97.4	954.7	0.2092E+07	0.2883E+05	0.9939	1.112	556.15
0.30	97.2	951.6	0.2159E+07	0.2892E+05	0.9939	1.112	556.07
0.31	97.1	948.4	0.2224E+07	0.2901E+05	0.9940	1.112	555.99
0.32	96.9	945.1	0.2289E+07	0.2910E+05	0.9940	1.112	555.91
0.33	96.7	941.7	0.2353E+07	0.2919E+05	0.9940	1.112	555.82
0.34	96.5	938.3	0.2417E+07	0.2929E+05	0.9940	1.112	555.73
0.35	96.3	934.7	0.2480E+07	0.2939E+05	0.9940	1.112	555.64
0.36	96.0	931.1	0.2543E+07	0.2949E+05	0.9940	1.112	555.55
0.37	95.8	927.4	0.2604E+07	0.2960E+05	0.9940	1.112	555.46
0.38	95.6	923.6	0.2665E+07	0.2971E+05	0.9941	1.112	555.36
0.39	95.3	919.7	0.2726E+07	0.2982E+05	0.9941	1.112	555.26
0.40	95.1	915.7	0.2785E+07	0.2994E+05	0.9941	1.112	555.15
0.41	94.9	911.6	0.2844E+07	0.3006E+05	0.9941	1.112	555.05
0.42	94.6	907.5	0.2902E+07	0.3019E+05	0.9941	1.112	554.94
0.43	94.4	903.3	0.2960E+07	0.3031E+05	0.9942	1.112	554.83
0.44	94.1	899.0	0.3016E+07	0.3044E+05	0.9942	1.112	554.72
0.45	93.8	894.6	0.3072E+07	0.3058E+05	0.9942	1.112	554.60
0.46	93.5	890.2	0.3127E+07	0.3072E+05	0.9942	1.112	554.48
0.47	93.3	885.6	0.3181E+07	0.3086E+05	0.9942	1.113	554.36
0.48	93.0	881.0	0.3234E+07	0.3100E+05	0.9943	1.113	554.23
0.49	92.7	876.4	0.3287E+07	0.3115E+05	0.9943	1.113	554.11
0.50	92.4	871.6	0.3338E+07	0.3131E+05	0.9943	1.113	553.98
0.51	92.1	866.8	0.3389E+07	0.3146E+05	0.9943	1.113	553.85
0.52	91.8	862.0	0.3439E+07	0.3162E+05	0.9944	1.113	553.71
0.53	91.4	857.1	0.3488E+07	0.3179E+05	0.9944	1.113	553.57
0.54	91.1	852.1	0.3536E+07	0.3196E+05	0.9944	1.113	553.43
0.55	90.8	847.0	0.3584E+07	0.3213E+05	0.9944	1.113	553.29
0.56	90.5	841.9	0.3630E+07	0.3230E+05	0.9945	1.113	553.15
0.57	90.1	836.7	0.3676E+07	0.3248E+05	0.9945	1.113	553.00
0.58	89.8	831.5	0.3720E+07	0.3267E+05	0.9945	1.113	552.85
0.59	89.4	826.2	0.3764E+07	0.3286E+05	0.9945	1.113	552.70
0.60	89.1	820.9	0.3807E+07	0.3305E+05	0.9946	1.113	552.54
0.61	88.7	815.5	0.3849E+07	0.3325E+05	0.9946	1.113	552.38
0.62	88.3	810.1	0.3889E+07	0.3345E+05	0.9946	1.113	552.22
0.63	88.0	804.6	0.3929E+07	0.3365E+05	0.9946	1.113	552.06
0.64	87.6	799.1	0.3968E+07	0.3386E+05	0.9947	1.113	551.89
0.65	87.2	793.5	0.4007E+07	0.3408E+05	0.9947	1.113	551.72
0.66	86.8	787.9	0.4044E+07	0.3430E+05	0.9947	1.113	551.55
0.67	86.4	782.2	0.4080E+07	0.3452E+05	0.9947	1.113	551.38

0.68	86.0	776.5	0.4115E+07	0.3475E+05	0.9948	1.113	551.20
0.69	85.6	770.8	0.4149E+07	0.3499E+05	0.9948	1.113	551.02
0.70	85.2	765.0	0.4183E+07	0.3522E+05	0.9948	1.113	550.84
0.71	84.8	759.2	0.4215E+07	0.3547E+05	0.9949	1.113	550.66
0.72	84.3	753.3	0.4246E+07	0.3572E+05	0.9949	1.114	550.47
0.73	83.9	747.5	0.4277E+07	0.3597E+05	0.9949	1.114	550.28
0.74	83.5	741.6	0.4306E+07	0.3623E+05	0.9949	1.114	550.09
0.75	83.0	735.6	0.4335E+07	0.3649E+05	0.9950	1.114	549.90
0.76	82.6	729.7	0.4362E+07	0.3676E+05	0.9950	1.114	549.70
0.77	82.1	723.7	0.4389E+07	0.3703E+05	0.9950	1.114	549.50
0.78	81.7	717.7	0.4414E+07	0.3731E+05	0.9951	1.114	549.30
0.79	81.2	711.6	0.4439E+07	0.3760E+05	0.9951	1.114	549.09
0.80	80.7	705.6	0.4463E+07	0.3789E+05	0.9951	1.114	548.89
0.81	80.3	699.5	0.4485E+07	0.3819E+05	0.9951	1.114	548.68
0.82	79.8	693.4	0.4507E+07	0.3849E+05	0.9952	1.114	548.46
0.83	79.3	687.3	0.4528E+07	0.3880E+05	0.9952	1.114	548.25
0.84	78.8	681.2	0.4548E+07	0.3911E+05	0.9952	1.114	548.03
0.85	78.3	675.0	0.4567E+07	0.3943E+05	0.9953	1.114	547.81
0.86	77.8	668.9	0.4585E+07	0.3976E+05	0.9953	1.114	547.59
0.87	77.3	662.7	0.4602E+07	0.4009E+05	0.9953	1.114	547.36
0.88	76.8	656.5	0.4618E+07	0.4043E+05	0.9954	1.114	547.13
0.89	76.3	650.4	0.4633E+07	0.4078E+05	0.9954	1.114	546.90
0.90	75.8	644.2	0.4647E+07	0.4113E+05	0.9954	1.115	546.67
0.91	75.2	638.0	0.4661E+07	0.4149E+05	0.9955	1.115	546.44
0.92	74.7	631.8	0.4673E+07	0.4186E+05	0.9955	1.115	546.20
0.93	74.2	625.6	0.4684E+07	0.4223E+05	0.9955	1.115	545.96
0.94	73.6	619.4	0.4695E+07	0.4261E+05	0.9956	1.115	545.71
0.95	73.1	613.2	0.4705E+07	0.4300E+05	0.9956	1.115	545.47
0.96	72.5	607.0	0.4714E+07	0.4339E+05	0.9956	1.115	545.22
0.97	72.0	600.9	0.4722E+07	0.4379E+05	0.9957	1.115	544.97
0.98	71.4	594.7	0.4729E+07	0.4420E+05	0.9957	1.115	544.72
0.99	70.8	588.5	0.4735E+07	0.4462E+05	0.9957	1.115	544.46
1.00	70.3	582.4	0.4740E+07	0.4505E+05	0.9957	1.115	544.20
1.01	69.7	576.2	0.4745E+07	0.4548E+05	0.9958	1.115	543.94
1.02	69.1	570.1	0.4748E+07	0.4592E+05	0.9958	1.115	543.68
1.03	68.5	563.9	0.4751E+07	0.4637E+05	0.9958	1.115	543.41
1.04	67.9	557.8	0.4753E+07	0.4683E+05	0.9959	1.116	543.15
1.05	67.3	551.7	0.4754E+07	0.4729E+05	0.9959	1.116	542.88
1.06	66.7	545.6	0.4755E+07	0.4777E+05	0.9959	1.116	542.60
1.07	66.1	539.5	0.4754E+07	0.4825E+05	0.9960	1.116	542.33
1.08	65.5	533.5	0.4753E+07	0.4874E+05	0.9960	1.116	542.05
1.09	64.9	527.4	0.4751E+07	0.4925E+05	0.9960	1.116	541.77
1.10	64.3	521.4	0.4748E+07	0.4976E+05	0.9961	1.116	541.48
1.11	63.6	515.4	0.4745E+07	0.5028E+05	0.9961	1.116	541.20
1.12	63.0	509.4	0.4740E+07	0.5081E+05	0.9961	1.116	540.91
1.13	62.4	503.5	0.4735E+07	0.5135E+05	0.9962	1.116	540.62
1.14	61.7	497.6	0.4730E+07	0.5190E+05	0.9962	1.116	540.33
1.15	61.1	491.7	0.4723E+07	0.5246E+05	0.9962	1.116	540.03
1.16	60.5	485.8	0.4716E+07	0.5303E+05	0.9963	1.117	539.74
1.17	59.8	479.9	0.4708E+07	0.5361E+05	0.9963	1.117	539.44
1.18	59.1	474.1	0.4700E+07	0.5420E+05	0.9963	1.117	539.13
1.19	58.5	468.3	0.4690E+07	0.5480E+05	0.9964	1.117	538.83
1.20	57.8	462.5	0.4681E+07	0.5542E+05	0.9964	1.117	538.52
1.21	57.1	456.8	0.4670E+07	0.5604E+05	0.9964	1.117	538.21
1.22	56.5	451.1	0.4659E+07	0.5668E+05	0.9965	1.117	537.90
1.23	55.8	445.4	0.4647E+07	0.5733E+05	0.9965	1.117	537.58
1.24	55.1	439.8	0.4635E+07	0.5799E+05	0.9965	1.117	537.27
1.25	54.4	434.2	0.4622E+07	0.5866E+05	0.9966	1.117	536.95
1.26	53.7	428.6	0.4608E+07	0.5934E+05	0.9966	1.117	536.62
1.27	53.0	423.1	0.4594E+07	0.6004E+05	0.9966	1.118	536.30
1.28	52.3	417.6	0.4579E+07	0.6075E+05	0.9966	1.118	535.97
1.29	51.6	412.1	0.4564E+07	0.6147E+05	0.9967	1.118	535.65
1.30	50.9	406.7	0.4548E+07	0.6221E+05	0.9967	1.118	535.31
1.31	50.2	401.3	0.4531E+07	0.6296E+05	0.9967	1.118	534.98
1.32	49.5	395.9	0.4515E+07	0.6373E+05	0.9968	1.118	534.65

I S E N T R O P I C E X P A N S I O N  
(Output file outmix8)

Tt (deg F)	Pt (lb/sq. ft)	Vt (ft^3/lbm-mol)	Zt	Cpt/Cvt	Prt	X134a	Xair
100.0	500.0	0.5547E+05	0.9969	1.111	0.678	0.950	0.050

M	T(deg F)	P(psf)	Re/ft	V(ft^3/lbm-mol)	Z	CP/CV	a(ft/sec)
0.00	100.0	500.0	0.1602E+05	0.5547E+05	0.9969	1.111	558.71
0.01	100.0	500.0	0.3752E+05	0.5547E+05	0.9969	1.111	558.71
0.02	100.0	499.9	0.7501E+05	0.5548E+05	0.9969	1.111	558.71
0.03	100.0	499.8	0.1125E+06	0.5550E+05	0.9969	1.111	558.70
0.04	100.0	499.6	0.1499E+06	0.5552E+05	0.9969	1.111	558.69
0.05	99.9	499.3	0.1873E+06	0.5554E+05	0.9969	1.111	558.68
0.06	99.9	499.0	0.2247E+06	0.5557E+05	0.9969	1.111	558.66
0.07	99.8	498.6	0.2620E+06	0.5561E+05	0.9969	1.111	558.64
0.08	99.8	498.2	0.2991E+06	0.5565E+05	0.9969	1.111	558.62
0.09	99.8	497.8	0.3363E+06	0.5570E+05	0.9969	1.111	558.60
0.10	99.7	497.2	0.3733E+06	0.5575E+05	0.9969	1.111	558.58
0.11	99.6	496.7	0.4102E+06	0.5581E+05	0.9969	1.111	558.55
0.12	99.6	496.0	0.4471E+06	0.5587E+05	0.9969	1.111	558.52
0.13	99.5	495.3	0.4838E+06	0.5594E+05	0.9969	1.111	558.48
0.14	99.4	494.6	0.5203E+06	0.5602E+05	0.9969	1.111	558.44
0.15	99.3	493.8	0.5567E+06	0.5610E+05	0.9969	1.111	558.40
0.16	99.2	493.0	0.5929E+06	0.5619E+05	0.9969	1.111	558.36
0.17	99.1	492.1	0.6290E+06	0.5628E+05	0.9969	1.111	558.32
0.18	99.0	491.1	0.6649E+06	0.5638E+05	0.9969	1.111	558.27
0.19	98.9	490.1	0.7006E+06	0.5648E+05	0.9969	1.111	558.22
0.20	98.8	489.1	0.7362E+06	0.5659E+05	0.9969	1.111	558.17
0.21	98.6	488.0	0.7715E+06	0.5671E+05	0.9969	1.111	558.11
0.22	98.5	486.8	0.8066E+06	0.5683E+05	0.9969	1.111	558.05
0.23	98.4	485.6	0.8415E+06	0.5696E+05	0.9969	1.111	557.99
0.24	98.2	484.3	0.8761E+06	0.5709E+05	0.9969	1.111	557.92
0.25	98.1	483.0	0.9105E+06	0.5723E+05	0.9969	1.111	557.86
0.26	97.9	481.7	0.9446E+06	0.5738E+05	0.9969	1.111	557.79
0.27	97.8	480.3	0.9786E+06	0.5753E+05	0.9970	1.111	557.72
0.28	97.6	478.8	0.1012E+07	0.5768E+05	0.9970	1.111	557.64
0.29	97.4	477.3	0.1046E+07	0.5785E+05	0.9970	1.111	557.56
0.30	97.2	475.7	0.1079E+07	0.5802E+05	0.9970	1.111	557.48
0.31	97.1	474.2	0.1111E+07	0.5820E+05	0.9970	1.111	557.40
0.32	96.9	472.5	0.1144E+07	0.5838E+05	0.9970	1.111	557.31
0.33	96.7	470.8	0.1176E+07	0.5857E+05	0.9970	1.111	557.22
0.34	96.5	469.1	0.1208E+07	0.5876E+05	0.9970	1.111	557.13
0.35	96.3	467.3	0.1239E+07	0.5896E+05	0.9970	1.111	557.04
0.36	96.0	465.5	0.1270E+07	0.5917E+05	0.9970	1.111	556.94
0.37	95.8	463.6	0.1301E+07	0.5939E+05	0.9970	1.111	556.84
0.38	95.6	461.7	0.1332E+07	0.5961E+05	0.9970	1.111	556.74
0.39	95.4	459.8	0.1362E+07	0.5984E+05	0.9970	1.111	556.64
0.40	95.1	457.8	0.1392E+07	0.6007E+05	0.9971	1.111	556.53
0.41	94.9	455.7	0.1421E+07	0.6031E+05	0.9971	1.111	556.42
0.42	94.6	453.7	0.1450E+07	0.6056E+05	0.9971	1.111	556.30
0.43	94.4	451.5	0.1479E+07	0.6082E+05	0.9971	1.111	556.19
0.44	94.1	449.4	0.1507E+07	0.6108E+05	0.9971	1.111	556.07
0.45	93.8	447.2	0.1535E+07	0.6135E+05	0.9971	1.111	555.95
0.46	93.6	445.0	0.1562E+07	0.6163E+05	0.9971	1.111	555.83
0.47	93.3	442.7	0.1589E+07	0.6191E+05	0.9971	1.111	555.70
0.48	93.0	440.4	0.1616E+07	0.6220E+05	0.9971	1.111	555.57
0.49	92.7	438.1	0.1642E+07	0.6250E+05	0.9972	1.111	555.44
0.50	92.4	435.7	0.1668E+07	0.6281E+05	0.9972	1.111	555.30
0.51	92.1	433.3	0.1693E+07	0.6312E+05	0.9972	1.112	555.17
0.52	91.8	430.9	0.1718E+07	0.6345E+05	0.9972	1.112	555.03
0.53	91.5	428.4	0.1743E+07	0.6377E+05	0.9972	1.112	554.88
0.54	91.1	425.9	0.1767E+07	0.6411E+05	0.9972	1.112	554.74
0.55	90.8	423.4	0.1790E+07	0.6446E+05	0.9972	1.112	554.59
0.56	90.5	420.8	0.1814E+07	0.6481E+05	0.9972	1.112	554.44
0.57	90.1	418.2	0.1836E+07	0.6517E+05	0.9972	1.112	554.29
0.58	89.8	415.6	0.1859E+07	0.6554E+05	0.9973	1.112	554.13
0.59	89.4	413.0	0.1880E+07	0.6592E+05	0.9973	1.112	553.97
0.60	89.1	410.3	0.1902E+07	0.6631E+05	0.9973	1.112	553.81
0.61	88.7	407.6	0.1923E+07	0.6670E+05	0.9973	1.112	553.64
0.62	88.4	404.9	0.1943E+07	0.6711E+05	0.9973	1.112	553.48
0.63	88.0	402.2	0.1963E+07	0.6752E+05	0.9973	1.112	553.31
0.64	87.6	399.4	0.1982E+07	0.6794E+05	0.9973	1.112	553.14
0.65	87.2	396.6	0.2001E+07	0.6837E+05	0.9973	1.112	552.96
0.66	86.8	393.8	0.2020E+07	0.6881E+05	0.9974	1.112	552.78
0.67	86.4	391.0	0.2038E+07	0.6926E+05	0.9974	1.112	552.60
0.68	86.0	388.1	0.2056E+07	0.6972E+05	0.9974	1.112	552.42
0.69	85.6	385.2	0.2073E+07	0.7019E+05	0.9974	1.112	552.24
0.70	85.2	382.3	0.2089E+07	0.7066E+05	0.9974	1.112	552.05

0.71	84.8	379.4	0.2106E+07	0.7115E+05	0.9974	1.112	551.86
0.72	84.4	376.5	0.2121E+07	0.7165E+05	0.9974	1.113	551.66
0.73	83.9	373.6	0.2136E+07	0.7216E+05	0.9975	1.113	551.47
0.74	83.5	370.6	0.2151E+07	0.7268E+05	0.9975	1.113	551.27
0.75	83.1	367.7	0.2165E+07	0.7320E+05	0.9975	1.113	551.07
0.76	82.6	364.7	0.2179E+07	0.7374E+05	0.9975	1.113	550.87
0.77	82.2	361.7	0.2192E+07	0.7429E+05	0.9975	1.113	550.66
0.78	81.7	358.7	0.2205E+07	0.7485E+05	0.9975	1.113	550.45
0.79	81.3	355.7	0.2217E+07	0.7543E+05	0.9975	1.113	550.24
0.80	80.8	352.6	0.2229E+07	0.7601E+05	0.9976	1.113	550.02
0.81	80.3	349.6	0.2240E+07	0.7660E+05	0.9976	1.113	549.81
0.82	79.8	346.5	0.2251E+07	0.7721E+05	0.9976	1.113	549.59
0.83	79.4	343.5	0.2262E+07	0.7783E+05	0.9976	1.113	549.37
0.84	78.9	340.4	0.2272E+07	0.7846E+05	0.9976	1.113	549.14
0.85	78.4	337.3	0.2281E+07	0.7910E+05	0.9976	1.113	548.91
0.86	77.9	334.3	0.2290E+07	0.7976E+05	0.9977	1.113	548.69
0.87	77.4	331.2	0.2298E+07	0.8042E+05	0.9977	1.113	548.45
0.88	76.9	328.1	0.2306E+07	0.8110E+05	0.9977	1.114	548.22
0.89	76.3	325.0	0.2314E+07	0.8180E+05	0.9977	1.114	547.98
0.90	75.8	321.9	0.2321E+07	0.8250E+05	0.9977	1.114	547.74
0.91	75.3	318.8	0.2328E+07	0.8322E+05	0.9977	1.114	547.50
0.92	74.8	315.7	0.2334E+07	0.8396E+05	0.9978	1.114	547.25
0.93	74.2	312.7	0.2340E+07	0.8470E+05	0.9978	1.114	547.01
0.94	73.7	309.6	0.2345E+07	0.8547E+05	0.9978	1.114	546.76
0.95	73.1	306.5	0.2350E+07	0.8624E+05	0.9978	1.114	546.50
0.96	72.6	303.4	0.2354E+07	0.8703E+05	0.9978	1.114	546.25
0.97	72.0	300.3	0.2358E+07	0.8784E+05	0.9978	1.114	545.99
0.98	71.5	297.2	0.2362E+07	0.8866E+05	0.9978	1.114	545.73
0.99	70.9	294.1	0.2365E+07	0.8949E+05	0.9979	1.114	545.47
1.00	70.3	291.0	0.2367E+07	0.9034E+05	0.9979	1.114	545.20
1.01	69.8	288.0	0.2370E+07	0.9121E+05	0.9979	1.114	544.93
1.02	69.2	284.9	0.2372E+07	0.9209E+05	0.9979	1.115	544.66
1.03	68.6	281.8	0.2373E+07	0.9300E+05	0.9979	1.115	544.39
1.04	68.0	278.8	0.2374E+07	0.9391E+05	0.9979	1.115	544.12
1.05	67.4	275.7	0.2374E+07	0.9485E+05	0.9980	1.115	543.84
1.06	66.8	272.7	0.2375E+07	0.9580E+05	0.9980	1.115	543.56
1.07	66.2	269.6	0.2374E+07	0.9677E+05	0.9980	1.115	543.27
1.08	65.6	266.6	0.2374E+07	0.9775E+05	0.9980	1.115	542.99
1.09	65.0	263.6	0.2373E+07	0.9876E+05	0.9980	1.115	542.70
1.10	64.4	260.6	0.2371E+07	0.9978E+05	0.9980	1.115	542.41
1.11	63.7	257.6	0.2370E+07	0.1008E+06	0.9981	1.115	542.12
1.12	63.1	254.6	0.2368E+07	0.1019E+06	0.9981	1.115	541.82
1.13	62.5	251.6	0.2365E+07	0.1030E+06	0.9981	1.116	541.53
1.14	61.8	248.7	0.2362E+07	0.1041E+06	0.9981	1.116	541.23
1.15	61.2	245.7	0.2359E+07	0.1052E+06	0.9981	1.116	540.92
1.16	60.5	242.8	0.2355E+07	0.1063E+06	0.9981	1.116	540.62
1.17	59.9	239.8	0.2351E+07	0.1075E+06	0.9982	1.116	540.31
1.18	59.2	236.9	0.2347E+07	0.1087E+06	0.9982	1.116	540.00
1.19	58.6	234.0	0.2343E+07	0.1099E+06	0.9982	1.116	539.69
1.20	57.9	231.2	0.2338E+07	0.1111E+06	0.9982	1.116	539.38
1.21	57.2	228.3	0.2332E+07	0.1124E+06	0.9982	1.116	539.06
1.22	56.6	225.4	0.2327E+07	0.1136E+06	0.9982	1.116	538.74
1.23	55.9	222.6	0.2321E+07	0.1149E+06	0.9982	1.116	538.42
1.24	55.2	219.8	0.2315E+07	0.1163E+06	0.9983	1.117	538.10
1.25	54.5	217.0	0.2308E+07	0.1176E+06	0.9983	1.117	537.77
1.26	53.8	214.2	0.2301E+07	0.1190E+06	0.9983	1.117	537.44
1.27	53.1	211.4	0.2294E+07	0.1204E+06	0.9983	1.117	537.11
1.28	52.4	208.7	0.2287E+07	0.1218E+06	0.9983	1.117	536.78
1.29	51.7	206.0	0.2279E+07	0.1232E+06	0.9983	1.117	536.44
1.30	51.0	203.2	0.2271E+07	0.1247E+06	0.9984	1.117	536.10
1.31	50.3	200.5	0.2263E+07	0.1262E+06	0.9984	1.117	535.76
1.32	49.6	197.9	0.2255E+07	0.1277E+06	0.9984	1.117	535.42

I S E N T R O P I C E X P A N S I O N  
(Output file outmix8)

Tt(deg F)	Pt(lb/sq.ft)	Vt(ft^3/lbm-mol)	Zt	Cpt/Cvt	Prt	X134a	Xair
100.0	200.0	0.1389E+06	0.9987	1.110	0.677	0.950	0.050
M	T(deg F)	P(psf)	Re/ft	V(ft^3/lbm-mol)	Z	CP/CV	a(ft/sec)
0.00	100.0	200.0	0.6411E+04	0.1389E+06	0.9987	1.110	559.59
0.01	100.0	200.0	0.1499E+05	0.1389E+06	0.9987	1.110	559.59



0.02	100.0	200.0	0.3000E+05	0.1390E+06	0.9987	1.110	559.58
0.03	100.0	199.9	0.4498E+05	0.1390E+06	0.9987	1.110	559.57
0.04	100.0	199.8	0.5995E+05	0.1391E+06	0.9987	1.110	559.56
0.05	99.9	199.7	0.7491E+05	0.1391E+06	0.9987	1.110	559.55
0.06	99.9	199.6	0.8983E+05	0.1392E+06	0.9987	1.110	559.54
0.07	99.8	199.5	0.1047E+06	0.1393E+06	0.9988	1.110	559.52
0.08	99.8	199.3	0.1196E+06	0.1394E+06	0.9988	1.110	559.50
0.09	99.8	199.1	0.1345E+06	0.1395E+06	0.9988	1.110	559.47
0.10	99.7	198.9	0.1493E+06	0.1396E+06	0.9988	1.110	559.45
0.11	99.6	198.7	0.1640E+06	0.1398E+06	0.9988	1.110	559.42
0.12	99.6	198.4	0.1788E+06	0.1399E+06	0.9988	1.110	559.38
0.13	99.5	198.1	0.1934E+06	0.1401E+06	0.9988	1.110	559.35
0.14	99.4	197.8	0.2080E+06	0.1403E+06	0.9988	1.110	559.31
0.15	99.3	197.5	0.2226E+06	0.1405E+06	0.9988	1.110	559.27
0.16	99.2	197.2	0.2371E+06	0.1407E+06	0.9988	1.110	559.23
0.17	99.1	196.8	0.2515E+06	0.1410E+06	0.9988	1.110	559.18
0.18	99.0	196.4	0.2659E+06	0.1412E+06	0.9988	1.110	559.13
0.19	98.9	196.0	0.2802E+06	0.1415E+06	0.9988	1.110	559.08
0.20	98.8	195.6	0.2944E+06	0.1417E+06	0.9988	1.110	559.03
0.21	98.7	195.2	0.3085E+06	0.1420E+06	0.9988	1.110	558.97
0.22	98.5	194.7	0.3225E+06	0.1423E+06	0.9988	1.110	558.91
0.23	98.4	194.2	0.3365E+06	0.1427E+06	0.9988	1.110	558.85
0.24	98.2	193.7	0.3503E+06	0.1430E+06	0.9988	1.110	558.78
0.25	98.1	193.2	0.3641E+06	0.1433E+06	0.9988	1.110	558.71
0.26	97.9	192.7	0.3777E+06	0.1437E+06	0.9988	1.110	558.64
0.27	97.8	192.1	0.3913E+06	0.1441E+06	0.9988	1.110	558.57
0.28	97.6	191.5	0.4047E+06	0.1445E+06	0.9988	1.110	558.49
0.29	97.4	190.9	0.4181E+06	0.1449E+06	0.9988	1.110	558.41
0.30	97.3	190.3	0.4313E+06	0.1453E+06	0.9988	1.110	558.33
0.31	97.1	189.6	0.4444E+06	0.1458E+06	0.9988	1.110	558.24
0.32	96.9	189.0	0.4573E+06	0.1462E+06	0.9988	1.110	558.15
0.33	96.7	188.3	0.4702E+06	0.1467E+06	0.9988	1.110	558.06
0.34	96.5	187.6	0.4829E+06	0.1472E+06	0.9988	1.110	557.97
0.35	96.3	186.9	0.4955E+06	0.1477E+06	0.9988	1.110	557.87
0.36	96.0	186.2	0.5080E+06	0.1482E+06	0.9988	1.110	557.77
0.37	95.8	185.4	0.5203E+06	0.1487E+06	0.9988	1.110	557.67
0.38	95.6	184.7	0.5325E+06	0.1493E+06	0.9988	1.110	557.57
0.39	95.4	183.9	0.5445E+06	0.1499E+06	0.9988	1.110	557.46
0.40	95.1	183.1	0.5564E+06	0.1505E+06	0.9988	1.110	557.35
0.41	94.9	182.3	0.5682E+06	0.1511E+06	0.9988	1.111	557.23
0.42	94.6	181.4	0.5798E+06	0.1517E+06	0.9988	1.111	557.12
0.43	94.4	180.6	0.5912E+06	0.1523E+06	0.9988	1.111	557.00
0.44	94.1	179.7	0.6025E+06	0.1530E+06	0.9988	1.111	556.88
0.45	93.8	178.9	0.6136E+06	0.1537E+06	0.9988	1.111	556.76
0.46	93.6	178.0	0.6246E+06	0.1544E+06	0.9988	1.111	556.63
0.47	93.3	177.1	0.6354E+06	0.1551E+06	0.9989	1.111	556.50
0.48	93.0	176.1	0.6461E+06	0.1558E+06	0.9989	1.111	556.37
0.49	92.7	175.2	0.6566E+06	0.1566E+06	0.9989	1.111	556.23
0.50	92.4	174.3	0.6669E+06	0.1573E+06	0.9989	1.111	556.09
0.51	92.1	173.3	0.6770E+06	0.1581E+06	0.9989	1.111	555.95
0.52	91.8	172.3	0.6870E+06	0.1589E+06	0.9989	1.111	555.81
0.53	91.5	171.3	0.6968E+06	0.1597E+06	0.9989	1.111	555.66
0.54	91.2	170.3	0.7064E+06	0.1606E+06	0.9989	1.111	555.52
0.55	90.8	169.3	0.7158E+06	0.1614E+06	0.9989	1.111	555.36
0.56	90.5	168.3	0.7251E+06	0.1623E+06	0.9989	1.111	555.21
0.57	90.2	167.3	0.7342E+06	0.1632E+06	0.9989	1.111	555.05
0.58	89.8	166.2	0.7431E+06	0.1642E+06	0.9989	1.111	554.89
0.59	89.5	165.2	0.7518E+06	0.1651E+06	0.9989	1.111	554.73
0.60	89.1	164.1	0.7603E+06	0.1661E+06	0.9989	1.111	554.57
0.61	88.7	163.0	0.7687E+06	0.1671E+06	0.9989	1.111	554.40
0.62	88.4	161.9	0.7768E+06	0.1681E+06	0.9989	1.111	554.23
0.63	88.0	160.8	0.7848E+06	0.1691E+06	0.9989	1.111	554.06
0.64	87.6	159.7	0.7926E+06	0.1702E+06	0.9989	1.111	553.88
0.65	87.2	158.6	0.8002E+06	0.1712E+06	0.9989	1.112	553.70
0.66	86.9	157.5	0.8076E+06	0.1723E+06	0.9989	1.112	553.52
0.67	86.5	156.3	0.8148E+06	0.1735E+06	0.9990	1.112	553.34
0.68	86.1	155.2	0.8218E+06	0.1746E+06	0.9990	1.112	553.15
0.69	85.7	154.1	0.8286E+06	0.1758E+06	0.9990	1.112	552.96
0.70	85.2	152.9	0.8353E+06	0.1770E+06	0.9990	1.112	552.77
0.71	84.8	151.7	0.8417E+06	0.1782E+06	0.9990	1.112	552.57
0.72	84.4	150.6	0.8480E+06	0.1794E+06	0.9990	1.112	552.38
0.73	84.0	149.4	0.8541E+06	0.1807E+06	0.9990	1.112	552.18

0.74	83.5	148.2	0.8599E+06	0.1820E+06	0.9990	1.112	551.98
0.75	83.1	147.0	0.8656E+06	0.1833E+06	0.9990	1.112	551.77
0.76	82.6	145.8	0.8711E+06	0.1847E+06	0.9990	1.112	551.56
0.77	82.2	144.6	0.8764E+06	0.1861E+06	0.9990	1.112	551.35
0.78	81.7	143.4	0.8815E+06	0.1875E+06	0.9990	1.112	551.14
0.79	81.3	142.2	0.8864E+06	0.1889E+06	0.9990	1.112	550.92
0.80	80.8	141.0	0.8911E+06	0.1904E+06	0.9990	1.112	550.70
0.81	80.3	139.8	0.8956E+06	0.1919E+06	0.9990	1.112	550.48
0.82	79.9	138.6	0.9000E+06	0.1934E+06	0.9990	1.113	550.26
0.83	79.4	137.4	0.9041E+06	0.1949E+06	0.9990	1.113	550.03
0.84	78.9	136.1	0.9081E+06	0.1965E+06	0.9991	1.113	549.81
0.85	78.4	134.9	0.9118E+06	0.1981E+06	0.9991	1.113	549.57
0.86	77.9	133.7	0.9154E+06	0.1997E+06	0.9991	1.113	549.34
0.87	77.4	132.4	0.9188E+06	0.2014E+06	0.9991	1.113	549.10
0.88	76.9	131.2	0.9220E+06	0.2031E+06	0.9991	1.113	548.87
0.89	76.4	130.0	0.9250E+06	0.2049E+06	0.9991	1.113	548.62
0.90	75.9	128.7	0.9279E+06	0.2066E+06	0.9991	1.113	548.38
0.91	75.3	127.5	0.9305E+06	0.2084E+06	0.9991	1.113	548.13
0.92	74.8	126.3	0.9330E+06	0.2103E+06	0.9991	1.113	547.88
0.93	74.3	125.0	0.9353E+06	0.2121E+06	0.9991	1.113	547.63
0.94	73.7	123.8	0.9374E+06	0.2140E+06	0.9991	1.113	547.38
0.95	73.2	122.5	0.9393E+06	0.2160E+06	0.9991	1.113	547.12
0.96	72.6	121.3	0.9411E+06	0.2179E+06	0.9991	1.114	546.86
0.97	72.1	120.1	0.9427E+06	0.2200E+06	0.9991	1.114	546.60
0.98	71.5	118.8	0.9441E+06	0.2220E+06	0.9991	1.114	546.33
0.99	71.0	117.6	0.9453E+06	0.2241E+06	0.9991	1.114	546.07
1.00	70.4	116.4	0.9464E+06	0.2262E+06	0.9992	1.114	545.80
1.01	69.8	115.1	0.9473E+06	0.2284E+06	0.9992	1.114	545.53
1.02	69.2	113.9	0.9480E+06	0.2306E+06	0.9992	1.114	545.25
1.03	68.6	112.7	0.9485E+06	0.2329E+06	0.9992	1.114	544.97
1.04	68.1	111.5	0.9489E+06	0.2352E+06	0.9992	1.114	544.69
1.05	67.5	110.2	0.9492E+06	0.2375E+06	0.9992	1.114	544.41
1.06	66.9	109.0	0.9492E+06	0.2399E+06	0.9992	1.114	544.13
1.07	66.3	107.8	0.9491E+06	0.2423E+06	0.9992	1.114	543.84
1.08	65.6	106.6	0.9489E+06	0.2448E+06	0.9992	1.115	543.55
1.09	65.0	105.4	0.9485E+06	0.2473E+06	0.9992	1.115	543.26
1.10	64.4	104.2	0.9479E+06	0.2498E+06	0.9992	1.115	542.96
1.11	63.8	103.0	0.9472E+06	0.2525E+06	0.9992	1.115	542.67
1.12	63.2	101.8	0.9464E+06	0.2551E+06	0.9992	1.115	542.37
1.13	62.5	100.6	0.9454E+06	0.2578E+06	0.9992	1.115	542.07
1.14	61.9	99.4	0.9442E+06	0.2606E+06	0.9992	1.115	541.76
1.15	61.3	98.3	0.9430E+06	0.2634E+06	0.9992	1.115	541.46
1.16	60.6	97.1	0.9415E+06	0.2662E+06	0.9993	1.115	541.15
1.17	60.0	95.9	0.9400E+06	0.2691E+06	0.9993	1.115	540.84
1.18	59.3	94.7	0.9383E+06	0.2721E+06	0.9993	1.116	540.52
1.19	58.6	93.6	0.9364E+06	0.2751E+06	0.9993	1.116	540.21
1.20	58.0	92.4	0.9344E+06	0.2782E+06	0.9993	1.116	539.89
1.21	57.3	91.3	0.9323E+06	0.2813E+06	0.9993	1.116	539.57
1.22	56.6	90.2	0.9301E+06	0.2845E+06	0.9993	1.116	539.24
1.23	56.0	89.0	0.9278E+06	0.2878E+06	0.9993	1.116	538.92
1.24	55.3	87.9	0.9253E+06	0.2911E+06	0.9993	1.116	538.59
1.25	54.6	86.8	0.9227E+06	0.2944E+06	0.9993	1.116	538.26
1.26	53.9	85.7	0.9200E+06	0.2979E+06	0.9993	1.116	537.93
1.27	53.2	84.6	0.9172E+06	0.3013E+06	0.9993	1.116	537.59
1.28	52.5	83.5	0.9142E+06	0.3049E+06	0.9993	1.117	537.26
1.29	51.8	82.4	0.9112E+06	0.3085E+06	0.9993	1.117	536.92
1.30	51.1	81.3	0.9080E+06	0.3122E+06	0.9993	1.117	536.58
1.31	50.4	80.2	0.9047E+06	0.3160E+06	0.9994	1.117	536.23
1.32	49.7	79.1	0.9014E+06	0.3198E+06	0.9994	1.117	535.89

I S E N T R O P I C E X P A N S I O N  
(Output file outmix8)

Tt (deg F)	Pt (lb/sq. ft)	Vt (ft^3/lbm-mol)	Zt	Cpt/Cvt	Prt	X134a	Xair
100.0	100.0	0.2781E+06	0.9994	1.110	0.677	0.950	0.050
M	T (deg F)	P (psf)	Re/ft	V (ft^3/lbm-mol)	Z	CP/CV	a (ft/sec)
0.00	100.0	100.0	0.3206E+04	0.2781E+06	0.9994	1.110	559.88
0.01	100.0	100.0	0.7493E+04	0.2781E+06	0.9994	1.110	559.88
0.02	100.0	100.0	0.1499E+05	0.2781E+06	0.9994	1.110	559.87
0.03	100.0	100.0	0.2249E+05	0.2782E+06	0.9994	1.110	559.87
0.04	100.0	99.9	0.2998E+05	0.2783E+06	0.9994	1.110	559.86

0.05	99.9	99.9	0.3745E+05	0.2784E+06	0.9994	1.110	559.84
0.06	99.9	99.8	0.4491E+05	0.2786E+06	0.9994	1.110	559.83
0.07	99.9	99.7	0.5237E+05	0.2787E+06	0.9994	1.110	559.81
0.08	99.8	99.6	0.5981E+05	0.2789E+06	0.9994	1.110	559.79
0.09	99.8	99.6	0.6723E+05	0.2792E+06	0.9994	1.110	559.76
0.10	99.7	99.4	0.7464E+05	0.2794E+06	0.9994	1.110	559.74
0.11	99.6	99.3	0.8201E+05	0.2797E+06	0.9994	1.110	559.71
0.12	99.6	99.2	0.8937E+05	0.2801E+06	0.9994	1.110	559.67
0.13	99.5	99.1	0.9670E+05	0.2804E+06	0.9994	1.110	559.64
0.14	99.4	98.9	0.1040E+06	0.2808E+06	0.9994	1.110	559.60
0.15	99.3	98.8	0.1113E+06	0.2812E+06	0.9994	1.110	559.56
0.16	99.2	98.6	0.1185E+06	0.2816E+06	0.9994	1.110	559.52
0.17	99.1	98.4	0.1257E+06	0.2821E+06	0.9994	1.110	559.47
0.18	99.0	98.2	0.1329E+06	0.2826E+06	0.9994	1.110	559.42
0.19	98.9	98.0	0.1401E+06	0.2831E+06	0.9994	1.110	559.37
0.20	98.8	97.8	0.1472E+06	0.2837E+06	0.9994	1.110	559.31
0.21	98.7	97.6	0.1542E+06	0.2842E+06	0.9994	1.110	559.25
0.22	98.5	97.4	0.1612E+06	0.2849E+06	0.9994	1.110	559.19
0.23	98.4	97.1	0.1682E+06	0.2855E+06	0.9994	1.110	559.13
0.24	98.2	96.9	0.1751E+06	0.2862E+06	0.9994	1.110	559.06
0.25	98.1	96.6	0.1820E+06	0.2869E+06	0.9994	1.110	558.99
0.26	97.9	96.3	0.1888E+06	0.2876E+06	0.9994	1.110	558.92
0.27	97.8	96.0	0.1956E+06	0.2884E+06	0.9994	1.110	558.85
0.28	97.6	95.8	0.2023E+06	0.2891E+06	0.9994	1.110	558.77
0.29	97.4	95.5	0.2090E+06	0.2900E+06	0.9994	1.110	558.69
0.30	97.3	95.1	0.2156E+06	0.2908E+06	0.9994	1.110	558.61
0.31	97.1	94.8	0.2222E+06	0.2917E+06	0.9994	1.110	558.52
0.32	96.9	94.5	0.2286E+06	0.2926E+06	0.9994	1.110	558.43
0.33	96.7	94.2	0.2351E+06	0.2936E+06	0.9994	1.110	558.34
0.34	96.5	93.8	0.2414E+06	0.2946E+06	0.9994	1.110	558.25
0.35	96.3	93.5	0.2477E+06	0.2956E+06	0.9994	1.110	558.15
0.36	96.0	93.1	0.2540E+06	0.2966E+06	0.9994	1.110	558.05
0.37	95.8	92.7	0.2601E+06	0.2977E+06	0.9994	1.110	557.95
0.38	95.6	92.3	0.2662E+06	0.2988E+06	0.9994	1.110	557.84
0.39	95.4	91.9	0.2722E+06	0.2999E+06	0.9994	1.110	557.73
0.40	95.1	91.5	0.2782E+06	0.3011E+06	0.9994	1.110	557.62
0.41	94.9	91.1	0.2840E+06	0.3023E+06	0.9994	1.110	557.51
0.42	94.6	90.7	0.2898E+06	0.3036E+06	0.9994	1.110	557.39
0.43	94.4	90.3	0.2956E+06	0.3049E+06	0.9994	1.110	557.27
0.44	94.1	89.9	0.3012E+06	0.3062E+06	0.9994	1.110	557.15
0.45	93.8	89.4	0.3068E+06	0.3075E+06	0.9994	1.110	557.02
0.46	93.6	89.0	0.3123E+06	0.3089E+06	0.9994	1.110	556.90
0.47	93.3	88.5	0.3177E+06	0.3103E+06	0.9994	1.110	556.76
0.48	93.0	88.1	0.3230E+06	0.3118E+06	0.9994	1.111	556.63
0.49	92.7	87.6	0.3282E+06	0.3133E+06	0.9994	1.111	556.50
0.50	92.4	87.1	0.3334E+06	0.3148E+06	0.9994	1.111	556.36
0.51	92.1	86.6	0.3384E+06	0.3164E+06	0.9994	1.111	556.22
0.52	91.8	86.2	0.3434E+06	0.3180E+06	0.9994	1.111	556.07
0.53	91.5	85.7	0.3483E+06	0.3197E+06	0.9994	1.111	555.92
0.54	91.2	85.2	0.3531E+06	0.3214E+06	0.9994	1.111	555.77
0.55	90.8	84.7	0.3579E+06	0.3231E+06	0.9994	1.111	555.62
0.56	90.5	84.1	0.3625E+06	0.3249E+06	0.9994	1.111	555.47
0.57	90.2	83.6	0.3670E+06	0.3267E+06	0.9995	1.111	555.31
0.58	89.8	83.1	0.3715E+06	0.3285E+06	0.9995	1.111	555.15
0.59	89.5	82.6	0.3758E+06	0.3304E+06	0.9995	1.111	554.98
0.60	89.1	82.0	0.3801E+06	0.3324E+06	0.9995	1.111	554.82
0.61	88.8	81.5	0.3843E+06	0.3343E+06	0.9995	1.111	554.65
0.62	88.4	81.0	0.3883E+06	0.3364E+06	0.9995	1.111	554.48
0.63	88.0	80.4	0.3923E+06	0.3384E+06	0.9995	1.111	554.30
0.64	87.6	79.9	0.3962E+06	0.3405E+06	0.9995	1.111	554.13
0.65	87.2	79.3	0.4000E+06	0.3427E+06	0.9995	1.111	553.95
0.66	86.9	78.7	0.4037E+06	0.3449E+06	0.9995	1.111	553.76
0.67	86.5	78.2	0.4073E+06	0.3471E+06	0.9995	1.111	553.58
0.68	86.1	77.6	0.4108E+06	0.3494E+06	0.9995	1.111	553.39
0.69	85.7	77.0	0.4142E+06	0.3518E+06	0.9995	1.112	553.20
0.70	85.2	76.4	0.4176E+06	0.3542E+06	0.9995	1.112	553.01
0.71	84.8	75.9	0.4208E+06	0.3566E+06	0.9995	1.112	552.81
0.72	84.4	75.3	0.4239E+06	0.3591E+06	0.9995	1.112	552.61
0.73	84.0	74.7	0.4269E+06	0.3617E+06	0.9995	1.112	552.41
0.74	83.5	74.1	0.4299E+06	0.3643E+06	0.9995	1.112	552.21
0.75	83.1	73.5	0.4327E+06	0.3669E+06	0.9995	1.112	552.00
0.76	82.7	72.9	0.4355E+06	0.3696E+06	0.9995	1.112	551.79

0.77	82.2	72.3	0.4381E+06	0.3724E+06	0.9995	1.112	551.58
0.78	81.8	71.7	0.4407E+06	0.3752E+06	0.9995	1.112	551.37
0.79	81.3	71.1	0.4431E+06	0.3780E+06	0.9995	1.112	551.15
0.80	80.8	70.5	0.4455E+06	0.3810E+06	0.9995	1.112	550.93
0.81	80.4	69.9	0.4477E+06	0.3839E+06	0.9995	1.112	550.71
0.82	79.9	69.3	0.4499E+06	0.3870E+06	0.9995	1.112	550.48
0.83	79.4	68.7	0.4520E+06	0.3901E+06	0.9995	1.112	550.26
0.84	78.9	68.1	0.4539E+06	0.3932E+06	0.9995	1.112	550.03
0.85	78.4	67.4	0.4558E+06	0.3964E+06	0.9995	1.113	549.79
0.86	77.9	66.8	0.4576E+06	0.3997E+06	0.9995	1.113	549.56
0.87	77.4	66.2	0.4593E+06	0.4031E+06	0.9995	1.113	549.32
0.88	76.9	65.6	0.4609E+06	0.4065E+06	0.9995	1.113	549.08
0.89	76.4	65.0	0.4624E+06	0.4099E+06	0.9995	1.113	548.84
0.90	75.9	64.4	0.4638E+06	0.4135E+06	0.9995	1.113	548.59
0.91	75.3	63.7	0.4652E+06	0.4171E+06	0.9995	1.113	548.34
0.92	74.8	63.1	0.4664E+06	0.4207E+06	0.9996	1.113	548.09
0.93	74.3	62.5	0.4675E+06	0.4245E+06	0.9996	1.113	547.84
0.94	73.7	61.9	0.4686E+06	0.4283E+06	0.9996	1.113	547.58
0.95	73.2	61.3	0.4696E+06	0.4322E+06	0.9996	1.113	547.33
0.96	72.6	60.6	0.4704E+06	0.4361E+06	0.9996	1.113	547.06
0.97	72.1	60.0	0.4712E+06	0.4402E+06	0.9996	1.113	546.80
0.98	71.5	59.4	0.4719E+06	0.4443E+06	0.9996	1.114	546.54
0.99	71.0	58.8	0.4725E+06	0.4485E+06	0.9996	1.114	546.27
1.00	70.4	58.2	0.4731E+06	0.4527E+06	0.9996	1.114	546.00
1.01	69.8	57.6	0.4735E+06	0.4571E+06	0.9996	1.114	545.72
1.02	69.2	57.0	0.4739E+06	0.4615E+06	0.9996	1.114	545.45
1.03	68.7	56.3	0.4742E+06	0.4660E+06	0.9996	1.114	545.17
1.04	68.1	55.7	0.4744E+06	0.4706E+06	0.9996	1.114	544.89
1.05	67.5	55.1	0.4745E+06	0.4753E+06	0.9996	1.114	544.60
1.06	66.9	54.5	0.4745E+06	0.4800E+06	0.9996	1.114	544.32
1.07	66.3	53.9	0.4745E+06	0.4849E+06	0.9996	1.114	544.03
1.08	65.7	53.3	0.4743E+06	0.4898E+06	0.9996	1.114	543.74
1.09	65.1	52.7	0.4741E+06	0.4948E+06	0.9996	1.115	543.44
1.10	64.4	52.1	0.4739E+06	0.5000E+06	0.9996	1.115	543.15
1.11	63.8	51.5	0.4735E+06	0.5052E+06	0.9996	1.115	542.85
1.12	63.2	50.9	0.4731E+06	0.5105E+06	0.9996	1.115	542.55
1.13	62.6	50.3	0.4726E+06	0.5159E+06	0.9996	1.115	542.25
1.14	61.9	49.7	0.4720E+06	0.5214E+06	0.9996	1.115	541.94
1.15	61.3	49.1	0.4714E+06	0.5270E+06	0.9996	1.115	541.63
1.16	60.6	48.5	0.4707E+06	0.5327E+06	0.9996	1.115	541.32
1.17	60.0	48.0	0.4699E+06	0.5386E+06	0.9996	1.115	541.01
1.18	59.3	47.4	0.4690E+06	0.5445E+06	0.9996	1.115	540.70
1.19	58.7	46.8	0.4681E+06	0.5505E+06	0.9996	1.115	540.38
1.20	58.0	46.2	0.4671E+06	0.5567E+06	0.9996	1.116	540.06
1.21	57.3	45.6	0.4661E+06	0.5629E+06	0.9996	1.116	539.74
1.22	56.7	45.1	0.4650E+06	0.5693E+06	0.9996	1.116	539.41
1.23	56.0	44.5	0.4638E+06	0.5758E+06	0.9997	1.116	539.09
1.24	55.3	43.9	0.4625E+06	0.5824E+06	0.9997	1.116	538.76
1.25	54.6	43.4	0.4612E+06	0.5891E+06	0.9997	1.116	538.42
1.26	53.9	42.8	0.4599E+06	0.5960E+06	0.9997	1.116	538.09
1.27	53.2	42.3	0.4585E+06	0.6030E+06	0.9997	1.116	537.75
1.28	52.5	41.7	0.4570E+06	0.6101E+06	0.9997	1.116	537.42
1.29	51.8	41.2	0.4555E+06	0.6173E+06	0.9997	1.117	537.08
1.30	51.1	40.6	0.4539E+06	0.6247E+06	0.9997	1.117	536.73
1.31	50.4	40.1	0.4523E+06	0.6322E+06	0.9997	1.117	536.39
1.32	49.7	39.6	0.4506E+06	0.6399E+06	0.9997	1.117	536.04

I S E N T R O P I C E X P A N S I O N  
(Output file outmix8)

Tt(deg F)	Pt(lb/sq.ft)	Vt(ft^3/lbm-mol)	Zt	Cpt/Cvt	Prt	X134a	Xair
100.0	50.0	0.5563E+06	0.9997	1.109	0.677	0.950	0.050
M	T(deg F)	P(psf)	Re/ft	V(ft^3/lbm-mol)	Z	CP/CV	a(ft/sec)
0.00	100.0	50.0	0.1603E+04	0.5563E+06	0.9997	1.109	560.02
0.01	100.0	50.0	0.3747E+04	0.5563E+06	0.9997	1.109	560.02
0.02	100.0	50.0	0.7495E+04	0.5564E+06	0.9997	1.109	560.02
0.03	100.0	50.0	0.1124E+05	0.5565E+06	0.9997	1.109	560.01
0.04	100.0	50.0	0.1499E+05	0.5567E+06	0.9997	1.109	560.00
0.05	99.9	49.9	0.1872E+05	0.5570E+06	0.9997	1.109	559.99
0.06	99.9	49.9	0.2245E+05	0.5573E+06	0.9997	1.109	559.97
0.07	99.9	49.9	0.2618E+05	0.5577E+06	0.9997	1.109	559.95

0.08	99.8	49.8	0.2990E+05	0.5581E+06	0.9997	1.110	559.93
0.09	99.8	49.8	0.3361E+05	0.5585E+06	0.9997	1.110	559.91
0.10	99.7	49.7	0.3732E+05	0.5591E+06	0.9997	1.110	559.88
0.11	99.6	49.7	0.4100E+05	0.5597E+06	0.9997	1.110	559.85
0.12	99.6	49.6	0.4468E+05	0.5603E+06	0.9997	1.110	559.82
0.13	99.5	49.5	0.4835E+05	0.5610E+06	0.9997	1.110	559.78
0.14	99.4	49.5	0.5200E+05	0.5618E+06	0.9997	1.110	559.74
0.15	99.3	49.4	0.5564E+05	0.5626E+06	0.9997	1.110	559.70
0.16	99.2	49.3	0.5927E+05	0.5634E+06	0.9997	1.110	559.66
0.17	99.1	49.2	0.6287E+05	0.5644E+06	0.9997	1.110	559.61
0.18	99.0	49.1	0.6646E+05	0.5654E+06	0.9997	1.110	559.56
0.19	98.9	49.0	0.7003E+05	0.5664E+06	0.9997	1.110	559.51
0.20	98.8	48.9	0.7358E+05	0.5675E+06	0.9997	1.110	559.46
0.21	98.7	48.8	0.7711E+05	0.5687E+06	0.9997	1.110	559.40
0.22	98.5	48.7	0.8061E+05	0.5699E+06	0.9997	1.110	559.34
0.23	98.4	48.6	0.8410E+05	0.5712E+06	0.9997	1.110	559.27
0.24	98.2	48.4	0.8756E+05	0.5725E+06	0.9997	1.110	559.21
0.25	98.1	48.3	0.9100E+05	0.5739E+06	0.9997	1.110	559.14
0.26	97.9	48.2	0.9441E+05	0.5754E+06	0.9997	1.110	559.06
0.27	97.8	48.0	0.9780E+05	0.5769E+06	0.9997	1.110	558.99
0.28	97.6	47.9	0.1012E+06	0.5785E+06	0.9997	1.110	558.91
0.29	97.4	47.7	0.1045E+06	0.5801E+06	0.9997	1.110	558.83
0.30	97.3	47.6	0.1078E+06	0.5818E+06	0.9997	1.110	558.75
0.31	97.1	47.4	0.1111E+06	0.5836E+06	0.9997	1.110	558.66
0.32	96.9	47.2	0.1143E+06	0.5854E+06	0.9997	1.110	558.57
0.33	96.7	47.1	0.1175E+06	0.5873E+06	0.9997	1.110	558.48
0.34	96.5	46.9	0.1207E+06	0.5893E+06	0.9997	1.110	558.38
0.35	96.3	46.7	0.1239E+06	0.5913E+06	0.9997	1.110	558.29
0.36	96.1	46.5	0.1270E+06	0.5934E+06	0.9997	1.110	558.19
0.37	95.8	46.4	0.1300E+06	0.5956E+06	0.9997	1.110	558.08
0.38	95.6	46.2	0.1331E+06	0.5978E+06	0.9997	1.110	557.98
0.39	95.4	46.0	0.1361E+06	0.6001E+06	0.9997	1.110	557.87
0.40	95.1	45.8	0.1391E+06	0.6024E+06	0.9997	1.110	557.76
0.41	94.9	45.6	0.1420E+06	0.6048E+06	0.9997	1.110	557.64
0.42	94.6	45.4	0.1449E+06	0.6073E+06	0.9997	1.110	557.53
0.43	94.4	45.1	0.1478E+06	0.6099E+06	0.9997	1.110	557.41
0.44	94.1	44.9	0.1506E+06	0.6125E+06	0.9997	1.110	557.28
0.45	93.8	44.7	0.1534E+06	0.6152E+06	0.9997	1.110	557.16
0.46	93.6	44.5	0.1561E+06	0.6180E+06	0.9997	1.110	557.03
0.47	93.3	44.3	0.1588E+06	0.6209E+06	0.9997	1.110	556.90
0.48	93.0	44.0	0.1615E+06	0.6238E+06	0.9997	1.110	556.76
0.49	92.7	43.8	0.1641E+06	0.6268E+06	0.9997	1.110	556.63
0.50	92.4	43.6	0.1667E+06	0.6299E+06	0.9997	1.111	556.49
0.51	92.1	43.3	0.1692E+06	0.6330E+06	0.9997	1.111	556.35
0.52	91.8	43.1	0.1717E+06	0.6362E+06	0.9997	1.111	556.20
0.53	91.5	42.8	0.1741E+06	0.6395E+06	0.9997	1.111	556.05
0.54	91.2	42.6	0.1766E+06	0.6429E+06	0.9997	1.111	555.90
0.55	90.8	42.3	0.1789E+06	0.6464E+06	0.9997	1.111	555.75
0.56	90.5	42.1	0.1812E+06	0.6499E+06	0.9997	1.111	555.59
0.57	90.2	41.8	0.1835E+06	0.6535E+06	0.9997	1.111	555.44
0.58	89.8	41.6	0.1857E+06	0.6572E+06	0.9997	1.111	555.27
0.59	89.5	41.3	0.1879E+06	0.6610E+06	0.9997	1.111	555.11
0.60	89.1	41.0	0.1900E+06	0.6649E+06	0.9997	1.111	554.94
0.61	88.8	40.8	0.1921E+06	0.6689E+06	0.9997	1.111	554.77
0.62	88.4	40.5	0.1942E+06	0.6729E+06	0.9997	1.111	554.60
0.63	88.0	40.2	0.1961E+06	0.6770E+06	0.9997	1.111	554.43
0.64	87.6	39.9	0.1981E+06	0.6813E+06	0.9997	1.111	554.25
0.65	87.3	39.6	0.2000E+06	0.6856E+06	0.9997	1.111	554.07
0.66	86.9	39.4	0.2018E+06	0.6900E+06	0.9997	1.111	553.89
0.67	86.5	39.1	0.2036E+06	0.6945E+06	0.9997	1.111	553.70
0.68	86.1	38.8	0.2054E+06	0.6991E+06	0.9997	1.111	553.51
0.69	85.7	38.5	0.2071E+06	0.7038E+06	0.9997	1.111	553.32
0.70	85.2	38.2	0.2088E+06	0.7086E+06	0.9997	1.112	553.13
0.71	84.8	37.9	0.2104E+06	0.7135E+06	0.9997	1.112	552.93
0.72	84.4	37.6	0.2119E+06	0.7184E+06	0.9997	1.112	552.73
0.73	84.0	37.3	0.2135E+06	0.7235E+06	0.9997	1.112	552.53
0.74	83.5	37.0	0.2149E+06	0.7287E+06	0.9997	1.112	552.33
0.75	83.1	36.8	0.2163E+06	0.7340E+06	0.9997	1.112	552.12
0.76	82.7	36.5	0.2177E+06	0.7394E+06	0.9998	1.112	551.91
0.77	82.2	36.2	0.2190E+06	0.7449E+06	0.9998	1.112	551.70
0.78	81.8	35.9	0.2203E+06	0.7506E+06	0.9998	1.112	551.48
0.79	81.3	35.6	0.2215E+06	0.7563E+06	0.9998	1.112	551.26

0.80	80.8	35.2	0.2227E+06	0.7621E+06	0.9998	1.112	551.04
0.81	80.4	34.9	0.2238E+06	0.7681E+06	0.9998	1.112	550.82
0.82	79.9	34.6	0.2249E+06	0.7742E+06	0.9998	1.112	550.60
0.83	79.4	34.3	0.2260E+06	0.7804E+06	0.9998	1.112	550.37
0.84	78.9	34.0	0.2269E+06	0.7867E+06	0.9998	1.112	550.14
0.85	78.4	33.7	0.2279E+06	0.7931E+06	0.9998	1.112	549.90
0.86	77.9	33.4	0.2288E+06	0.7997E+06	0.9998	1.113	549.67
0.87	77.4	33.1	0.2296E+06	0.8064E+06	0.9998	1.113	549.43
0.88	76.9	32.8	0.2304E+06	0.8132E+06	0.9998	1.113	549.19
0.89	76.4	32.5	0.2312E+06	0.8201E+06	0.9998	1.113	548.94
0.90	75.9	32.2	0.2319E+06	0.8272E+06	0.9998	1.113	548.70
0.91	75.4	31.9	0.2326E+06	0.8344E+06	0.9998	1.113	548.45
0.92	74.8	31.6	0.2332E+06	0.8417E+06	0.9998	1.113	548.20
0.93	74.3	31.3	0.2337E+06	0.8492E+06	0.9998	1.113	547.94
0.94	73.7	30.9	0.2343E+06	0.8568E+06	0.9998	1.113	547.69
0.95	73.2	30.6	0.2348E+06	0.8646E+06	0.9998	1.113	547.43
0.96	72.7	30.3	0.2352E+06	0.8725E+06	0.9998	1.113	547.17
0.97	72.1	30.0	0.2356E+06	0.8806E+06	0.9998	1.113	546.90
0.98	71.5	29.7	0.2359E+06	0.8888E+06	0.9998	1.113	546.64
0.99	71.0	29.4	0.2362E+06	0.8972E+06	0.9998	1.114	546.37
1.00	70.4	29.1	0.2365E+06	0.9057E+06	0.9998	1.114	546.09
1.01	69.8	28.8	0.2367E+06	0.9144E+06	0.9998	1.114	545.82
1.02	69.3	28.5	0.2369E+06	0.9232E+06	0.9998	1.114	545.54
1.03	68.7	28.2	0.2371E+06	0.9322E+06	0.9998	1.114	545.26
1.04	68.1	27.9	0.2372E+06	0.9414E+06	0.9998	1.114	544.98
1.05	67.5	27.6	0.2372E+06	0.9508E+06	0.9998	1.114	544.70
1.06	66.9	27.3	0.2372E+06	0.9603E+06	0.9998	1.114	544.41
1.07	66.3	27.0	0.2372E+06	0.9700E+06	0.9998	1.114	544.12
1.08	65.7	26.6	0.2371E+06	0.9799E+06	0.9998	1.114	543.83
1.09	65.1	26.3	0.2370E+06	0.9899E+06	0.9998	1.114	543.54
1.10	64.4	26.0	0.2369E+06	0.1000E+07	0.9998	1.115	543.24
1.11	63.8	25.7	0.2367E+06	0.1011E+07	0.9998	1.115	542.94
1.12	63.2	25.4	0.2365E+06	0.1021E+07	0.9998	1.115	542.64
1.13	62.6	25.2	0.2363E+06	0.1032E+07	0.9998	1.115	542.34
1.14	61.9	24.9	0.2360E+06	0.1043E+07	0.9998	1.115	542.03
1.15	61.3	24.6	0.2357E+06	0.1054E+07	0.9998	1.115	541.72
1.16	60.6	24.3	0.2353E+06	0.1066E+07	0.9998	1.115	541.41
1.17	60.0	24.0	0.2349E+06	0.1077E+07	0.9998	1.115	541.10
1.18	59.3	23.7	0.2345E+06	0.1089E+07	0.9998	1.115	540.78
1.19	58.7	23.4	0.2340E+06	0.1101E+07	0.9998	1.115	540.46
1.20	58.0	23.1	0.2335E+06	0.1114E+07	0.9998	1.116	540.14
1.21	57.3	22.8	0.2330E+06	0.1126E+07	0.9998	1.116	539.82
1.22	56.7	22.5	0.2325E+06	0.1139E+07	0.9998	1.116	539.50
1.23	56.0	22.3	0.2319E+06	0.1152E+07	0.9998	1.116	539.17
1.24	55.3	22.0	0.2312E+06	0.1165E+07	0.9998	1.116	538.84
1.25	54.6	21.7	0.2306E+06	0.1179E+07	0.9998	1.116	538.51
1.26	53.9	21.4	0.2299E+06	0.1192E+07	0.9998	1.116	538.17
1.27	53.2	21.1	0.2292E+06	0.1206E+07	0.9998	1.116	537.84
1.28	52.5	20.9	0.2285E+06	0.1220E+07	0.9998	1.116	537.50
1.29	51.8	20.6	0.2277E+06	0.1235E+07	0.9998	1.116	537.15
1.30	51.1	20.3	0.2269E+06	0.1250E+07	0.9998	1.117	536.81
1.31	50.4	20.0	0.2261E+06	0.1265E+07	0.9998	1.117	536.47
1.32	49.7	19.8	0.2253E+06	0.1280E+07	0.9998	1.117	536.12

\*\*\* ALL DATA CASES HAVE BEEN READ AND PROCESSED - JOB IS COMPLETED \*\*\*

## Appendix H

### Sample Output from Program MACHPG

=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2200.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0000	0.00	0.00	0.7779E-02	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.17	0.2641E-06	1.109	0.0000E+00	0.677
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2198.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0405	2.00	22.68	0.7772E-02	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.14	0.2641E-06	1.109	0.6674E+06	0.677
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2196.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0573	4.00	32.08	0.7766E-02	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.12	0.2641E-06	1.109	0.9434E+06	0.677
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2194.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0702	5.99	39.30	0.7760E-02	99.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.10	0.2641E-06	1.109	0.1155E+07	0.677
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2192.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0810	7.99	45.39	0.7753E-02	99.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.07	0.2640E-06	1.109	0.1333E+07	0.677
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2190.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0906	9.98	50.76	0.7747E-02	99.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.05	0.2640E-06	1.109	0.1489E+07	0.677
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2220.0	2180.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1811	39.67	101.37	0.7722E-02	99.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.70	0.2637E-06	1.109	0.2968E+07	0.677
=====				

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2220.0	2160.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2224	59.26	124.41	0.7658E-02	98.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.46	0.2634E-06	1.110	0.3616E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2220.0	2140.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2574	78.68	143.96	0.7594E-02	98.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.22	0.2632E-06	1.110	0.4153E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2220.0	2120.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2885	97.94	161.29	0.7530E-02	97.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.98	0.2630E-06	1.110	0.4618E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2100.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2899	97.92	162.04	0.7459E-02	97.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.97	0.2630E-06	1.110	0.4596E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2080.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3184	116.99	177.88	0.7395E-02	96.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.72	0.2627E-06	1.110	0.5006E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2060.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3448	135.89	192.55	0.7331E-02	96.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.47	0.2625E-06	1.110	0.5377E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2040.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3696	154.61	206.29	0.7267E-02	95.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.22	0.2622E-06	1.110	0.5716E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2020.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3930	173.16	219.28	0.7203E-02	95.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.96	0.2620E-06	1.110	0.6028E+07	0.678



Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	2000.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4154	191.52	231.66	0.7139E-02	94.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.71	0.2618E-06	1.110	0.6317E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1980.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4368	209.71	243.50	0.7074E-02	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.45	0.2615E-06	1.110	0.6587E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1960.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4575	227.71	254.90	0.7010E-02	93.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.18	0.2612E-06	1.110	0.6839E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1940.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4775	245.52	265.91	0.6946E-02	93.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.92	0.2610E-06	1.110	0.7076E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1920.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4969	263.15	276.57	0.6881E-02	92.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.65	0.2607E-06	1.110	0.7298E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1900.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5157	280.59	286.94	0.6817E-02	91.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.38	0.2605E-06	1.110	0.7508E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1800.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6041	364.85	335.25	0.6493E-02	88.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
554.97	0.2591E-06	1.111	0.8400E+07	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1700.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6856	444.02	379.46	0.6168E-02	85.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.47	0.2577E-06	1.111	0.9082E+07	0.682

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1600.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7630	517.77	421.07	0.5841E-02	82.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
551.88	0.2562E-06	1.112	0.9601E+07	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1500.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8379	585.74	461.01	0.5513E-02	78.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.17	0.2545E-06	1.112	0.9983E+07	0.685
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1400.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9117	647.51	499.92	0.5182E-02	74.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
548.34	0.2528E-06	1.113	0.1025E+08	0.687
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1300.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9853	702.59	538.31	0.4850E-02	70.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
546.37	0.2509E-06	1.114	0.1040E+08	0.688
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1200.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0595	750.43	576.60	0.4515E-02	66.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
544.22	0.2489E-06	1.114	0.1046E+08	0.691
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1150.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0971	771.43	595.83	0.4347E-02	63.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
543.07	0.2478E-06	1.115	0.1045E+08	0.692
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1100.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1353	790.36	615.18	0.4177E-02	61.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
541.86	0.2467E-06	1.115	0.1042E+08	0.693
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1050.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1741	807.12	634.69	0.4008E-02	58.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
540.60	0.2455E-06	1.115	0.1036E+08	0.695

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	1000.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2136	821.60	654.43	0.3837E-02	56.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
539.27	0.2443E-06	1.116	0.1028E+08	0.696
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	950.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2539	833.68	674.45	0.3666E-02	53.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
537.86	0.2430E-06	1.116	0.1018E+08	0.698
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	900.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2954	843.20	694.80	0.3494E-02	50.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
536.37	0.2416E-06	1.117	0.1005E+08	0.700
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	850.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3380	850.03	715.55	0.3321E-02	46.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
534.79	0.2401E-06	1.117	0.9895E+07	0.702
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
2200.0	800.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3820	853.99	736.77	0.3147E-02	43.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
533.11	0.2386E-06	1.118	0.9718E+07	0.704
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	1000.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0000	0.00	0.00	0.3536E-02	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.17	0.2641E-06	1.109	0.0000E+00	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	999.5	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0300	0.50	16.82	0.3534E-02	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.15	0.2641E-06	1.109	0.2250E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	999.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0425	1.00	23.79	0.3533E-02	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.14	0.2641E-06	1.109	0.3182E+06	0.677

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	998.5	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0520	1.50	29.14	0.3531E-02	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.13	0.2641E-06	1.109	0.3896E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	998.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0601	2.00	33.65	0.3529E-02	99.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.12	0.2641E-06	1.109	0.4497E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	996.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0850	3.99	47.61	0.3523E-02	99.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.06	0.2640E-06	1.109	0.6352E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	994.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1042	5.98	58.34	0.3517E-02	99.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.01	0.2640E-06	1.109	0.7771E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	992.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1204	7.97	67.40	0.3510E-02	99.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.96	0.2639E-06	1.109	0.8962E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	990.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1346	9.95	75.38	0.3504E-02	99.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.91	0.2639E-06	1.109	0.1001E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	988.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1476	11.93	82.62	0.3498E-02	99.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.86	0.2638E-06	1.109	0.1095E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	986.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1595	13.91	89.28	0.3491E-02	99.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.80	0.2638E-06	1.109	0.1181E+07	0.677

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	984.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1706	15.88	95.48	0.3485E-02	99.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.75	0.2637E-06	1.109	0.1262E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	982.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1810	17.85	101.32	0.3478E-02	99.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.70	0.2637E-06	1.109	0.1336E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	980.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1909	19.82	106.85	0.3472E-02	98.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.65	0.2636E-06	1.110	0.1407E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	960.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2715	39.27	151.81	0.3408E-02	97.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.12	0.2631E-06	1.110	0.1966E+07	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	940.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3344	58.34	186.81	0.3344E-02	96.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.57	0.2626E-06	1.110	0.2379E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	920.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3884	77.03	216.74	0.3280E-02	95.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.02	0.2621E-06	1.110	0.2712E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	900.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4368	95.32	243.50	0.3216E-02	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.45	0.2615E-06	1.110	0.2994E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	880.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4814	113.21	268.07	0.3151E-02	92.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.86	0.2609E-06	1.110	0.3237E+07	0.679

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	860.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5231	130.69	291.01	0.3087E-02	91.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.27	0.2604E-06	1.111	0.3450E+07	0.680
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	840.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5628	147.74	312.70	0.3022E-02	90.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.65	0.2598E-06	1.111	0.3637E+07	0.680
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	820.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6007	164.35	333.41	0.2957E-02	89.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.03	0.2592E-06	1.111	0.3804E+07	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	800.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6373	180.52	353.32	0.2892E-02	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
554.38	0.2586E-06	1.111	0.3952E+07	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	780.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6729	196.23	372.59	0.2827E-02	86.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.72	0.2579E-06	1.111	0.4084E+07	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	760.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7076	211.47	391.32	0.2762E-02	84.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.04	0.2573E-06	1.111	0.4201E+07	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	740.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7416	226.22	409.62	0.2697E-02	83.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
552.34	0.2566E-06	1.112	0.4305E+07	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	720.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7751	240.48	427.55	0.2631E-02	81.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
551.61	0.2559E-06	1.112	0.4396E+07	0.683

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	700.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8081	254.22	445.19	0.2566E-02	80.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.87	0.2552E-06	1.112	0.4475E+07	0.684
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	680.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8409	267.42	462.58	0.2500E-02	78.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.10	0.2545E-06	1.112	0.4544E+07	0.685
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	660.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8734	280.09	479.78	0.2434E-02	77.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
549.31	0.2537E-06	1.113	0.4602E+07	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	640.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9058	292.18	496.83	0.2368E-02	75.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
548.50	0.2529E-06	1.113	0.4650E+07	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	620.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9381	303.70	513.78	0.2301E-02	73.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
547.65	0.2521E-06	1.113	0.4689E+07	0.687
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	600.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9705	314.61	530.65	0.2235E-02	71.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
546.77	0.2513E-06	1.113	0.4718E+07	0.688
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	580.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0030	324.89	547.49	0.2168E-02	69.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
545.87	0.2505E-06	1.114	0.4739E+07	0.689
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	560.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0356	334.52	564.33	0.2101E-02	67.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
544.92	0.2496E-06	1.114	0.4750E+07	0.690

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	540.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0685	343.48	581.20	0.2034E-02	65.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
543.95	0.2486E-06	1.114	0.4754E+07	0.691
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	520.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1017	351.73	598.14	0.1966E-02	63.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
542.93	0.2477E-06	1.115	0.4748E+07	0.692
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	500.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1353	359.25	615.18	0.1899E-02	61.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
541.86	0.2467E-06	1.115	0.4735E+07	0.693
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	450.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2216	374.64	658.41	0.1729E-02	55.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
538.99	0.2440E-06	1.116	0.4664E+07	0.697
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	400.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3123	384.67	703.05	0.1557E-02	48.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
535.75	0.2410E-06	1.117	0.4541E+07	0.701
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	350.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.4092	388.59	749.76	0.1383E-02	41.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
532.04	0.2376E-06	1.118	0.4363E+07	0.706
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
1000.0	300.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.5150	385.45	799.45	0.1206E-02	32.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
527.70	0.2336E-06	1.120	0.4128E+07	0.712
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	500.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0000	0.00	0.00	0.1768E-02	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.17	0.2641E-06	1.109	0.0000E+00	0.677



Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	490.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1909	9.91	106.85	0.1736E-02	98.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.65	0.2636E-06	1.110	0.7035E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	480.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2715	19.63	151.81	0.1704E-02	97.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.12	0.2631E-06	1.110	0.9831E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	470.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3344	29.17	186.81	0.1672E-02	96.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.57	0.2626E-06	1.110	0.1189E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	460.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3884	38.51	216.74	0.1640E-02	95.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.02	0.2621E-06	1.110	0.1356E+07	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	450.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4368	47.66	243.50	0.1608E-02	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.45	0.2615E-06	1.110	0.1497E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	440.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4814	56.61	268.07	0.1576E-02	92.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.86	0.2609E-06	1.110	0.1618E+07	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	430.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5231	65.34	291.01	0.1543E-02	91.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.27	0.2604E-06	1.111	0.1725E+07	0.680
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	420.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5628	73.87	312.70	0.1511E-02	90.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.65	0.2598E-06	1.111	0.1819E+07	0.680

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	410.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6007	82.18	333.41	0.1479E-02	89.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.03	0.2592E-06	1.111	0.1902E+07	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	400.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6373	90.26	353.32	0.1446E-02	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
554.38	0.2586E-06	1.111	0.1976E+07	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	390.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6729	98.12	372.59	0.1414E-02	86.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.72	0.2579E-06	1.111	0.2042E+07	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	380.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7076	105.73	391.32	0.1381E-02	84.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.04	0.2573E-06	1.111	0.2100E+07	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	370.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7416	113.11	409.62	0.1348E-02	83.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
552.34	0.2566E-06	1.112	0.2152E+07	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	360.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7751	120.24	427.55	0.1316E-02	81.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
551.61	0.2559E-06	1.112	0.2198E+07	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	350.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8081	127.11	445.19	0.1283E-02	80.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.87	0.2552E-06	1.112	0.2238E+07	0.684
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	340.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8409	133.71	462.58	0.1250E-02	78.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.10	0.2545E-06	1.112	0.2272E+07	0.685

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	330.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8734	140.04	479.78	0.1217E-02	77.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
549.31	0.2537E-06	1.113	0.2301E+07	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	320.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9058	146.09	496.83	0.1184E-02	75.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
548.50	0.2529E-06	1.113	0.2325E+07	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	310.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9381	151.85	513.78	0.1151E-02	73.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
547.65	0.2521E-06	1.113	0.2344E+07	0.687
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	300.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9705	157.30	530.65	0.1117E-02	71.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
546.77	0.2513E-06	1.113	0.2359E+07	0.688
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	280.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0356	167.26	564.33	0.1051E-02	67.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
544.92	0.2496E-06	1.114	0.2375E+07	0.690
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	270.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0685	171.74	581.20	0.1017E-02	65.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
543.95	0.2486E-06	1.114	0.2377E+07	0.691
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	260.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1017	175.87	598.14	0.9832E-03	63.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
542.93	0.2477E-06	1.115	0.2374E+07	0.692
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	240.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1694	183.01	632.34	0.9155E-03	59.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
540.75	0.2457E-06	1.115	0.2356E+07	0.694

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	220.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2393	188.55	667.21	0.8472E-03	54.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
538.38	0.2434E-06	1.116	0.2322E+07	0.697
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	200.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3123	192.33	703.05	0.7783E-03	48.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
535.75	0.2410E-06	1.117	0.2270E+07	0.701
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	180.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3892	194.17	740.21	0.7088E-03	42.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
532.83	0.2383E-06	1.118	0.2202E+07	0.704
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	160.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.4714	193.81	779.15	0.6386E-03	36.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
529.52	0.2353E-06	1.119	0.2115E+07	0.709
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	140.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.5605	190.97	820.41	0.5675E-03	28.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
525.74	0.2318E-06	1.120	0.2008E+07	0.715
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	120.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.6589	185.24	864.79	0.4954E-03	19.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
521.30	0.2278E-06	1.122	0.1881E+07	0.723
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
500.0	100.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.7703	176.09	913.42	0.4222E-03	9.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
515.97	0.2230E-06	1.124	0.1729E+07	0.733
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	200.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0000	0.00	0.00	0.7072E-03	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.17	0.2641E-06	1.109	0.0000E+00	0.677

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	190.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3044	9.77	170.13	0.6752E-03	97.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.85	0.2629E-06	1.110	0.4370E+06	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	180.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4368	19.06	243.50	0.6431E-03	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.45	0.2615E-06	1.110	0.5988E+06	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	170.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5432	27.85	301.99	0.6109E-03	91.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.96	0.2601E-06	1.111	0.7093E+06	0.680
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	160.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6373	36.10	353.32	0.5785E-03	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
554.38	0.2586E-06	1.111	0.7904E+06	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	150.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7247	43.78	400.52	0.5459E-03	84.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
552.69	0.2569E-06	1.112	0.8509E+06	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	140.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8081	50.84	445.19	0.5131E-03	80.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.87	0.2552E-06	1.112	0.8950E+06	0.684
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	130.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8896	57.24	488.32	0.4802E-03	76.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
548.91	0.2533E-06	1.113	0.9254E+06	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	120.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9705	62.92	530.65	0.4470E-03	71.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
546.77	0.2513E-06	1.113	0.9436E+06	0.688

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	110.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0520	67.82	572.76	0.4135E-03	66.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
544.44	0.2491E-06	1.114	0.9506E+06	0.690
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	100.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1353	71.85	615.18	0.3798E-03	61.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
541.86	0.2467E-06	1.115	0.9469E+06	0.693
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	90.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2216	74.93	658.41	0.3457E-03	55.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
538.99	0.2440E-06	1.116	0.9328E+06	0.697
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	80.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3123	76.93	703.05	0.3113E-03	48.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
535.75	0.2410E-06	1.117	0.9081E+06	0.701
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	70.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.4092	77.72	749.76	0.2765E-03	41.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
532.04	0.2376E-06	1.118	0.8726E+06	0.706
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	60.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.5150	77.09	799.45	0.2413E-03	32.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
527.70	0.2336E-06	1.120	0.8256E+06	0.712
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	50.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.6333	74.79	853.35	0.2054E-03	22.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
522.48	0.2289E-06	1.121	0.7659E+06	0.720
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	40.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.7703	70.44	913.42	0.1689E-03	9.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
515.97	0.2230E-06	1.124	0.6915E+06	0.733

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	30.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.9374	63.45	982.97	0.1314E-03	-7.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
507.37	0.2154E-06	1.127	0.5993E+06	0.752
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	20.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
2.1602	52.82	1068.78	0.9250E-04	-31.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
494.77	0.2045E-06	1.132	0.4833E+06	0.788
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	10.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
2.5208	36.29	1189.24	0.5132E-04	-74.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
471.77	0.1854E-06	1.142	0.3292E+06	0.893
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
200.0	5.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
2.8724	23.82	1282.48	0.2897E-04	*****
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
446.49	0.1654E-06	1.155	0.2245E+06	1.133
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	100.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.0000	0.00	0.00	0.3536E-03	100.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
560.17	0.2641E-06	1.109	0.0000E+00	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	98.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.1909	1.98	106.85	0.3472E-03	98.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.65	0.2636E-06	1.110	0.1407E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	96.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.2715	3.93	151.81	0.3408E-03	97.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
559.12	0.2631E-06	1.110	0.1966E+06	0.677
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	94.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3344	5.83	186.81	0.3344E-03	96.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.57	0.2626E-06	1.110	0.2379E+06	0.678

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	92.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.3884	7.70	216.74	0.3280E-03	95.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
558.02	0.2621E-06	1.110	0.2712E+06	0.678
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	90.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4368	9.53	243.50	0.3216E-03	94.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
557.45	0.2615E-06	1.110	0.2994E+06	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	88.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.4814	11.32	268.07	0.3151E-03	92.9
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.86	0.2609E-06	1.110	0.3237E+06	0.679
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	86.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5231	13.07	291.01	0.3087E-03	91.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
556.27	0.2604E-06	1.111	0.3450E+06	0.680
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	84.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.5628	14.77	312.70	0.3022E-03	90.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.65	0.2598E-06	1.111	0.3637E+06	0.680
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	82.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6007	16.44	333.41	0.2957E-03	89.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
555.03	0.2592E-06	1.111	0.3804E+06	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	80.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6373	18.05	353.32	0.2892E-03	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
554.38	0.2586E-06	1.111	0.3952E+06	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	78.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6729	19.62	372.59	0.2827E-03	86.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.72	0.2579E-06	1.111	0.4084E+06	0.682



Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	76.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7076	21.15	391.32	0.2762E-03	84.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.04	0.2573E-06	1.111	0.4201E+06	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	74.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7416	22.62	409.62	0.2697E-03	83.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
552.34	0.2566E-06	1.112	0.4305E+06	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	72.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7751	24.05	427.55	0.2631E-03	81.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
551.61	0.2559E-06	1.112	0.4396E+06	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	70.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8081	25.42	445.19	0.2566E-03	80.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.87	0.2552E-06	1.112	0.4475E+06	0.684
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	65.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8896	28.62	488.32	0.2401E-03	76.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
548.91	0.2533E-06	1.113	0.4627E+06	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	60.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9705	31.46	530.65	0.2235E-03	71.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
546.77	0.2513E-06	1.113	0.4718E+06	0.688
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	55.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0520	33.91	572.76	0.2067E-03	66.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
544.44	0.2491E-06	1.114	0.4753E+06	0.690
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	50.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1353	35.93	615.18	0.1899E-03	61.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
541.86	0.2467E-06	1.115	0.4735E+06	0.693

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	45.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2216	37.46	658.41	0.1729E-03	55.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
538.99	0.2440E-06	1.116	0.4664E+06	0.697
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	40.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3123	38.47	703.05	0.1557E-03	48.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
535.75	0.2410E-06	1.117	0.4541E+06	0.701
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	35.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.4092	38.86	749.76	0.1383E-03	41.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
532.04	0.2376E-06	1.118	0.4363E+06	0.706
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
100.0	30.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.5150	38.55	799.45	0.1206E-03	32.4
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
527.70	0.2336E-06	1.120	0.4128E+06	0.712
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	40.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6373	9.03	353.32	0.1446E-03	87.7
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
554.38	0.2586E-06	1.111	0.1976E+06	0.681
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	39.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.6729	9.81	372.59	0.1414E-03	86.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.72	0.2579E-06	1.111	0.2042E+06	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	38.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7076	10.57	391.32	0.1381E-03	84.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
553.04	0.2573E-06	1.111	0.2100E+06	0.682
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	37.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7416	11.31	409.62	0.1348E-03	83.3
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
552.34	0.2566E-06	1.112	0.2152E+06	0.683

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	36.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.7751	12.02	427.55	0.1316E-03	81.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
551.61	0.2559E-06	1.112	0.2198E+06	0.683
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	35.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8081	12.71	445.19	0.1283E-03	80.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.87	0.2552E-06	1.112	0.2238E+06	0.684
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	34.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8409	13.37	462.58	0.1250E-03	78.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
550.10	0.2545E-06	1.112	0.2272E+06	0.685
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	33.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.8734	14.00	479.78	0.1217E-03	77.0
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
549.31	0.2537E-06	1.113	0.2301E+06	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	32.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9058	14.61	496.83	0.1184E-03	75.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
548.50	0.2529E-06	1.113	0.2325E+06	0.686
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	31.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9381	15.18	513.78	0.1151E-03	73.5
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
547.65	0.2521E-06	1.113	0.2344E+06	0.687
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	30.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
0.9705	15.73	530.65	0.1117E-03	71.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
546.77	0.2513E-06	1.113	0.2359E+06	0.688
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	28.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.0356	16.73	564.33	0.1051E-03	67.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
544.92	0.2496E-06	1.114	0.2375E+06	0.690

Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	26.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1017	17.59	598.14	0.9832E-04	63.6
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
542.93	0.2477E-06	1.115	0.2374E+06	0.692
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	24.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.1694	18.30	632.34	0.9155E-04	59.1
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
540.75	0.2457E-06	1.115	0.2356E+06	0.694
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	22.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.2393	18.85	667.21	0.8472E-04	54.2
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
538.38	0.2434E-06	1.116	0.2322E+06	0.697
=====				
Pt (lb/sq. ft)	Ps (lb/sq. ft)	Tt (deg F)	X134a	Xair
50.0	20.0	100.0	0.950	0.050
M	q (lb/sq. ft)	u (ft/sec)	RHO (slugs/cu. ft)	Ts (deg F)
1.3123	19.23	703.05	0.7783E-04	48.8
a (ft/sec)	Mu (lb-sec/sq. ft)	Gamma	Re/ft	Pr
535.75	0.2410E-06	1.117	0.2270E+06	0.701
=====				
*** ALL DATA CASES HAVE BEEN READ AND PROCESSED - JOB IS COMPLETED ***				

## References

1. Notes on the Proceedings of the 1939 Meeting of the Aircraft Industry with the National Advisory Committee for Aeronautics. *Journal of the Aeronautical Sciences*, Vol. 6, Number 7, May 1939, pp. 299-301.
2. Moxey, R. L.: Transonic Dynamics Wind Tunnel. *Compressed Air Magazine*, Vol. 68, Number 10, October 1963, pp. 8-13.
3. Reed, W. H., III.: *Aeroelasticity Matters: Some Reflections on Two Decades of Testing in the NASA Langley Transonic Dynamics Tunnel*. NASA TM-83210, 1981.
4. Ricketts, R. H.: *Experimental Aeroelasticity History, Status and Future in Brief*. NASA TM 102651, April 1990.
5. Cole, S. R.; and Rivera, J. A., Jr.: The New Heavy Gas Testing Capability in the NASA Langley Transonic Dynamics Tunnel. Presented at the Royal Aeronautical Society Wind Tunnels and Wind Tunnel Test Techniques Forum, Churchill College, Cambridge, UK, April 14-16, 1997.
6. Corliss, J. M.; and Cole, S. R.: Heavy Gas Conversion of the NASA Langley Transonic Dynamics Tunnel. 20th AIAA Advanced Measurement and Ground Testing Technology Conference, June 15-18, 1998, Albuquerque, NM (AIAA Paper 98-2710).
7. *Thermodynamics and Physics of Matter. Vol. 1, High Speed Aerodynamics and Jet Propulsion*, Princeton University Press, 1955.
8. Anders, J. B.: Heavy Gas Wind-Tunnel Research at Langley Research Center. 93-FE-5, ASME, June 1993.
9. Anders, J. B.; Anderson, W. K.; and Murthy, A. V.: The Use of Heavy Gas for Increased Reynolds Numbers in Transonic Wind Tunnels. 20th AIAA Advanced Measurement and Ground Testing Technology Conference, June 15-18, 1998, Albuquerque, NM (AIAA Paper 98-2882).
10. Jenkins, R. V.: *Program to Calculate Isentropic Flow Properties of Sulfur Hexafluoride*. NASA TM-4358, 1992.
11. Jenkins, R. V.: *Program to Calculate Mach Number Given Total Temperature, Total Pressure, and Static Pressure in Sulfur Hexafluoride*. NASA TM-4609, 1994.
12. Jenkins, R. V.: *Programs to Calculate Properties of Air and Sulfur Hexafluoride Mixtures*. NASA TM-4725, 1996.

13. Modell, M; and Reid, R. C.: *Thermodynamics and Its Applications*, Second edition. Prentice-Hall, 1974.
14. Wark, K., Jr.: *Thermodynamics*, Fifth edition. McGraw-Hill, 1988.
15. Huang, F. F.: *Engineering Thermodynamics – Fundamentals and Applications*, Second edition, Macmillan Publishing Co., 1988.
16. Shavit, A.; and Gutfinger, C.: *Thermodynamics: From Concepts to Applications*. Prentice Hall, 1995.
17. Pai, S.: *Introduction to the Theory of Compressible Flow*. D. Van Nostrand Co., 1959.
18. Owczarek, J. A.: *Fundamentals of Gas Dynamics*. International Textbook Co., 1964.
19. Ames Research Staff: *Equations, Tables, and Charts for Compressible Flow*. NACA Report 1135, 1953.
20. Reid, R. C.; Prausnitz, J. M.; and Poling, B. E.: *The Properties of Gases and Liquids*. McGraw-Hill, 1987.
21. Thermodynamic Properties of HFC-134a. T-134a-ENG, DuPont Fluoroproducts, 1993.
22. Bird, R. B.; Stewart, W. E.; and Lightfoot, E. N.: *Transport Phenomena*. John Wiley & Sons, Inc., 1960.
23. White, F. M.: *Viscous Fluid Flow*. McGraw-Hill Book Co., 1974.
24. Wilke, C. R.: A Viscosity Equation for Gas Mixtures. *Journal of Chemical Physics*, Vol. 18, No. 4, April 1950, pp. 517-519.
25. *Tables of Thermodynamic and Transport Properties of Air, Argon, Carbon Dioxide, Carbon Monoxide, Hydrogen, Nitrogen, Oxygen, and Steam*. Pergamon Press, 1960.
26. Transport Properties of SUVA Refrigerants. ART-1, DuPont Fluoroproducts, 1992.
27. Downing, R. C. (Editor): *Fluorocarbon Refrigerants Handbook*. Prentice-Hall, 1988.
28. Masi, J. F.: Thermodynamic Properties of Gaseous Difluorodichloromethane (Freon-12). *J. Amer. Chem. Soc.*, Vol. 74, No. 19, October 5, 1952, pp. 4738-4741.
29. McHarness, R. C.; Eiseman, B. J., Jr.; and Martin, J. J.: Thermodynamic Properties of the Freon Refrigerants: I. Freon 12. *Refrig. Eng.*, 63 (Sept., 1955), pp. 31-44.

30. Brokaw, R. S.: *Alignment Charts for Transport Properties, Viscosity, Thermal Conductivity, and Diffusion Coefficients for Nonpolar Gases and Gas Mixtures at Low Density*. NASA TR R-81, 1961.
31. Tillner-Roth, R.; and Baehr, H. D.: An International Standard Formulation for the Thermodynamic Properties of 1,1,1,2-Tetrafluoroethane (HFC-134a) for Temperatures from 170 K to 455 K and Pressures up to 70 MPa. *J. Phys. Chem. Ref. Data*, Vol. 23, No. 5, 1994, pp. 657-729.
32. Witte, D. W.; and Tatum, K. E.: *Computer Code for Determination of Thermally Perfect Gas Properties*. NASA TP 3447, September 1994.

Table 1. Critical Conditions and Redlich-Kwong Coefficients for Relevant Gases

Species	Critical temperature, K	Critical pressure, Pa	$a_i$ , N-m <sup>4</sup> -K <sup>0.5</sup> /kmol <sup>2</sup>	$b_i$ , m <sup>3</sup> /kmol
H <sub>2</sub> O	647.3	$2.212 \times 10^7$	$1.424132814 \times 10^7$	0.021079896
N <sub>2</sub>	126.2	$3.39 \times 10^6$	$1.559625357 \times 10^6$	0.026816842
O <sub>2</sub>	154.6	$5.04 \times 10^6$	$1.742467899 \times 10^6$	0.022096675
R134a	374.23	$4.0603 \times 10^6$	$1.971785813 \times 10^7$	0.066393673
SF <sub>6</sub>	318.7	$3.76 \times 10^6$	$1.425078907 \times 10^7$	0.061057947
R12	385.0	$4.14 \times 10^6$	$2.075978467 \times 10^7$	0.06698948





Figure 1. Langley Transonic Dynamics Tunnel.




Figure 2. Principal computational steps in program MACHRK




Figure 3. Principal computational steps in program MIXRK.




Figure 3. Principal computational steps in program MIXRK (Concluded).




Figure 4. Mach-q curves for air ( $T_t = 100^\circ\text{F}$ ).




Figure 5. Mach- $q$  curves for 95-percent R-134a/air mixture ( $T_t = 100^\circ\text{F}$ ).




Figure 6. Mass density of 95-percent R-134a/air mixture.




Figure 7. Speed of sound for 95-percent R-134a/air mixture.






Figure 8. Absolute viscosity of 95-percent R-134a/air mixture.




Figure 9. Thermal conductivity of 95-percent R-134a/air mixture.




Figure 10. Variation of Reynolds number with Mach number for 95-percent R-134a/air mixture.




Figure 11. Variation of static temperature with Mach number for 95-percent R-134a/air mixture.




Figure 12. Variation of ratio of specific heats with speed of sound.




Figure 13. Compressible flow relations for 95-percent R-134a/air mixture ( $T_t = 100^\circ\text{F}$ ).

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE November 2000		3. REPORT TYPE AND DATES COVERED Technical Memorandum
4. TITLE AND SUBTITLE Computer Programs for Calculating the Isentropic Flow Properties for Mixtures of R-134a and Air			5. FUNDING NUMBERS  WU 522-31-21-05	
6. AUTHOR(S) Raymond G. Kvaternik				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  NASA Langley Research Center Hampton, VA 23681-2199			8. PERFORMING ORGANIZATION REPORT NUMBER  L-18028	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER  NASA/TM-2000-210622	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 02      Distribution: Nonstandard Availability: NASA CASI (301) 621-0390			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Three computer programs for calculating the isentropic flow properties of R-134a/air mixtures which were developed in support of the heavy gas conversion of the Langley Transonic Dynamics Tunnel (TDT) from dichlorodifluoromethane (R-12) to 1,1,1,2 tetrafluoroethane (R-134a) are described. The first program calculates the Mach number and the corresponding flow properties when the total temperature, total pressure, static pressure, and mole fraction of R-134a in the mixture are given. The second program calculates tables of isentropic flow properties for a specified set of free-stream Mach numbers given the total pressure, total temperature, and mole fraction of R-134a. Real-gas effects are accounted for in these programs by treating the gases comprising the mixture as both thermally and calorically imperfect. The third program is a specialized version of the first program in which the gases are thermally perfect. It was written to provide a simpler computational alternative to the first program in those cases where real-gas effects are not important. The theory and computational procedures underlying the programs are summarized, the equations used to compute the flow quantities of interest are given, and sample calculated results that encompass the operating conditions of the TDT are shown.				
14. SUBJECT TERMS R-134a; Wind tunnel flow properties; Real-gas equations; Compressible flow relations; Isentropic flow; Gas mixtures; Computer codes for mixtures of real gases			15. NUMBER OF PAGES  127	
			16. PRICE CODE A07	
17. SECURITY CLASSIFICATION REPORT Unclassified	18. SECURITY CLASSIFICATION PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL	